References

[1] A.K. Agrawala and S.K. Tripathi. On an exponential server with general cyclic arrivals. *Acta Inf.*, 18(3):319–334, 1982.

[2] B. Allen. On the costs of optimal and near-optimal binary search trees. *Acta Inf.*, 18(3):255–263, 1982.

[3] S.O. Anderson and R.C. Backhouse. An alternative implementation of an insertion-only recovery technique. *Acta Inf.*, 18(3):289–298, 1982.

[4] Jean-Pierre Banâtre, Patrice Frison, and Patrice Quinton. A network for the detection of words in continuous speech. *Acta Inf.*, 18(4):431–448, 1982/83.

[5] D.J. Brown, B.S. Baker, and H.P. Katseff. Lower bounds for on-line two-dimensional packing algorithms. *Acta Inf.*, 18(2):207–225, 1982.

[6] M. Broy and M. Wirsing. Partial abstract types. *Acta Inf.*, 18(1):47–64, 1982.

[7] T.A. Budd and D. Angluin. Two notions of correctness and their relation to testing. *Acta Inf.*, 18(1):31–45, 1982.

[8] L.R. Carter. Further analysis of code generation for a single register machine. *Acta Inf.*, 18(2):135–147, 1982.

[9] K. Culik II, J. Gruska, and A. Salomaa. Systolic automata for vlsi on balanced trees. *Acta Inf.*, 18(4):335–344, 1983.

[10] R.B.K. Dewar, S.M. Merritt, and M. Sharir. Some modified algorithms for dijkstra's longest upsequence problem. *Acta Inf.*, 18(1):1–15, 1982.

[11] O. Eriksen and J. Staunstrup. Concurrent algorithms for root searching. *Acta Inf.*, 18(4):361–376, 1983.

[12] G.W. Ernst, J.K. Navlakha, and W.F. Ogden. Verification of programs with procedure-type parameters. *Acta Inf.*, 18(2):149–169, 1982.

[13] C. Frougny, J. Sakarovitch, and E. Valkema. On the hotz group of a context-free grammar. *Acta Inf.*, 18(1):109–115, 1982.

[14] H. Langmaack. On termination problems for finitely interpreted algol-like programs. *Acta Inf.*, 18(1):79–108, 1982.

[15] J. Leguy. Saturated languages and decreasing cones, bifaithful languages and bifaithful cones. *Acta Inf.*, 18(1):65–78, 1982.

[16] Philippe Nain. Task scheduling between two homogeneous processors. *Acta Inf.*, 18(4):449–466, 1983.

[17] N. Nakatsu, Y. Kambayashi, and S. Yajima. A longest common subsequence algorithm suitable for similar text strings. *Acta Inf.*, 18(2):171–179, 1982.

[18] J.-M. Nicolas. Logic for improving integrity checking in relational data bases. *Acta Inf.*, 18(3):227–253, 1982.

[19] F. Nielson. A denotational framework for data flow analysis. *Acta Inf.*, 18(3):265–287, 1982.

[20] A. Pettorossi and R.M. Burstall. Deriving very efficient algorithms for evaluating linear recurrence relations using the program transformation technique. *Acta Inf.*, 18(2):181–206, 1982.

[21] R.J. Ramirez, F.W. Tompa, and J.I. Munro. Optimum reorganization points for arbitrary database costs. *Acta Inf.*, 18(1):17–30, 1982.

[22] W. Reisig. Deterministic buffer synchronization of sequential processes. *Acta Inf.*, 18(2):117–134, 1982.

[23] Giora Slutzki. Finite state relational programs. *Acta Inf.*, 18(4):393–409, 1982/83.

[24] K.J. Supowit and E.M. Reingold. The complexity of drawing trees nicely. *Acta Inf.*, 18(4):377–392, 1983. see Erratum in Acta Inf., Vol. 40, 2004, No. 8, 603-607.

[25] J. van Leeuwen and M.H. Overmars. Stratified balanced search trees. *Acta Inf.*, 18(4):345–359, 1983.

[26] K. Winklmann. On the complexity of some problems concerning the use of procedures. i. *Acta Inf.*, 18(3):299–318, 1982.