References

[1] N.M. Amato. Finding a closest visible vertex pair between two polygons. *Algorithmica*, 14:183–201, 1995.

[2] N.M. Amato and F.P. Preparata. A time-optimal parallel algorithm for three-dimensional convex hulls. *Algorithmica*, 14:169–182, 1995.

[3] M.J. Atallah, D.Z. Chen, and D.T. Lee. An optimal algorithm for shortest paths on weighted interval and circular-arc graphs, with applications. *Algorithmica*, 14:429–441, 1995.

[4] R.B. Borie. Generation of polynomial-time algorithms for some optimization problems on tree-decomposable graphs. *Algorithmica*, 14:123–137, 1995.

[5] D. Breslauer and Z. Galil. Finding all periods and initial palindromes of a string in parallel. *Algorithmica*, 14:355–366, 1995.

[6] L. Cai and D. Corneil. Isomorphic tree spanner problems. *Algorithmica*, 14:138–153, 1995.

[7] Yui-Bin Chen and D.J. Ierardi. The complexity of oblivious plans for orienting and distinguishing polygonal parts. *Algorithmica*, 14:367–397, 1995.

[8] B.S. Chlebus, K. Diks, and M. Kowaluk. $o(\log \log n)$-time integer geometry on the crcw pram. *Algorithmica*, 14(1):52–69, 1995.

[9] Seung-Hak Choi, Sung Yong Shin, and Kyung-Yong Chwa. Characterizing and recognizing the visibility graph of a funnel-shaped polygon. *Algorithmica*, 14(1):27–51, 1995.

[10] Shuo-Yan Chou and T.C. Woo. A linear-time algorithm for constructing a circular visibility diagram. *Algorithmica*, 14:203–228, 1995.

[11] P. Dietz, K. Mehlhorn, R. Raman, and C. Uhrig. Lower bounds for set intersection queries. *Algorithmica*, 14:154–168, 1995.

[12] B.R. Donald and P.G. Xavier. Provably good approximation algorithms for optimal kinodynamic planning for cartesian robots and open-chain manipulators. *Algorithmica*, 14:480–530, 1995.

[13] B.R. Donald and P.G. Xavier. Provably good approximation algorithms for optimal kinodynamic planning: Robots with decoupled dynamics bounds. *Algorithmica*, 14:443–479, 1995.

[14] S.A. Goldman and R.H. Sloan. Can pac learning algorithms tolerate random attribute noise? *Algorithmica*, 14(1):70–84, 1995.

[15] Ming-Yang Kao, Shang-Hua Teng, and K. Toyama. An optimal parallel algorithm for planar cycle separators. *Algorithmica*, 14:398–408, 1995.

[16] S. Khuller, B. Raghavachari, and N. Young. Balancing minimum spanning trees and shortest-path trees. *Algorithmica*, 14:305–321, 1995.

[17] J.R. Knight and E.W. Myers. Approximate regular expression pattern matching with concave gap penalties. *Algorithmica*, 14(1):85–121, 1995.

[18] T. Leighton, F. Makedon, and I.G. Tollis. A $2n-2$ step algorithm for routing in an $n \times n$ array with constant-size queues. *Algorithmica*, 14:291–304, 1995.

[19] A. Lingas, A. Maheshwari, and J.-R. Sack. Optimal parallel algorithms for rectilinear link-distance problems. *Algorithmica*, 14:261–289, 1995.

[20] R.M. McConnell. An $o(n^2)$ incremental algorithm for modular decomposition of graphs and 2-structures. *Algorithmica*, 14:229–248, 1995.

[21] W. Panny and H. Prodinger. Bottom-up mergesort — a detailed analysis. *Algorithmica*, 14:340–354, 1995.

[22] S. Schuierer and D. Wood. Staircase visibility and computation of kernels. *Algorithmica*, 14(1):1–26, 1995.

[23] S. Subramanian, R. Tamassia, and J.S. Vitter. An efficient parallel algorithm for shortest paths in planar layered digraphs. *Algorithmica*, 14:322–339, 1995.

[24] E. Ukkonen. On-line construction of suffix trees. *Algorithmica*, 14:249–260, 1995.

[25] A.C.-C. Yao. Minimean optimal key arrangements in hash tables. *Algorithmica*, 14:409–428, 1995.