References

[1] S. Alstrup, P.W. Lauridsen, and M. Thorup. Generalized dominators for structured programs. *Algorithmica*, 27:244–253, 2000.

[2] B. Aspvall, A. Proskurowski, and J.A. Telle. Memory requirements for table computations in partial k-tree algorithms. *Algorithmica*, 27:382–394, 2000.

[3] C.L. Bajaj and A.V. Royappa. Parameterization in finite precision. *Algorithmica*, 27(1):100–114, 2000.

[4] R. Bar-Yehuda. One for the price of two: A unified approach for approximating covering problems. *Algorithmica*, 27(2):131–144, 2000.

[5] H.L. Bodlaender. Introduction. *Algorithmica*, 27:209–211, 2000.

[6] H. Brönnimann and M. Yvinec. Efficient exact evaluation of signs of determinants. *Algorithmica*, 27(1):21–56, 2000.

[7] C. Burnikel, R. Fleischer, K. Mehlhorn, and S. Schirra. A strong and easily computable separation bound for arithmetic expressions involving radicals. *Algorithmica*, 27(1):87–99, 2000.

[8] S. Chaudhuri and C.D. Zaroliagis. Shortest paths in digraphs of small treewidth — part i: Sequential algorithms. *Algorithmica*, 27:212–226, 2000.

[9] A. Dessmark, A. Lingas, and A. Proskurowski. Faster algorithms for subgraph isomorphism of k-connected partial k-trees. *Algorithmica*, 27:337–347, 2000.

[10] D. Eppstein. Diameter and treewidth in minor-closed graph families. *Algorithmica*, 27:275–291, 2000.

[11] S. Fortune. Introduction. *Algorithmica*, 27(1):1–4, 2000.

[12] A. Gupta, D. Kaller, and T. Shermer. Linear-time algorithms for partial k-tree complements. *Algorithmica*, 27:254–274, 2000.

[13] N. Guttman-Beck and R. Hassin. Approximation algorithms for minimum k-cut. *Algorithmica*, 27(2):198–207, 2000.

[14] T. Hagerup. Dynamic algorithms for graphs of bounded treewidth. *Algorithmica*, 27:292–315, 2000.

[15] D. Kaller. Definability equals recognizability of partial 3-trees and k-connected partial k-trees. *Algorithmica*, 27:348–381, 2000.

[16] S. Kapoor and H. Ramesh. An algorithm for enumerating all spanning trees of a directed graph. *Algorithmica*, 27(2):120–130, 2000.

[17] C. Lucet, J.-F. Manouvrier, and J. Carlier. Evaluating network reliability and 2-edge-connected reliability in linear time for bounded pathwidth graphs. *Algorithmica*, 27:316–336, 2000.

[18] V.J. Milenkovic. Shortest path geometric rounding. *Algorithmica*, 27(1):57–86, 2000.

[19] G. Navarro, E.F. Barbosa, R. Baeza-Yates, W. Cunto, and N. Ziviani. Binary searching with nonuniform costs and its application to text retrieval. *Algorithmica*, 27(2):145–169, 2000.

[20] S.-L. Peng, M.-T. Ko, C.-W. Ho, T.-s. Hsu, and C.Y. Tang. Graph searching on some subclasses of chordal graphs. *Algorithmica*, 27:395–426, 2000.

[21] G. Sajith and S. Saxena. Optimal sublogarithmic time parallel algorithms on rooted forests. *Algorithmica*, 27(2):187–197, 2000.

[22] E. Schömer, J. Sellen, M. Teichmann, and Chee Yap. Smallest enclosing cylinders. *Algorithmica*, 27(2):170–186, 2000.

[23] K. Sugihara, M. Iri, H. Inagaki, and T. Imai. Topology-oriented implementation — an approach to robust geometric algorithms. *Algorithmica*, 27(1):5–20, 2000.

[24] X. Zhou, K. Fuse, and T. Nishizeki. A linear algorithm for finding $[g, f]$-colorings of partial k-trees. *Algorithmica*, 27:227–243, 2000.