References

[1] T. Akutsu, K. Onizuka, and M. Ishikawa. Rapid protein fragment search using hash functions based on the fourier transform. *Bioinformatics*, 13(4):357–364, 1997.

[2] P. Aloy, J. Cedano, B. Oliva, F.X. Aviles, and E. Querol. "transmem": A neural network implemented in excel spreadsheets for predicting transmembrane domains of proteins. *Bioinformatics*, 13(3):231–234, 1997.

[3] J.S. Amthor. Calculation of daylength. *Bioinformatics*, 13(4):479–480, 1997.

[4] M. Andrade, G. Casari, A. de Daruvar, C. Sander, R. Schneider, J. Tamames, A. Valencia, and C. Ouzounis. Sequence analysis of the methanococcus jannaschii genome and the prediction of protein function. *Bioinformatics*, 13(4):481–483, 1997.

[5] A.G. Bachinsky, A.A. Yarigin, E.H. Guseva, V.A. Kulichkov, and L.P. Nizolenko. A bank of protein family patterns for rapid identification of possible functions of amino acid sequences. *Bioinformatics*, 13(2):115–122, 1997.

[6] W. Bains. Hexanucleotide frequency database. *Bioinformatics*, 13(1):107–108, 1997.

[7] C. Barrett, R. Hughey, and K. Karplus. Scoring hidden markov models. *Bioinformatics*, 13(2):191–199, 1997.

[8] I. Belyi and P.A. Pevzner. Software for dna sequencing by hybridization. *Bioinformatics*, 13(2):205–210, 1997.

[9] V. Biaudet, F. Samson, and P. Bessieres. Micado — a network-oriented database for microbial genomes. *Bioinformatics*, 13(4):431–438, 1997.

[10] J. Blazewicz, J. Kaczmarek, M. Kasprzak, W.T. Markiewicz, and J. Weglarz. Sequential and parallel algorithms for dna sequencing. *Bioinformatics*, 13(2):151–158, 1997.

[11] K.M. Chao, J. Zhang, J. Ostell, and W. Miller. A tool for aligning very similar dna sequences. *Bioinformatics*, 13(1):75–80, 1997.

[12] G. Chelvanayagam and S. Easteal. Correlating patterns in alignments of polymorphic sequences with experimental assays. *Bioinformatics*, 13(1):13–22, 1997.

[13] Q.K. Chen, G.Z. Hertz, and G.D. Stormo. Promfd 1.0: A computer program that predicts eukaryotic pol ii promoters using strings and imd matrices. *Bioinformatics*, 13(1):29–35, 1997.

[14] C. Chevalet, J. Gouzy, and M. SanCristobal-Gaudy. Regional assignment of genetic markers using a somatic cell hybrid panel: A www interactive program available for the pig genome. *Bioinformatics*, 13(1):69–73, 1997.

[15] L. Cocea. Search the human cdna database at tigr. *Bioinformatics*, 13(2):201–204, 1997.

[16] K.M. Currey and B.A. Shapiro. Secondary structure computer prediction of the poliovirus 5' non-coding region is improved by a genetic algorithm. *Bioinformatics*, 13(1):1–12, 1997.

[17] E. Depiereux, G. Baudoux, P. Briffeuil, I. Reginster, X. de Bolle, C. Vinals, and E. Feytmans. Match-box server: A multiple sequence alignment tool placing emphasis on reliability. *Bioinformatics*, 13(3):249–256, 1997.

[18] J. Dopazo. A new index to find regions showing an unexpected variability or conservation in sequence alignments. *Bioinformatics*, 13(3):313–317, 1997.

[19] P.A. Doris, A. Hayward-Lester, and Sr. Hays J.K. Q-rt-pcr: Data analysis software for measurement of gene expression by competitive rt-pcr. *Bioinformatics*, 13(6):587–591, 1997.

[20] P. Durand, L. Canard, and J.P. Mornon. Visual blast and visual fasta: Graphic workbenches for interactive analysis of full blast and fasta outputs under microsoft windows 95/nt. *Bioinformatics*, 13(4):407–413, 1997.

[21] L. Ehrlich, C. Munkel, G. Chirico, and J. Langowski. A brownian dynamics model for the chromatin fiber. *Bioinformatics*, 13(3):271–279, 1997.

[22] D. Fenyo. A software tool for the analysis of mass spectrometric disulfide mapping experiments. *Bioinformatics*, 13(6):617–618, 1997.

[23] A. Fiser, Z. Dosztanyi, and I. Simon. The role of long-range interactions in defining the secondary structure of proteins is overestimated. *Bioinformatics*, 13(3):297–301, 1997.

[24] Jr. Forsythe, R.G., P.D. Karp, and M.L. Mavrovouniotis. Estimation of equilibrium constants using automated group contribution methods. *Bioinformatics*, 13(5):537–543, 1997.

[25] K. Frech, P. Dietze, and T. Werner. Consinspector 3.0: New library and enhanced functionality. *Bioinformatics*, 13(1):109–110, 1997.

[26] K. Frech, K. Quandt, and T. Werner. Software for the analysis of dna sequence elements of transcription. *Bioinformatics*, 13(1):89–97, 1997.

[27] A.S. Frolov, I.S. Pika, and A.M. Eroshkin. Promsed: Protein multiple sequence editor for windows 3.11/95. *Bioinformatics*, 13(3):243–248, 1997.

[28] R. Fuchs. Grouper — creation of marker sets for multiplexed genotyping. *Bioinformatics*, 13(3):239–241, 1997.

[29] R.W. Gill, T.C. Hodgman, C.B. Littler, M.D. Oxer, D.S. Montgomery, S. Taylor, and P. Sanseau. A new dynamic tool to perform assembly of expressed sequence tags (ests). *Bioinformatics*, 13(4):453–457, 1997.

[30] E. Glemet and J.J. Codani. Lassap, a large scale sequence comparison package. *Bioinformatics*, 13(2):137–143, 1997.

[31] S. Goldberg, P. Ferrand, N.Q. Nguyen, J.F. Boisvieux, and S. Hazout. Bi-dimensional scaling map (bds-map): An approach for building large genetic maps. *Bioinformatics*, 13(5):497–508, 1997.

[32] J. Gorodkin, L.J. Heyer, S. Brunak, and G.D. Stormo. Displaying the information contents of structural rna alignments: The structure logos. *Bioinformatics*, 13(6):583–586, 1997.

[33] J. Gouzy, P. Eugene, E.A. Greene, D. Kahn, and F. Corpet. Xdom, a graphical tool to analyse domain arrangements in any set of protein sequences. *Bioinformatics*, 13(6):601–608, 1997.

[34] N.C. Grassly, J. Adachi, and A. Rambaut. Pseq-gen: An application for the monte carlo simulation of protein sequence evolution along phylogenetic trees. *Bioinformatics*, 13(5):559–560, 1997.

[35] J.A. Grice, R. Hughey, and D. Speck. Reduced space sequence alignment. *Bioinformatics*, 13(1):45–53, 1997.

[36] W. Gronwald, R.F. Boyko, and B.D. Sykes. Gsc: A graphical program for nmr chemical shift comparison. *Bioinformatics*, 13(5):557–558, 1997.

[37] W.N. Grundy, T.L. Bailey, C.P. Elkan, and M.E. Baker. Meta-meme: Motif-based hidden markov models of protein families. *Bioinformatics*, 13(4):397–406, 1997.

[38] P. Guerdoux-Jamet and D. Lavenier. Samba: Hardware accelerator for biological sequence comparison. *Bioinformatics*, 13(6):609–615, 1997.

[39] H. Hegyi, J.M. Lai, and P. Bork. The sequence alerting server — a new web server. *Bioinformatics*, 13(6):619–620, 1997.

[40] J.H. Hofmeyr and A. Cornish-Bowden. The reversible hill equation: How to incorporate cooperative enzymes into metabolic models. *Bioinformatics*, 13(4):377–385, 1997.

[41] R.W. Hooft, C. Sander, and G. Vriend. Objectively judging the quality of a protein structure from a ramachandran plot. *Bioinformatics*, 13(4):425–430, 1997.

[42] C. Hoogland and C. Biemont. Drosoposon: A knowledge base on chromosomal localization of transposable element insertions in drosophila. *Bioinformatics*, 13(1):61–68, 1997.

[43] M. Ito, Y. Matsuo, and K. Nishikawa. Prediction of protein secondary structure using the 3d-1d compatibility algorithm. *Bioinformatics*, 13(4):415–424, 1997.

[44] A.S. Ivanov, A.B Rumjantsev, V.S. Skvortsov, and A.I. Archakov. Onix: An interactive pc program for the examination of protein 3d structure from pdb. *Bioinformatics*, 13(1):111–113, 1997.

[45] I. Jonassen. Efficient discovery of conserved patterns using a pattern graph. *Bioinformatics*, 13(5):509–522, 1997.

[46] H. Kato and Y. Takahashi. Ss3d-p2: A three dimensional substructure search program for protein motifs based on secondary structure elements. *Bioinformatics*, 13(6):593–600, 1997.

[47] R.D. King, M. Saqi, R. Sayle, and M.J. Sternberg. Dsc: Public domain protein secondary structure predication. *Bioinformatics*, 13(4):473–474, 1997.

[48] E.V. Korotkov, M.A. Korotkova, and J.S. Tulko. Latent sequence periodicity of some oncogenes and dna-binding protein genes. *Bioinformatics*, 13(1):37–44, 1997.

[49] G. Labesse, N. Colloc'h, J. Pothier, and J.P. Mornon. P-sea: A new efficient assignment of secondary structure from c alpha trace of proteins. *Bioinformatics*, 13(3):291–295, 1997.

[50] A.S. Law and D.W. Burt. Two applications to facilitate the viewing of database search result files on the macintosh. *Bioinformatics*, 13(6):623–624, 1997.

[51] S. Lay and D. Bray. A computer program for the analysis of protein complex formation. *Bioinformatics*, 13(4):439–444, 1997.

[52] E. Lorenz, S. Leeton, and R.J. Owen. A simple method for sizing large fragments of bacterial dna separated by pfge. *Bioinformatics*, 13(4):485–486, 1997.

[53] R.R. Mallios. An iterative algorithm for converting a class ii mhc binding motif into a quantitative predictive model. *Bioinformatics*, 13(3):211–215, 1997.

[54] G.S. Miller and R. Fuchs. Post-processing of blast results using databases of clustered sequences. *Bioinformatics*, 13(1):81–87, 1997.

[55] R. Mott. Est_genome: A program to align spliced dna sequences to unspliced genomic dna. *Bioinformatics*, 13(4):477–478, 1997.

[56] P.M. Nadkarni. Mapdiff: Determining differences between two genomic maps. *Bioinformatics*, 13(3):217–225, 1997.

[57] J. Panek and J. Vohradsky. Object-oriented developmental environment for image-analysis applications: Implementation for 2d gel electrophoretogram analysis. *Bioinformatics*, 13(3):257–262, 1997.

[58] S. Panzer, L. Cooley, and P.L. Miller. Using explicitly represented biological relationships for database navigation and searching via the world-wide web. *Bioinformatics*, 13(3):281–290, 1997.

[59] F. Pazos, O. Olmea, and A. Valencia. A graphical interface for correlated mutations and other protein structure prediction methods. *Bioinformatics*, 13(3):319–321, 1997.

[60] W.R. Pearson. Identifying distantly related protein sequences. *Bioinformatics*, 13(4):325–332, 1997.

[61] A. Rambaut and N.C. Grassly. Seq-gen: An application for the monte carlo simulation of dna sequence evolution along phylogenetic trees. *Bioinformatics*, 13(3):235–238, 1997.

[62] A. Rambaut, P.H. Harvey, and S. Nee. End-epi: An application for inferring phylogenetic and population dynamical processes from molecular sequences. *Bioinformatics*, 13(3):303–306, 1997.

[63] E. Rivals, O. Delgrange, J.P. Delahaye, M. Dauchet, M.O. Delorme, A. Henaut, and E. Ollivier. Detection of significant patterns by compression algorithms: The case of approximate tandem repeats in dna sequences. *Bioinformatics*, 13(2):131–136, 1997.

[64] M.G. Roberts, D.A. Phoenix, and A.R. Pewsey. An algorithm for the detection of surface-active alpha helices with the potential to anchor proteins at the membrane interface. *Bioinformatics*, 13(1):99–106, 1997.

[65] J.P. Rolland, P. Bon, and D. Thomas. Macs: Automatic counting of objects based on shape recognition. *Bioinformatics*, 13(5):563–564, 1997.

[66] B. Rost and S. O'Donoghue. Sisyphus and prediction of protein structure. *Bioinformatics*, 13(4):345–356, 1997.

[67] J. Rozas and R. Rozas. Dnasp version 2.0: A novel software package for extensive molecular population genetics analysis. *Bioinformatics*, 13(3):307–311, 1997.

[68] A.A. Salamov and V.V. Solovyev. Recognition of 3'-processing sites of human mrna precursors. *Bioinformatics*, 13(1):23–28, 1997.

[69] S.L. Salzberg. A method for identifying splice sites and translational start sites in eukaryotic mrna. *Bioinformatics*, 13(4):365–376, 1997.

[70] J. Schafer and M. Schoniger. Distree: A tool for estimating genetic distances between aligned dna sequences. *Bioinformatics*, 13(4):445–451, 1997.

[71] D.B. Searls. Linguistic approaches to biological sequences. *Bioinformatics*, 13(4):333–344, 1997.

[72] B.A. Shapiro and J.C. Wu. Predicting rna h-type pseudoknots with the massively parallel genetic algorithm. *Bioinformatics*, 13(4):459–471, 1997.

[73] I.N. Shindyalov and P.E. Bourne. Protein data representation and query using optimized data decomposition. *Bioinformatics*, 13(5):487–496, 1997.

[74] B. Shomer. Embl sequence submission system — an object-oriented approach to developing interactive data collection systems through the www. *Bioinformatics*, 13(1):55–60, 1997.

[75] B. Shomer. Seqalert — a daily sequence alertness server for the embl and swissprot databases. *Bioinformatics*, 13(5):545–547, 1997.

[76] T. Sicheritz-Ponten. Biowish: A molecular biology command extension to tcl/tk. *Bioinformatics*, 13(6):621–622, 1997.

[77] T.M. Smith, C. Abajian, and L. Hood. Hopper: Software for automating data tracking and flow in dna sequencing. *Bioinformatics*, 13(2):175–182, 1997.

[78] C. Soderlund, I. Longden, and R. Mott. Fpc: A system for building contigs from restriction fingerprinted clones. *Bioinformatics*, 13(5):523–535, 1997.

[79] J. Stoye, V. Moulton, and A.W. Dress. Dca: An efficient implementation of the divide-and-conquer approach to simultaneous multiple sequence alignment. *Bioinformatics*, 13(6):625–626, 1997.

[80] S. Tiwari, S. Ramachandran, A. Bhattacharya, S. Bhattacharya, and R. Ramaswamy. Prediction of probable genes by fourier analysis of genomic sequences. *Bioinformatics*, 13(3):263–270, 1997.

[81] H. Toh. Introduction of a distance cut-off into structural alignment by the double dynamic programming algorithm. *Bioinformatics*, 13(4):387–396, 1997.

[82] L.I. Toldo. Jambw 1.1: Java-based molecular biologists' workbench. *Bioinformatics*, 13(4):475–476, 1997.

[83] Y. Tsukamoto, K. Takiguchi, K. Satou, E. Furuichi, T. Takagi, and S. Kuhara. Application of a deductive database system to search for topological and similar three-dimensional structures in protein. *Bioinformatics*, 13(2):183–190, 1997.

[84] Y. van de Peer and R. de Wachter. Construction of evolutionary distance trees with treecon for windows: Accounting for variation in nucleotide substitution rate among sites. *Bioinformatics*, 13(3):227–230, 1997.

[85] R. Varon, F. Garcia-Sevilla, M. Garcia-Moreno, F. Garcia-Canovas, R. Peyro, and R.G. Duggleby. Computer program for the equations describing the steady state of enzyme reactions. *Bioinformatics*, 13(2):159–167, 1997.

[86] Y. Wada, K. Inoue, K. Ohga, and H. Yasue. Software tool for gene mapping: granch. *Bioinformatics*, 13(3):323–324, 1997.

[87] H. Williams and J. Zobel. Compression of nucleotide databases for fast searching. *Bioinformatics*, 13(5):549–554, 1997.

[88] L. Winder, M. Lefley, and B. Smith. A key for freshwater invertebrates using fuzzy logic. *Bioinformatics*, 13(2):169–174, 1997.

[89] D.S. Wishart, S. Fortin, D.R. Woloschuk, W. Wong, T. Rosborough, G. van Domselaar, J. Schaeffer, and D. Szafron. A platform-independent graphical user interface for seqsee and xalign. *Bioinformatics*, 13(5):561–562, 1997.

[90] J.H. Woods and H.M. Sauro. Elasticities in metabolic control analysis: Algebraic derivation of simplified expressions. *Bioinformatics*, 13(2):123–130, 1997.

[91] A. Wozniak. Using video-oriented instructions to speed up sequence comparison. *Bioinformatics*, 13(2):145–150, 1997.

[92] Z. Yang. Paml: A program package for phylogenetic analysis by maximum likelihood. *Bioinformatics*, 13(5):555–556, 1997.

[93] C. Zhang and A.K. Wong. A genetic algorithm for multiple molecular sequence alignment. *Bioinformatics*, 13(6):565–581, 1997.