References

[1] Thomas Abeel, Thibault Helleputte, Yves Van de Peer, Pierre Dupont, and Yvan Saeys. Robust biomarker identification for cancer diagnosis with ensemble feature selection methods. *Bioinformatics*, 26(3):392–398, 2010.

[2] Haley J. Abel, Eric J. Duncavage, Nils Becker, Jon R. Armstrong, Vincent J. Magrini, and John D. Pfeifer. Slope: A quick and accurate method for locating non-snp structural variation from targeted next-generation sequence data. *Bioinformatics*, 26(21):2684–2688, 2010.

[3] Delali A. Adiamah, Julia Handl, and Jean-Marc Schwartz. Streamlining the construction of large-scale dynamic models using generic kinetic equations. *Bioinformatics*, 26(10):1324–1331, 2010.

[4] Raphael B.M. Aggio, Katya Ruggiero, and Silas Granato Villas-Bôas. Pathway activity profiling (papi): From the metabolite profile to the metabolic pathway activity. *Bioinformatics*, 26(23):2969–2976, 2010.

[5] Eneko Agirre, Aitor Soroa, and Mark Stevenson. Graph-based word sense disambiguation of biomedical documents. *Bioinformatics*, 26(22):2889–2896, 2010.

[6] Yang Ai-Jun and Song Xin-Yuan. Bayesian variable selection for disease classification using gene expression data. *Bioinformatics*, 26(2):215–222, 2010.

[7] Gökmen Altay and Frank Emmert-Streib. Revealing differences in gene network inference algorithms on the network level by ensemble methods. *Bioinformatics*, 26(14):1738–1744, 2010.

[8] André Altmann, Laura Toloşi, Oliver Sander, and Thomas Lengauer. Permutation importance: A corrected feature importance measure. *Bioinformatics*, 26(10):1340–1347, 2010.

[9] Carson M. Andorf, Carolyn J. Lawrence, Lisa C. Harper, Mary L. Schaeffer, Darwin A. Campbell, and Taner Z. Sen. The locus lookup tool at maizegdb: Identification of genomic regions in maize by integrating sequence information with and genetic maps. *Bioinformatics*, 26(3):434–436, 2010.

[10] Danny Arends, Pjotr Prins, Ritsert C. Jansen, and Karl W. Broman. R/qtl: High-throughput multiple qtl mapping. *Bioinformatics*, 26(23):2990–2992, 2010.

[11] Erik Arner, Yoshihide Hayashizaki, and Carsten O. Daub. Ngsview: An extensible open source editor for next-generation sequencing data. *Bioinformatics*, 26(1):125–126, 2010.

[12] Manimozhiyan Arumugam, Eoghan D. Harrington, Konrad U. Foerstner, Jeroen Raes, and Peer Bork. Smashcommunity: A metagenomic annotation and analysis tool. *Bioinformatics*, 26(23):2977–2978, 2010.

[13] Manonmani Arunachalam, Karthik Jayasurya, Pavel Tomancak, and Uwe Ohler. An alignment-free method to identify candidate orthologous enhancers in multiple drosophila genomes. *Bioinformatics*, 26(17):2109–2115, 2010.

[14] H.M. Shahzad Asif, Matthew D. Rolfe, Jeff Green, Neil D. Lawrence, Magnus Rattray, and Guido Sanguinetti. Tfinfer: A tool for probabilistic inference of transcription factor activities. *Bioinformatics*, 26(20):2635–2636, 2010.

[15] Nikolas Askitis and Ranjan Sinha. Repmaestro: Scalable repeat detection on disk-based genome sequences. *Bioinformatics*, 26(19):2368–2374, 2010.

[16] T.K. Attwood, D.B. Kell, P. McDermott, J. Marsh, S.R. Pettifer, and D. Thorne. Utopia documents: Linking scholarly literature with research data. *Bioinformatics*, 26(18):568–574, 2010.

[17] Ozgun Babur, Ugur Dogrusoz, Emek Demir, and Chris Sander. Chibe: Interactive visualization and manipulation of biopax pathway models. *Bioinformatics*, 26(3):429–431, 2010.

[18] Pantelis G. Bagos, Elisanthi P. Nikolaou, Theodore D. Liakopoulos, and Konstantinos D. Tsirigos. Combined prediction of tat and sec signal peptides with hidden markov models. *Bioinformatics*, 26(22):2811–2817, 2010.

[19] Jie Bai, Junrong Wang, Feng Xue, Jingsong Li, Lijing Bu, Junming Hu, Gang Xu, Qiyu Bao, Guoping Zhao, Xiaoming Ding, Jie Yan, and

Jinyu Wu. protf: A comprehensive data and phylogenomics resource for prokaryotic transcription factors. *Bioinformatics*, 26(19):2493–2495, 2010.

[20] Michael Baitaluk and Julia Ponomarenko. Semantic integration of data on transcriptional regulation. *Bioinformatics*, 26(13):1651–1661, 2010.

[21] Pedro J. Ballester and John B.O. Mitchell. A machine learning approach to predicting protein-ligand binding affinity with applications to molecular docking. *Bioinformatics*, 26(9):1169–1175, 2010.

[22] Susanne Balzer, Ketil Malde, Anders Lanzén, Animesh Sharma, and Inge Jonassen. Characteristics of 454 pyrosequencing data — enabling realistic simulation with flowsim. *Bioinformatics*, 26(18):420–425, 2010. see Corrigendum in Bioinformatics, Vol. 27, 2011, No. 15, 2117-2117.

[23] Ipsita Banerjee, Spandan Maiti, Natesh Parashurama, and Martin Yarmush. An integer programming formulation to identify the sparse network architecture governing differentiation of embryonic stem cells. *Bioinformatics*, 26(10):1332–1339, 2010.

[24] Vikas Bansal. A statistical method for the detection of variants from next-generation resequencing of dna pools. *Bioinformatics*, 26(12):318–324, 2010.

[25] Yoseph Barash, Benjamin J. Blencowe, and Brendan J. Frey. Model-based detection of alternative splicing signals. *Bioinformatics*, 26(12):325–333, 2010.

[26] David T. Barkan, Daniel R. Hostetter, Sami Mahrus, Ursula Pieper, James A. Wells, Charles S. Craik, and Andrej Sali. Prediction of protease substrates using sequence and structure features. *Bioinformatics*, 26(14):1714–1722, 2010.

[27] Nenad Bartonicek and Anton J. Enright. Sylarray: A web server for automated detection of mirna effects from expression data. *Bioinformatics*, 26(22):2900–2901, 2010.

[28] Gregory Batt, Michel Page, Irene Cantone, Gregor Goessler, Pedro Monteiro, and Hidde de Jong. Efficient parameter search for qualitative models of regulatory networks using symbolic model checking. *Bioinformatics*, 26(18):603–610, 2010.

[29] Christian Baudet, Claire Lemaitre, Zanoni Dias, Christian Gautier, Eric Tannier, and Marie-France Sagot. Cassis: Detection of genomic rearrangement breakpoints. *Bioinformatics*, 26(15):1897–1898, 2010.

[30] Anna Bauer-Mehren, Michael Rautschka, Ferran Sanz, and Laura I. Furlong. Disgenet: A cytoscape plugin to visualize, integrate, search and analyze gene-disease networks. *Bioinformatics*, 26(22):2924–2926, 2010.

[31] Christian Baumgartner, Gregory D. Lewis, Michael Netzer, Bernhard Pfeifer, and Robert E. Gerszten. A new data mining approach for profiling and categorizing kinetic patterns of metabolic biomarkers after myocardial injury. *Bioinformatics*, 26(14):1745–1751, 2010.

[32] Jumamurat R. Bayjanov, Roland J. Siezen, and Sacha A.F.T. van Hijum. Pancghweb: A web tool for genotype calling in pangenome cgh data. *Bioinformatics*, 26(9):1256–1257, 2010.

[33] Nathaniel Beagley, Kelly G. Stratton, and Bobbie-Jo M. Webb-Robertson. Vibe 2.0: Visual integration for bayesian evaluation. *Bioinformatics*, 26(2):280–282, 2010.

[34] John E. Beaver, Murat Taşan, Francis D. Gibbons, Weidong Tian, Timothy R. Hughes, and Frederick P. Roth. Funcbase: A resource for quantitative gene function annotation. *Bioinformatics*, 26(14):1806–1807, 2010.

[35] Daniela Beisser, Gunnar W. Klau, Thomas Dandekar, Tobias Müller, and Marcus T. Dittrich. Bionet: An r-package for the functional analysis of biological networks. *Bioinformatics*, 26(8):1129–1130, 2010.

[36] Christian Bender, Frauke Henjes, Holger Fröhlich, Stefan Wiemann, Ulrike Korf, and Tim Beißbarth. Dynamic deterministic effects propagation networks: Learning signalling pathways from longitudinal protein array data. *Bioinformatics*, 26(18):596–602, 2010.

[37] H. Paul Benton, Elizabeth J. Want, and Timothy M.D. Ebbels. Correction of mass calibration gaps in liquid chromatography-mass spectrometry metabolomics data. *Bioinformatics*, 26(19):2488–2489, 2010.

[38] Sivan Bercovici, Christopher Meek, Ydo Wexler, and Dan Geiger. Estimating genome-wide ibd sharing from snp data via an efficient hidden markov model of ld with application to gene mapping. *Bioinformatics*, 26(12):175–182, 2010.

[39] Francois Berenger, Camille Coti, and Kam Y.J. Zhang. Par: A parallel and distributed job crusher. *Bioinformatics*, 26(22):2918–2919, 2010.

[40] Marco Biasini, Valerio Mariani, Jürgen Haas, Stefan Scheuber, Andreas D. Schenk, Torsten Schwede, and Ansgar Philippsen. Openstructure: A flexible software framework for computational structural biology. *Bioinformatics*, 26(20):2626–2628, 2010.

[41] J.R. Bilbao-Castro, C.O.S. Sorzano, I. García, and J.J. Fernández. Xmsf: Structure-preserving noise reduction and pre-segmentation in microscope tomography. *Bioinformatics*, 26(21):2786–2787, 2010.

[42] Thomas W. Binsl, David J.C. Alders, Jaap Heringa, A.B. Johan Groeneveld, and Johannes H.G.M. van Beek. Computational quantification of metabolic fluxes from a single isotope snapshot: Application to an animal biopsy. *Bioinformatics*, 26(5):653–660, 2010.

[43] Ambarish Biswas, Kalyan C. Mynampati, Shivshankar Umashankar, Sheela Reuben, Gauri Parab, Raghuraj Rao, Velayutham S. Kannan, and Sanjay Swarup. Metdat: A modular and workflow-based free online pipeline for mass spectrometry data processing, analysis and interpretation. *Bioinformatics*, 26(20):2639–2640, 2010.

[44] Jari Björne, Filip Ginter, Sampo Pyysalo, Jun'ichi Tsujii, and Tapio Salakoski. Complex event extraction at pubmed scale. *Bioinformatics*, 26(12):382–390, 2010.

[45] Daniel Blankenberg, Assaf Gordon, Gregory Von Kuster, Nathan Coraor, James Taylor, Anton Nekrutenko, and the Galaxy Team. Manipulation of fastq data with galaxy. *Bioinformatics*, 26(14):1783–1785, 2010.

[46] Jasmina Bogojeska, Steffen Bickel, André Altmann, and Thomas Lengauer. Dealing with sparse data in predicting outcomes of hiv combination therapies. *Bioinformatics*, 26(17):2085–2092, 2010.

[47] James K. Bonfield and Andrew Whitwham. Gap5 — editing the billion fragment sequence assembly. *Bioinformatics*, 26(14):1699–1703, 2010.

[48] Eric Bonnet, Ying He, Kenny Billiau, and Yves Van de Peer. Tapir, a web server for the prediction of plant microrna targets, including target mimics. *Bioinformatics*, 26(12):1566–1568, 2010.

[49] Eric Bonnet, Tom Michoel, and Yves Van de Peer. Prediction of a gene regulatory network linked to prostate cancer from gene expression, microrna and clinical data. *Bioinformatics*, 26(18):638–644, 2010.

[50] Remco R. Bouckaert. Densitree: Making sense of sets of phylogenetic trees. *Bioinformatics*, 26(10):1372–1373, 2010.

[51] Anne-Laure Boulesteix. Over-optimism in bioinformatics research. *Bioinformatics*, 26(3):437–439, 2010.

[52] Guillaume Bouvier, Nathalie Evrard-Todeschi, Jean-Pierre Girault, and Gildas Bertho. Automatic clustering of docking poses in virtual screening process using self-organizing map. *Bioinformatics*, 26(1):53–60, 2010.

[53] Frédéric Boyer, Bruno Besson, Guillaume Baptist, Jérôme Izard, Corinne Pinel, Delphine Ropers, Johannes Geiselmann, and Hidde de Jong. Wellreader: A matlab program for the analysis of fluorescence and luminescence reporter gene data. *Bioinformatics*, 26(9):1262–1263, 2010.

[54] Serdar Bozdag, Aiguo Li, Stefan Wuchty, and Howard A. Fine. Fastmedusa: A parallelized tool to infer gene regulatory networks. *Bioinformatics*, 26(14):1792–1793, 2010.

[55] Sebastian Briesemeister, Jörg Rahnenführer, and Oliver Kohlbacher. Going from where to why — interpretable prediction of protein subcellular localization. *Bioinformatics*, 26(9):1232–1238, 2010.

[56] Dumitru Brinza, Matthew Schultz, Glenn Tesler, and Vineet Bafna. Rapid detection of gene-gene interactions in genome-wide association studies. *Bioinformatics*, 26(22):2856–2862, 2010.

[57] Sylvain Brohée, Roland Barriot, and Yves Moreau. Biological knowledge bases using wikis: Combining the flexibility of wikis with the structure of databases. *Bioinformatics*, 26(17):2210–2211, 2010.

[58] Helena Brunel, Joan-Josep Gallardo-Chacón, Alfonso Buil, Montserrat Vallverdú, José Manuel Soria, Pere Caminal, and Alexandre Perera. Miss: A non-linear methodology based on mutual information for genetic association studies in both population and sib-pairs analysis. *Bioinformatics*, 26(15):1811–1818, 2010.

[59] Jr. Bryant, Douglas W., Rongkun Shen, Henry D. Priest, Weng-Keen Wong, and Todd C. Mockler. Supersplat — spliced rna-seq alignment. *Bioinformatics*, 26(12):1500–1505, 2010.

[60] Joshua Buckner, Justin Wilson, Mark Seligman, Brian Athey, Stanley Watson, and Fan Meng. The gputools package enables gpu computing in r. *Bioinformatics*, 26(1):134–135, 2010.

[61] Ingo Bulla, Anne-Kathrin Schultz, Fabian Schreiber, Ming Zhang, Thomas Leitner, Bette Korber, Burkhard Morgenstern, and Mario Stanke. Hiv classification using the coalescent theory. *Bioinformatics*, 26(11):1409–1415, 2010.

[62] William S. Bush, Scott M. Dudek, and Marylyn D. Ritchie. Visualizing snp statistics in the context of linkage disequilibrium using ld-plus. *Bioinformatics*, 26(4):578–579, 2010.

[63] Fabian A. Buske, Mikael Bodén, Denis C. Bauer, and Timothy L. Bailey. Assigning roles to dna regulatory motifs using comparative genomics. *Bioinformatics*, 26(7):860–866, 2010.

[64] Violeta Calian and Jason C. Hsu. Response to letter to the editor by philip good on to permute or not to permute. *Bioinformatics*, 26(17):2215–2215, 2010.

[65] M. Luz Calle, Víctor Urrea, Núria Malats, and Kristel Van Steen. mbmdr: An r package for exploring gene-gene interactions associated with binary or quantitative traits. *Bioinformatics*, 26(17):2198–2199, 2010.

[66] Isabelle Callebaut and Jean-Paul Mornon. Lotus, a new domain associated with small rna pathways in the germline. *Bioinformatics*, 26(9):1140–1144, 2010.

[67] Stephen Cammer and Jr. Carter, Charles W. Six rossmannoid folds, including the class i aminoacyl-trna synthetases, share a partial core with the anti-codon-binding domain of a class ii aminoacyl-trna synthetase. *Bioinformatics*, 26(6):709–714, 2010.

[68] Carlo Vittorio Cannistraci, Timothy Ravasi, Franco Maria Montevecchi, Trey Ideker, and Massimo Alessio. Nonlinear dimension reduction and clustering by minimum curvilinearity unfold neuropathic pain and tissue embryological classes. *Bioinformatics*, 26(18):531–539, 2010.

[69] Kim-Anh Lê Cao, Emmanuelle Meugnier, and Geoffrey J. McLachlan. Integrative mixture of experts to combine clinical factors and gene markers. *Bioinformatics*, 26(9):1192–1198, 2010.

[70] Yiqun Cao, Tao Jiang, and Thomas Girke. Accelerated similarity searching and clustering of large compound sets by geometric embedding and locality sensitive hashing. *Bioinformatics*, 26(7):953–959, 2010.

[71] J. Gregory Caporaso, Kyle Bittinger, Frederic D. Bushman, Todd Z. DeSantis, Gary L. Andersen, and Rob Knight. Pynast: A flexible tool for aligning sequences to a template alignment. *Bioinformatics*, 26(2):266–267, 2010.

[72] Pablo Carbonell and Jean-Loup Faulon. Molecular signatures-based prediction of enzyme promiscuity. *Bioinformatics*, 26(16):2012–2019, 2010.

[73] Brian Carrillo, Corey Yanofsky, Sylvie Laboissiere, Robert Nadon, and Robert E. Kearney. Methods for combining peptide intensities to estimate relative protein abundance. *Bioinformatics*, 26(1):98–103, 2010.

[74] Hyrum D. Carroll, Maricel G. Kann, Sergey L. Sheetlin, and John L. Spouge. Threshold average precision (tap-k): A measure of retrieval designed for bioinformatics. *Bioinformatics*, 26(14):1708–1713, 2010.

[75] Benilton S. Carvalho and Rafael A. Irizarry. A framework for oligonucleotide microarray preprocessing. *Bioinformatics*, 26(19):2363–2367, 2010.

[76] Benilton S. Carvalho, Thomas A. Louis, and Rafael A. Irizarry. Quantifying uncertainty in genotype calls. *Bioinformatics*, 26(2):242–249, 2010.

[77] Paulo C. Carvalho, Xuemei Han, Tao Xu, Daniel Cociorva, Maria da Gloria Carvalho, Valmir C. Barbosa, and John R. Yates III. Xdia: Improving on the label-free data-independent analysis. *Bioinformatics*, 26(6):847–848, 2010.

[78] Tim Carver, Ulrike Böhme, Thomas D. Otto, Julian Parkhill, and Matthew Berriman. Bamview: Viewing mapped read alignment data in the context of the reference sequence. *Bioinformatics*, 26(5):676–677, 2010.

[79] Emmet Caulfield and Andreas Hellander. Cellmc — a multiplatform model compiler for the cell broadband engine and x86. *Bioinformatics*, 26(3):426–428, 2010.

[80] Florian Centler, Christoph Kaleta, Pietro Speroni di Fenizio, and Peter Dittrich. A parallel algorithm to compute chemical organizations in biological networks. *Bioinformatics*, 26(14):1788–1789, 2010.

[81] Monica Chagoyen and Florencio Pazos. Quantifying the biological significance of gene ontology biological processes — implications for the analysis of systems-wide data. *Bioinformatics*, 26(3):378–384, 2010.

[82] Sidhartha Chaudhury, Sergey Lyskov, and Jeffrey J. Gray. Pyrosetta: A script-based interface for implementing molecular modeling algorithms using rosetta. *Bioinformatics*, 26(5):689–691, 2010.

[83] Dijun Chen, Yijun Meng, Xiaoxia Ma, Chuanzao Mao, Youhuang Bai, Junjie Cao, Haibin Gu, Ping Wu, and Ming Chen. Small rnas in

angiosperms: Sequence characteristics, distribution and generation. *Bioinformatics*, 26(11):1391–1394, 2010.

[84] Kuan-Bei Chen and Yu Zhang. A varying threshold method for chip peak-calling using multiple sources of information. *Bioinformatics*, 26(18):504–510, 2010.

[85] Li Chen, Jianhua Xuan, Rebecca B. Riggins, Yue Wang, Eric P. Hoffman, and Robert Clarke. Multilevel support vector regression analysis to identify condition-specific regulatory networks. *Bioinformatics*, 26(11):1416–1422, 2010.

[86] Liang Chen. A link between h3k27me3 mark and exon length in the gene promoters of pluripotent and differentiated cells. *Bioinformatics*, 26(7):855–859, 2010.

[87] Ming-Huei Chen and Qiong Yang. Gwaf: An r package for genome-wide association analyses with family data. *Bioinformatics*, 26(4):580–581, 2010.

[88] Xiaoyu Chen, Michael M. Hoffman, Jeff A. Bilmes, Jay R. Hesselberth, and William S. Noble. A dynamic bayesian network for identifying protein-binding footprints from single molecule-based sequencing data. *Bioinformatics*, 26(12):334–342, 2010.

[89] Zhi-Zhong Chen and Lusheng Wang. Hybridnet: A tool for constructing hybridization networks. *Bioinformatics*, 26(22):2912–2913, 2010.

[90] Tiejun Cheng, Yanli Wang, and Stephen H. Bryant. Investigating the correlations among the chemical structures, bioactivity profiles and molecular targets of small molecules. *Bioinformatics*, 26(22):2881–2888, 2010.

[91] François Chevenet, Olivier Croce, Maxime Hebrard, Richard Christen, and Vincent Berry. Scriptree: Scripting phylogenetic graphics. *Bioinformatics*, 26(8):1125–1126, 2010.

[92] Tsung-Han Chiang, David Hsu, and Jean-Claude Latombe. Markov dynamic models for long-timescale protein motion. *Bioinformatics*, 26(12):269–277, 2010.

[93] Wei-Yao Chou, Wei-I Chou, Tun-Wen Pai, Shu-Chuan Lin, Ting-Ying Jiang, Chuan-Yi Tang, and Margaret Dah-Tsyr Chang. Feature-incorporated alignment based ligand-binding residue prediction for carbohydrate-binding modules. *Bioinformatics*, 26(8):1022–1028, 2010.

[94] Wen-Chi Chou, Yanbin Yin, and Ying Xu. Golgip: Prediction of golgi-resident proteins in plants. *Bioinformatics*, 26(19):2464–2465, 2010.

[95] Tianjiao Chu, Kimberly Bunce, W. Allen Hogge, and David G. Peters. Statistical considerations for digital approaches to non-invasive fetal genotyping. *Bioinformatics*, 26(22):2863–2866, 2010.

[96] Cheng-Long Chuang, Jia-Hong Wu, Chi-Sheng Cheng, and Grace S. Shieh. Webpare: Web-computing for inferring genetic or transcriptional interactions. *Bioinformatics*, 26(4):582–584, 2010.

[97] Li-Yeh Chuang, Jui-Hung Tsai, and Cheng-Hong Yang. Ppo: Predictor for prokaryotic operons. *Bioinformatics*, 26(24):3127–3128, 2010.

[98] Daniel Chubb, Benjamin R. Jefferys, Michael J.E. Sternberg, and Lawrence A. Kelley. Sequencing delivers diminishing returns for homology detection: Implications for mapping the protein universe. *Bioinformatics*, 26(21):2664–2671, 2010.

[99] Taane G. Clark, Susana G. Campino, Elisa Anastasi, Sarah Auburn, Yik Y. Teo, Kerrin Small, Kirk A. Rockett, Dominic P. Kwiatkowski, and Christopher C. Holmes. A bayesian approach using covariance of single nucleotide polymorphism data to detect differences in linkage disequilibrium patterns between groups of individuals. *Bioinformatics*, 26(16):1999–2003, 2010.

[100] Jennifer Clarke, Pearl Seo, and Bertrand Clarke. Statistical expression deconvolution from mixed tissue samples. *Bioinformatics*, 26(8):1043–1049, 2010.

[101] Kendell Clement, Nathaniel Gustafson, Amanda Berbert, Hyrum Carroll, Christopher Merris, Ammon Olsen, Mark Clement, Quinn Snell, Jared Allen, and Randall J. Roper. Pathgen: A transitive gene pathway generator. *Bioinformatics*, 26(3):423–425, 2010.

[102] Nathan L. Clement, Quinn Snell, Mark J. Clement, Peter C. Hollenhorst, Jahnvi Purwar, Barbara J. Graves, Bradley R. Cairns, and W. Evan Johnson. The gnumap algorithm: Unbiased probabilistic mapping of oligonucleotides from next-generation sequencing. *Bioinformatics*, 26(1):38–45, 2010.

[103] Luis Pedro Coelho, Tao Peng, and Robert F. Murphy. Quantifying the distribution of probes between subcellular locations using unsupervised pattern unmixing. *Bioinformatics*, 26(12):7–12, 2010.

[104] Ofir Cohen, Haim Ashkenazy, Frida Belinky, Dorothée Huchon, and Tal Pupko. Gloome: Gain loss mapping engine. *Bioinformatics*, 26(22):2914–2915, 2010.

[105] M.T. Cooling, V. Rouilly, G. Misirli, J. Lawson, T. Yu, J. Hallinan, and A. Wipat. Standard virtual biological parts: A repository of modular modeling components for synthetic biology. *Bioinformatics*, 26(7):925–931, 2010.

[106] Eduardo Corel, Florian Pitschi, and Burkhard Morgenstern. A min-cut algorithm for the consistency problem in multiple sequence alignment. *Bioinformatics*, 26(8):1015–1021, 2010.

[107] Gergely Csaba and Ralf Zimmer. Vorescore — fold recognition improved by rescoring of protein structure models. *Bioinformatics*, 26(18):474–481, 2010.

[108] Gábor Csárdi, Zoltán Kutalik, and Sven Bergmann. Modular analysis of gene expression data with r. *Bioinformatics*, 26(10):1376–1377, 2010.

[109] Miklós Csűrös. Count: Evolutionary analysis of phylogenetic profiles with parsimony and likelihood. *Bioinformatics*, 26(15):1910–1912, 2010.

[110] Xinping Cui, Na You, Thomas Girke, Richard Michelmore, and Allen Van Deynze. Single feature polymorphism detection using recombinant inbred line microarray expression data. *Bioinformatics*, 26(16):1983–1989, 2010.

[111] Tobias Czauderna, Christian Klukas, and Falk Schreiber. Editing, validating and translating of sbgn maps. *Bioinformatics*, 26(18):2340–2341, 2010.

[112] Joseph O. Dada, Irena Spasić, Norman W. Paton, and Pedro Mendes. Sbrml: A markup language for associating systems biology data with models. *Bioinformatics*, 26(7):932–938, 2010.

[113] Daniel Dahlmeier and Hwee Tou Ng. Domain adaptation for semantic role labeling in the biomedical domain. *Bioinformatics*, 26(8):1098–1104, 2010.

[114] Adrian V. Dalca, Stephen M. Rumble, Samuel Levy, and Michael Brudno. Varid: A variation detection framework for color-space and letter-space platforms. *Bioinformatics*, 26(12):343–349, 2010.

[115] Phuong Dao, Recep Colak, Raheleh Salari, Flavia Moser, Elai Davicioni, Alexander Schönhuth, and Martin Ester. Inferring cancer subnetwork markers using density-constrained biclustering. *Bioinformatics*, 26(18):625–631, 2010.

[116] N. Darzentas, A. Bousios, V. Apostolidou, and A.S. Tsaftaris. Masive: Mapping and analysis of sirevirus elements in plant genome sequences. *Bioinformatics*, 26(19):2452–2454, 2010.

[117] Nikos Darzentas. Circoletto: Visualizing sequence similarity with circos. *Bioinformatics*, 26(20):2620–2621, 2010.

[118] Sourav Das, Michael P. Krein, and Curt M. Breneman. Pesdserv: A server for high-throughput comparison of protein binding site surfaces. *Bioinformatics*, 26(15):1913–1914, 2010.

[119] Saheli Datta, Raquel Prado, Abel Rodríguez, and Ananías A. Escalante. Characterizing molecular adaptation: A hierarchical approach to assess the selective influence of amino acid properties. *Bioinformatics*, 26(22):2818–2825, 2010.

[120] Robert P. Davey, Stephen A. James, Jo Dicks, and Ian N. Roberts. Turnip: Tracking unresolved nucleotide polymorphisms in large hard-to-assemble regions of repetitive dna sequence. *Bioinformatics*, 26(22):2908–2909, 2010.

[121] Ryan Day, Kristin P. Lennox, David B. Dahl, Marina Vannucci, and Jerry W. Tsai. Characterizing the regularity of tetrahedral packing motifs in protein tertiary structure. *Bioinformatics*, 26(24):3059–3066, 2010.

[122] Wayne Delport, Art F.Y. Poon, Simon D.W. Frost, and Sergei L. Kosakovsky Pond. Datamonkey 2010: A suite of phylogenetic analysis tools for evolutionary biology. *Bioinformatics*, 26(19):2455–2457, 2010.

[123] Ozgur Demir-Kavuk, Henning Riedesel, and Ernst-Walter Knapp. Exploring classification strategies with the coepra 2006 contest. *Bioinformatics*, 26(5):603–609, 2010.

[124] Joshua C. Denny, Marylyn D. Ritchie, Melissa A. Basford, Jill M. Pulley, Lisa Bastarache, Kristin Brown-Gentry, Deede Wang, Dan R. Masys, Dan M. Roden, and Dana C. Crawford. Phewas: Demonstrating the feasibility of a phenome-wide scan to discover gene-disease associations. *Bioinformatics*, 26(9):1205–1210, 2010.

[125] Ninad Dewal, Matthew L. Freedman, Thomas LaFramboise, and Itsik Pe'er. Power to detect selective allelic amplification in genome-wide scans of tumor data. *Bioinformatics*, 26(4):518–528, 2010.

[126] Pietro Di Lena, Piero Fariselli, Luciano Margara, Marco Vassura, and Rita Casadio. Fast overlapping of protein contact maps by alignment of eigenvectors. *Bioinformatics*, 26(18):2250–2258, 2010.

[127] Paolo Di Tommaso, Miquel Orobitg, Fernando Guirado, Fernado Cores, Toni Espinosa, and Cedric Notredame. Cloud-coffee: Implementation of a parallel consistency-based multiple alignment algorithm in the t-coffee package and its benchmarking on the amazon elastic-cloud. *Bioinformatics*, 26(15):1903–1904, 2010.

[128] Abdoulaye Banire Diallo, Vladimir Makarenkov, and Mathieu Blanchette. Ancestors 1.0: A web server for ancestral sequence reconstruction. *Bioinformatics*, 26(1):130–131, 2010.

[129] Daria V. Dibrova, Michael Y. Galperin, and Armen Y. Mulkidjanian. Characterization of the n-atpase, a distinct, laterally transferred na^+-

translocating form of the bacterial f-type membrane atpase. *Bioinformatics*, 26(12):1473–1476, 2010.

[130] Ivan Dimitrov, Panayot Garnev, Darren R. Flower, and Irini Doytchinova. Epitop — a proteochemometric tool for mch class ii binding prediction. *Bioinformatics*, 26(16):2066–2068, 2010.

[131] Rezarta Islamaj Doğan and Zhiyong Lu. Click-words: Learning to predict document keywords from a user perspective. *Bioinformatics*, 26(21):2767–2775, 2010.

[132] Kevin C. Dorff, Nyasha Chambwe, Marko Srdanovic, and Fabien Campagne. Bdval: Reproducible large-scale predictive model development and validation in high-throughput datasets. *Bioinformatics*, 26(19):2472–2473, 2010.

[133] Arnaud Droit, Charles Cheung, and Raphael Gottardo. rmat — an r/bioconductor package for analyzing chip-chip experiments. *Bioinformatics*, 26(5):678–679, 2010.

[134] Daniela Dunkler, Michael Schemper, and Georg Heinze. Gene selection in microarray survival studies under possibly non-proportional hazards. *Bioinformatics*, 26(6):784–790, 2010.

[135] Chris Duran, Zoran Boskovic, Michael Imelfort, Jacqueline Batley, Nicholas A. Hamilton, and David Edwards. Cmap3d: A 3d visualization tool for comparative genetic maps. *Bioinformatics*, 26(2):273–274, 2010.

[136] Oleh Dzyubachyk, Jeroen Essers, Wiggert A. van Cappellen, Céline Baldeyron, Akiko Inagaki, Wiro J. Niessen, and Erik Meijering. Automated analysis of time-lapse fluorescence microscopy images: From live cell images to intracellular foci. *Bioinformatics*, 26(19):2424–2430, 2010.

[137] Robert C. Edgar. Search and clustering orders of magnitude faster than blast. *Bioinformatics*, 26(19):2460–2461, 2010.

[138] Krystian Eitner, Uwe Koch, Tomasz Gawęda, and Jędrzej Marciniak. Statistical distribution of amino acid sequences: A proof of darwinian evolution. *Bioinformatics*, 26(23):2933–2935, 2010.

[139] Anne-Katrin Emde, Marcel Grunert, David Weese, Knut Reinert, and Silke R. Sperling. Microrazers: Rapid alignment of small rna reads. *Bioinformatics*, 26(1):123–124, 2010.

[140] Florian Erhard and Ralf Zimmer. Classification of ncrnas using position and size information in deep sequencing data. *Bioinformatics*, 26(18):426–432, 2010.

[141] Timo Erkkilä, Saara Lehmusvaara, Pekka Ruusuvuori, Tapio Visakorpi, Ilya Shmulevich, and Harri Lähdesmäki. Probabilistic analysis of gene expression measurements from heterogeneous tissues. *Bioinformatics*, 26(20):2571–2577, 2010.

[142] Mounir Errami, Zhaohui Sun, Angela C. George, Tara C. Long, Michael A. Skinner, Jonathan D. Wren, and Harold R. Garner. Identifying duplicate content using statistically improbable phrases. *Bioinformatics*, 26(11):1453–1457, 2010.

[143] Cesim Erten and Melih Sözdinler. Improving performances of suboptimal greedy iterative biclustering heuristics via localization. *Bioinformatics*, 26(20):2594–2600, 2010.

[144] Gregory Ewing and Joachim Hermisson. Msms: A coalescent simulation program including recombination, demographic structure and selection at a single locus. *Bioinformatics*, 26(16):2064–2065, 2010.

[145] Rick A. Fasani and Michael A. Savageau. Automated construction and analysis of the design space for biochemical systems. *Bioinformatics*, 26(20):2601–2609, 2010.

[146] Karoline Faust, Pierre Dupont, Jérôme Callut, and Jacques van Helden. Pathway discovery in metabolic networks by subgraph extraction. *Bioinformatics*, 26(9):1211–1218, 2010.

[147] Andrew D. Fernandes and Gregory B. Gloor. Corrigendum to "mutual information is critically dependent on prior assumptions: Would the correct estimate of mutual information please identify itself?". *Bioinformatics*, 26(19):2500–2500, 2010. Originally in Bioinformatics, Vol. 26, 2010, No. 9, 1135-1139.

[148] Andrew D. Fernandes and Gregory B. Gloor. Mutual information is critically dependent on prior assumptions: Would the correct estimate of mutual information please identify itself? *Bioinformatics*, 26(9):1135–1139, 2010. see Corrigendum in Bioinformatics, Vol. 26, 2010, No. 19, 2500-2500.

[149] Elana J. Fertig, Jie Ding, Alexander V. Favorov, Giovanni Parmigiani, and Michael F. Ochs. Cogaps: An r/c++ package to identify patterns and biological process activity in transcriptomic data. *Bioinformatics*, 26(21):2792–2793, 2010.

[150] Hiram A. Firpi, Duygu Ucar, and Kai Tan. Discover regulatory dna elements using chromatin signatures and artificial neural network. *Bioinformatics*, 26(13):1579–1586, 2010.

[151] Julia D. Fischer, Gemma L. Holliday, and Janet M. Thornton. The cofactor database: Organic cofactors in enzyme catalysis. *Bioinformatics*, 26(19):2496–2497, 2010.

[152] Marc Fiume, Vanessa Williams, Andrew Brook, and Michael Brudno. Savant: Genome browser for high-throughput sequencing data. *Bioinformatics*, 26(16):1938–1944, 2010.

[153] Aris Floratos, Kenneth Smith, Zhou Ji, John Watkinson, and Andrea Califano. geworkbench: An open source platform for integrative genomics. *Bioinformatics*, 26(14):1779–1780, 2010.

[154] Lope A. Flórez, Christoph R. Lammers, Raphael Michna, and Jörg Stülke. Cellpublisher: A web platform for the intuitive visualization and sharing of metabolic, signalling and regulatory pathways. *Bioinformatics*, 26(23):2997–2999, 2010.

[155] Christine Fong, Dennis C. Ko, Michael Wasnick, Matthew Radey, Samuel I. Miller, and Mitchell Brittnacher. Gwas analyzer: Integrating genotype, phenotype and public annotation data for genome-wide association study analysis. *Bioinformatics*, 26(4):560–564, 2010.

[156] Thomas Forth, Glenn A. McConkey, and David R. Westhead. Metnetmaker: A free and open-source tool for the creation of novel metabolic networks in sbml format. *Bioinformatics*, 26(18):2352–2353, 2010.

[157] Robert A. Forties and Ralf Bundschuh. Modeling the interplay of single-stranded binding proteins and nucleic acid secondary structure. *Bioinformatics*, 26(1):61–67, 2010.

[158] Karl Frank, Markus Gruber, and Manfred J. Sippl. Cops benchmark: Interactive analysis of database search methods. *Bioinformatics*, 26(4):574–575, 2010.

[159] Jr. Freeman, Thomas C. and William C. Wimley. A highly accurate statistical approach for the prediction of transmembrane β-barrels. *Bioinformatics*, 26(16):1965–1974, 2010.

[160] Caroline C. Friedel, Stefanie Kaufmann, Lars Dölken, and Ralf Zimmer. Halo — a java framework for precise transcript half-life determination. *Bioinformatics*, 26(9):1264–1266, 2010.

[161] Yitzhak Friedman, Guy Naamati, and Michal Linial. Mirror: A combinatorial analysis web tool for ensembles of micrornas and their targets. *Bioinformatics*, 26(15):1920–1921, 2010.

[162] Sebastian Fröhler and Christoph Dieterich. Accusa — accurate snp calling on draft genomes. *Bioinformatics*, 26(10):1364–1365, 2010.

[163] Menachem Fromer and Michal Linial. Exposing the co-adaptive potential of protein-protein interfaces through computational sequence design. *Bioinformatics*, 26(18):2266–2272, 2010.

[164] Menachem Fromer, Chen Yanover, Amir Harel, Ori Shachar, Yair Weiss, and Michal Linial. Sprint: Side-chain prediction inference toolbox for multistate protein design. *Bioinformatics*, 26(19):2466–2467, 2010.

[165] André Fujita, Kaname Kojima, Alexandre G. Patriota, João R. Sato, Patricia Severino, and Satoru Miyano. A fast and robust statistical test based on likelihood ratio with bartlett correction to identify granger causality between gene sets. *Bioinformatics*, 26(18):2349–2351, 2010.

[166] Idan Gabdank, Danny Barash, and Edward N. Trifonov. Finestr: A web server for single-base-resolution nucleosome positioning. *Bioinformatics*, 26(6):845–846, 2010.

[167] Raj K. Gaire, James Bailey, Jennifer Bearfoot, Ian G. Campbell, Peter J. Stuckey, and Izhak Haviv. Miragaa — a methodology for finding coordinated effects of microrna expression changes and genome aberrations in cancer. *Bioinformatics*, 26(2):161–167, 2010.

[168] Michal J. Gajda, Irina Tuszynska, Marta Kaczor, Anastasia Yu. Bakulina, and Janusz M. Bujnicki. Filtrest3d: Discrimination of structural models using restraints from experimental data. *Bioinformatics*, 26(23):2986–2987, 2010.

[169] Sergio Gálvez, David Díaz, Pilar Hernández, Francisco J. Esteban, Juan A. Caballero, and Gabriel Dorado. Next-generation bioinformatics: Using many-core processor architecture to develop a web service for sequence alignment. *Bioinformatics*, 26(5):683–686, 2010.

[170] Eric R. Gamazon, Wei Zhang, Anuar Konkashbaev, Shiwei Duan, Emily O. Kistner, Dan L. Nicolae, M. Eileen Dolan, and Nancy J. Cox. Scan: Snp and copy number annotation. *Bioinformatics*, 26(2):259–262, 2010.

[171] Jing Gao, V. Glenn Tarcea, Alla Karnovsky, Barbara R. Mirel, Terry E. Weymouth, Christopher W. Beecher, James D. Cavalcoli, Brian D. Athey, Gilbert S. Omenn, Charles F. Burant, and H.V. Jagadish. Metscape: A cytoscape plug-in for visualizing and interpreting metabolomic data in the context of human metabolic networks. *Bioinformatics*, 26(7):971–973, 2010.

[172] Mu Gao and Jeffrey Skolnick. ialign: A method for the structural comparison of protein-protein interfaces. *Bioinformatics*, 26(18):2259–2265, 2010.

[173] Sergiy O. Garbuzynskiy, Michail Yu. Lobanov, and Oxana V. Galzitskaya. Foldamyloid: A method of prediction of amyloidogenic regions from protein sequence. *Bioinformatics*, 26(3):326–332, 2010.

[174] Miguel García-Remesal, Alejandro Cuevas, David Pérez-Rey, Luis Martín, Alberto Anguita, Diana de la Iglesia, Guillermo de la Calle, José Crespo, and Víctor Maojo. Pubdna finder: A web database linking full-text articles to sequences of nucleic acids. *Bioinformatics*, 26(21):2801–2802, 2010.

[175] Ricard Garcia-Serna, Oleg Ursu, Tudor I. Oprea, and Jordi Mestres. iphace: Integrative navigation in pharmacological space. *Bioinformatics*, 26(7):985–986, 2010.

[176] Steven Gay, Sylvain Soliman, and François Fages. A graphical method for reducing and relating models in systems biology. *Bioinformatics*, 26(18):575–581, 2010.

[177] Pascal Gellert, Katharina Jenniches, Thomas Braun, and Shizuka Uchida. C-it: A knowledge database for tissue-enriched genes. *Bioinformatics*, 26(18):2328–2333, 2010.

[178] Filippo Geraci. A comparison of several algorithms for the single individual snp haplotyping reconstruction problem. *Bioinformatics*, 26(18):2217–2225, 2010.

[179] Noushin Ghaffari, Ivan Ivanov, Xiaoning Qian, and Edward R. Dougherty. A cod-based reduction algorithm for designing stationary control policies on boolean networks. *Bioinformatics*, 26(12):1556–1563, 2010.

[180] Amin Moghaddas Gholami and Kurt Fellenberg. Cross-species common regulatory network inference without requirement for prior gene affiliation. *Bioinformatics*, 26(8):1082–1090, 2010.

[181] Jungsoo Gim, Ho-Shik Kim, Junil Kim, Minsoo Choi, Jeong-Rae Kim, Yeun Jun Chung, and Kwang-Hyun Cho. A system-level investigation into the cellular toxic response mechanism mediated by ahr signal transduction pathway. *Bioinformatics*, 26(17):2169–2175, 2010.

[182] Enrico Glaab, Anaïs Baudot, Natalio Krasnogor, and Alfonso Valencia. Topogsa: Network topological gene set analysis. *Bioinformatics*, 26(9):1271–1272, 2010.

[183] Florian Gnad, Shubin Ren, Chunaram Choudhary, Jürgen Cox, and Matthias Mann. Predicting post-translational lysine acetylation using support vector machines. *Bioinformatics*, 26(13):1666–1668, 2010.

[184] David Golan, Carmit Levy, Brad Friedman, and Noam Shomron. Biased hosting of intronic microrna genes. *Bioinformatics*, 26(8):992–995, 2010.

[185] Johannes Goll, Douglas B. Rusch, David M. Tanenbaum, Mathangi Thiagarajan, Kelvin Li, Barbara A. Methé, and Shibu Yooseph. Metarep: Jcvi metagenomics reports — an open source tool for high-performance comparative metagenomics. *Bioinformatics*, 26(20):2631–2632, 2010.

[186] Alexander Goncearenco and Igor N. Berezovsky. Prototypes of elementary functional loops unravel evolutionary connections between protein functions. *Bioinformatics*, 26(18):497–503, 2010.

[187] Mileidy W. Gonzalez and William R. Pearson. Refprotdom: A protein database with improved domain boundaries and homology relationships. *Bioinformatics*, 26(18):2361–2362, 2010.

[188] Phillip Good. Exchangeable random variables. *Bioinformatics*, 26(17):2214–2214, 2010.

[189] Leo Goodstadt. Ruffus: A lightweight python library for computational pipelines. *Bioinformatics*, 26(21):2778–2779, 2010.

[190] Vanathi Gopalakrishnan, Jonathan L. Lustgarten, Shyam Visweswaran, and Gregory F. Cooper. Bayesian rule learning for biomedical data mining. *Bioinformatics*, 26(5):668–675, 2010.

[191] Eduardo Gorrón, Fausto Rodríguez, Diana Bernal, Luis Miguel Rodriguez-Rojas, Adriana Bernal, Silvia Restrepo, and Joe Tohme. A new method for designing degenerate primers and its use in the identification of sequences in brachiaria showing similarity to apomixis-associated genes. *Bioinformatics*, 26(16):2053–2054, 2010.

[192] Naohisa Goto, Pjotr Prins, Mitsuteru Nakao, Raoul Bonnal, Jan Aerts, and Toshiaki Katayama. Bioruby: Bioinformatics software for the ruby programming language. *Bioinformatics*, 26(20):2617–2619, 2010.

[193] Rodrigo Goya, Mark G.F. Sun, Ryan D. Morin, Gillian Leung, Gavin Ha, Kimberley C. Wiegand, Janine Senz, Anamaria Crisan, Marco A. Marra, Martin Hirst, David Huntsman, Kevin P. Murphy, Sam Aparicio, and Sohrab P. Shah. Snvmix: Predicting single nucleotide variants from next-generation sequencing of tumors. *Bioinformatics*, 26(6):730–736, 2010.

[194] Manfred G. Grabherr, Pamela Russell, Miriah Meyer, Evan Mauceli, Jessica Alföldi, Federica Di Palma, and Kerstin Lindblad-Toh. Genome-wide synteny through highly sensitive sequence alignment: Satsuma. *Bioinformatics*, 26(9):1145–1151, 2010.

[195] Casey S. Greene, Nicholas A. Sinnott-Armstrong, Daniel S. Himmelstein, Paul J. Park, Jason H. Moore, and Brent T. Harris. Multifactor dimensionality reduction for graphics processing units enables genome-wide testing of epistasis in sporadic als. *Bioinformatics*, 26(5):694–695, 2010.

[196] Philip Groth, Ivan Kalev, Ivaylo Kirov, Borislav Traikov, Ulf Leser, and Bertram Weiss. Phenoclustering: Online mining of cross-species phenotypes. *Bioinformatics*, 26(15):1924–1925, 2010.

[197] Yuchun Guo, Georgios Papachristoudis, Robert C. Altshuler, Georg K. Gerber, Tommi S. Jaakkola, David K. Gifford, and Shaun Mahony. Discovering homotypic binding events at high spatial resolution. *Bioinformatics*, 26(24):3028–3034, 2010.

[198] Lionel Guy, Jens Roat Kultima, and Siv G.E. Andersson. genoplotr: Comparative gene and genome visualization in r. *Bioinformatics*, 26(18):2334–2335, 2010.

[199] Iman Hajirasouliha, Fereydoun Hormozdiari, Can Alkan, Jeffrey M. Kidd, Inanc Birol, Evan E. Eichler, and S. Cenk Sahinalp. Detection and characterization of novel sequence insertions using paired-end next-generation sequencing. *Bioinformatics*, 26(10):1277–1283, 2010.

[200] Kousuke Hanada, Kenji Akiyama, Tetsuya Sakurai, Tetsuro Toyoda, Kazuo Shinozaki, and Shin-Han Shiu. sorf finder: A program package to identify small open reading frames with high coding potential. *Bioinformatics*, 26(3):399–400, 2010.

[201] Timothy Hancock, Ichigaku Takigawa, and Hiroshi Mamitsuka. Mining metabolic pathways through gene expression. *Bioinformatics*, 26(17):2128–2135, 2010.

[202] Blaise Hanczar, Jianping Hua, Chao Sima, John Weinstein, Michael Bittner, and Edward R. Dougherty. Small-sample precision of roc-related estimates. *Bioinformatics*, 26(6):822–830, 2010.

[203] Eoghan D. Harrington, Manimozhiyan Arumugam, Jeroen Raes, Peer Bork, and David A. Relman. Smashcell: A software framework for the analysis of single-cell amplified genome sequences. *Bioinformatics*, 26(23):2979–2980, 2010.

[204] Elena Y. Harris, Nadia Ponts, Aleksandr Levchuk, Karine Le Roch, and Stefano Lonardi. Brat: Bisulfite-treated reads analysis tool. *Bioinformatics*, 26(4):572–573, 2010. see Corrigendum in Bioinformatics, Vol. 26, 2010, No. 19, 2499-2499.

[205] Elena Y. Harris, Nadia Ponts, Aleksandr Levchuk, Karine Le Roch, and Stefano Lonardi. Corrigendum to “brat: Bisulfite-treated reads analysis tool”. *Bioinformatics*, 26(19):2499–2499, 2010. Originally in Bioinformatics, Vol. 26, 2010, No. 4, 572-573.

[206] Dan He, Arthur Choi, Knot Pipatsrisawat, Adnan Darwiche, and Eleazar Eskin. Optimal algorithms for haplotype assembly from whole-genome sequence data. *Bioinformatics*, 26(12):183–190, 2010.

[207] Allison P. Heath, George N. Bennett, and Lydia E. Kavraki. Finding metabolic pathways using atom tracking. *Bioinformatics*, 26(12):1548–1555, 2010.

[208] N.L. Heinecke, B.S. Pratt, T. Vaisar, and L. Becker. Pepc: Proteomics software for identifying differentially expressed proteins based on spectral counting. *Bioinformatics*, 26(12):1574–1575, 2010.

[209] Chris Hemmerich, Aaron Buechlein, Ram Podicheti, Kashi V. Revanna, and Qunfeng Dong. An ergatis-based prokaryotic genome annotation web server. *Bioinformatics*, 26(8):1122–1124, 2010.

[210] Bart S. Hendriks and Christopher W. Espelin. Datapflex: A matlab-based tool for the manipulation and visualization of multidimensional datasets. *Bioinformatics*, 26(3):432–433, 2010.

[211] Andrew L. Hipp and Marcial Escudero. Maticce: Mapping transitions in continuous character evolution. *Bioinformatics*, 26(1):132–133, 2010.

[212] Sepp Hochreiter, Ulrich Bodenhofer, Martin Heusel, Andreas Mayr, Andreas Mitterecker, Adetayo Kasim, Tatsiana Khamiakova, Suzy Van Sanden, Dan Lin, Willem Talloen, Luc Bijnens, Hinrich W.H.

Göhlmann, Ziv Shkedy, and Djork-Arné Clevert. Fabia: Factor analysis for bicluster acquisition. *Bioinformatics*, 26(12):1520–1527, 2010.

[213] Stefan Hoehme and Dirk Drasdo. A cell-based simulation software for multi-cellular systems. *Bioinformatics*, 26(20):2641–2642, 2010.

[214] Robert Hoehndorf, Anika Oellrich, and Dietrich Rebholz-Schuhmann. Interoperability between phenotype and anatomy ontologies. *Bioinformatics*, 26(24):3112–3118, 2010.

[215] Michael M. Hoffman, Orion J. Buske, and William Stafford Noble. The genomedata format for storing large-scale functional genomics data. *Bioinformatics*, 26(11):1458–1459, 2010.

[216] Matthew E. Holford, Ekta Khurana, Kei-Hoi Cheung, and Mark Gerstein. Using semantic web rules to reason on an ontology of pseudogenes. *Bioinformatics*, 26(12):71–78, 2010.

[217] Jens Hollunder, Maik Friedel, Martin Kuiper, and Thomas Wilhelm. Dass-gui: A user interface for identification and analysis of significant patterns in non-sequential data. *Bioinformatics*, 26(7):987–989, 2010.

[218] Christian Höner zu Siederdissen and Ivo L. Hofacker. Discriminatory power of rna family models. *Bioinformatics*, 26(18):453–459, 2010.

[219] Sean D. Hooper, Daniel Dalevi, Amrita Pati, Konstantinos Mavromatis, Natalia N. Ivanova, and Nikos C. Kyrpides. Estimating dna coverage and abundance in metagenomes using a gamma approximation. *Bioinformatics*, 26(3):295–301, 2010.

[220] Fereydoun Hormozdiari, Iman Hajirasouliha, Phuong Dao, Faraz Hach, Deniz Yorukoglu, Can Alkan, Evan E. Eichler, and S. Cenk Sahinalp. Next-generation variationhunter: Combinatorial algorithms for transposon insertion discovery. *Bioinformatics*, 26(12):350–357, 2010.

[221] Mark E.T. Horn and Peter M. Waterhouse. Rapid match-searching for gene silencing assessment. *Bioinformatics*, 26(16):1932–1937, 2010.

[222] Matthew Horton, Natacha Bodenhausen, and Joy Bergelson. Marta: A suite of java-based tools for assigning taxonomic status to dna sequences. *Bioinformatics*, 26(4):568–569, 2010.

[223] Jianfei Hu, Jun Wan, Jr. Hackler, Laszlo, Donald J. Zack, and Jiang Qian. Computational analysis of tissue-specific gene networks: Application to murine retinal functional studies. *Bioinformatics*, 26(18):2289–2297, 2010.

[224] Rui Hu, Xing Qiu, and Galina Glazko. A new gene selection procedure based on the covariance distance. *Bioinformatics*, 26(3):348–354, 2010.

[225] Yanhua Hu, Elvira Osuna-Highley, Juchang Hua, Theodore Scott Nowicki, Robert Stolz, Camille McKayle, and Robert F. Murphy. Automated analysis of protein subcellular location in time series images. *Bioinformatics*, 26(13):1630–1636, 2010.

[226] Yin Hu, Kai Wang, Xiaping He, Derek Y. Chiang, Jan F. Prins, and Jinze Liu. A probabilistic framework for aligning paired-end rna-seq data. *Bioinformatics*, 26(16):1950–1957, 2010.

[227] Xing Hua, Han Zhang, Hong Zhang, Yaning Yang, and Anthony Y.C. Kuk. Testing multiple gene interactions by the ordered combinatorial partitioning method in case-control studies. *Bioinformatics*, 26(15):1871–1878, 2010.

[228] Danzhi Huang, Ting Zhou, Karine Lafleur, Cristina Nevado, and Amedeo Caflisch. Kinase selectivity potential for inhibitors targeting the atp binding site: A network analysis. *Bioinformatics*, 26(2):198–204, 2010.

[229] Fenix W.D. Huang, Jing Qin, Christian M. Reidys, and Peter F. Stadler. Target prediction and a statistical sampling algorithm for rna-rna interaction. *Bioinformatics*, 26(2):175–181, 2010.

[230] Liang-Tsung Huang and M. Michael Gromiha. First insight into the prediction of protein folding rate change upon point mutation. *Bioinformatics*, 26(17):2121–2127, 2010.

[231] Wei Huang, Xiaoyi Cao, and Sheng Zhong. Network-based comparison of temporal gene expression patterns. *Bioinformatics*, 26(23):2944–2951, 2010.

[232] Ying Huang, Beifang Niu, Ying Gao, Limin Fu, and Weizhong Li. Cd-hit suite: A web server for clustering and comparing biological sequences. *Bioinformatics*, 26(5):680–682, 2010.

[233] Willy Hugo, Fushan Song, Zeyar Aung, See-Kiong Ng, and Wing-Kin Sung. Slim on diet: Finding short linear motifs on domain interaction interfaces in protein data bank. *Bioinformatics*, 26(8):1036–1042, 2010.

[234] Stacy S. Hung, James Wasmuth, Christopher Sanford, and John Parkinson. Detect — a density estimation tool for enzyme classification and its application to plasmodium falciparum. *Bioinformatics*, 26(14):1690–1698, 2010.

[235] Ilkka Huopaniemi, Tommi Suvitaival, Janne Nikkilä, Matej Orešič, and Samuel Kaski. Multivariate multi-way analysis of multi-source data. *Bioinformatics*, 26(12):391–398, 2010.

[236] Peter Husemann and Jens Stoye. r2cat: Synteny plots and comparative assembly. *Bioinformatics*, 26(4):570–571, 2010.

[237] Natthakan Iam-on, Tossapon Boongoen, and Simon Garrett. Lce: A link-based cluster ensemble method for improved gene expression data analysis. *Bioinformatics*, 26(12):1513–1519, 2010.

[238] E. Iannuccelli, F. Mompart, J. Gellin, Y. Lahbib-Mansais, M. Yerle, and T. Boudier. Nemo: A tool for analyzing gene and chromosome territory distributions from 3d-fish experiments. *Bioinformatics*, 26(5):696–697, 2010.

[239] Ignacio L. Ibarra and Francisco Melo. Interactive software tool to comprehend the calculation of optimal sequence alignments with dynamic programming. *Bioinformatics*, 26(13):1664–1665, 2010.

[240] Aaron Ikin, Carlos Riveros, Pablo Moscato, and Alexandre Mendes. The gene interaction miner: A new tool for data mining contextual information for protein-protein interaction analysis. *Bioinformatics*, 26(2):283–284, 2010.

[241] Royi Itzhack and Yoram Louzoun. Random distance dependent attachment as a model for neural network generation in the caenorhabditis elegans. *Bioinformatics*, 26(5):647–652, 2010.

[242] Zohar Itzhaki, Eyal Akiva, and Hanah Margalit. Preferential use of protein domain pairs as interaction mediators: Order and transitivity. *Bioinformatics*, 26(20):2564–2570, 2010.

[243] Sergii Ivakhno, Tom Royce, Anthony J. Cox, Dirk J. Evers, R. Keira Cheetham, and Simon Tavaré. Cnaseg — a novel framework for identification of copy number changes in cancer from second-generation sequencing data. *Bioinformatics*, 26(24):3051–3058, 2010.

[244] Sergii Ivakhno and Simon Tavaré. Cnanova: A new approach for finding recurrent copy number abnormalities in cancer snp microarray data. *Bioinformatics*, 26(11):1395–1402, 2010.

[245] Katherine J.L. Jackson, Scott Boyd, Bruno A. Gaëta, and Andrew M. Collins. Benchmarking the performance of human antibody gene alignment utilities using a 454 sequence dataset. *Bioinformatics*, 26(24):3129–3130, 2010.

[246] Steffen Jaensch, Markus Decker, Anthony A. Hyman, and Eugene W. Myers. Automated tracking and analysis of centrosomes in early caenorhabditis elegans embryos. *Bioinformatics*, 26(12):13–20, 2010.

[247] Ariel Jaimovich, Ruty Rinott, Maya Schuldiner, Hanah Margalit, and Nir Friedman. Modularity and directionality in genetic interaction maps. *Bioinformatics*, 26(12):228–236, 2010.

[248] Navdeep Jaitly, Marcus A. Brubaker, John L. Rubinstein, and Ryan H. Lilien. A bayesian method for 3d macromolecular structure inference using class average images from single particle electron microscopy. *Bioinformatics*, 26(19):2406–2415, 2010.

[249] Hyunchul Jang, Jinhyun Kim, Sang-Kyun Kim, Chul Kim, Soon-Hee Bae, Anna Kim, Dong-Myung Eom, and Mi-Young Song. Ontology for medicinal materials based on traditional korean medicine. *Bioinformatics*, 26(18):2359–2360, 2010.

[250] Stefan Janssen and Robert Giegerich. Faster computation of exact rna shape probabilities. *Bioinformatics*, 26(5):632–639, 2010.

[251] Monika Jelizarow, Vincent Guillemot, Arthur Tenenhaus, Korbinian Strimmer, and Anne-Laure Boulesteix. Over-optimism in bioinformatics: An illustration. *Bioinformatics*, 26(16):1990–1998, 2010.

[252] Hui Jiang, Fan Wang, Nigel P. Dyer, and Wing Hung Wong. Cisgenome browser: A flexible tool for genomic data visualization. *Bioinformatics*, 26(14):1781–1782, 2010.

[253] Peng Jiang and Mona Singh. Spici: A fast clustering algorithm for large biological networks. *Bioinformatics*, 26(8):1105–1111, 2010.

[254] Bo Jin and Xinghua Lu. Identifying informative subsets of the gene ontology with information bottleneck methods. *Bioinformatics*, 26(19):2445–2451, 2010.

[255] Anika Jöcker, Johanna Sonntag, Frauke Henjes, Frank Götschel, Achim Tresch, Tim Beißbarth, Stefan Wiemann, and Ulrike Korf. Quantproreloaded: Quantitative analysis of microspot immunoassays. *Bioinformatics*, 26(19):2480–2481, 2010.

[256] Frank Johannes, René Wardenaar, Maria Colomé-Tatché, Florence Mousson, Petra de Graaf, Michal Mokry, Victor Guryev, H.Th. Marc Timmers, Edwin Cuppen, and Ritsert C. Jansen. Comparing genome-wide chromatin profiles using chip-chip or chip-seq. *Bioinformatics*, 26(8):1000–1006, 2010.

[257] Marc Johannes, Jan C. Brase, Holger Fröhlich, Stephan Gade, Mathias Gehrmann, Maria Fälth, Holger Sültmann, and Tim Beißbarth. Integration of pathway knowledge into a reweighted recursive feature elimination approach for risk stratification of cancer patients. *Bioinformatics*, 26(17):2136–2144, 2010.

[258] Andrew D. Johnson. An extended iupac nomenclature code for polymorphic nucleic acids. *Bioinformatics*, 26(10):1386–1389, 2010.

[259] Thibaut Jombart, François Balloux, and Stéphane Dray. adephylo: New tools for investigating the phylogenetic signal in biological traits. *Bioinformatics*, 26(15):1907–1909, 2010.

[260] Fabrice Jossinet, Thomas E. Ludwig, and Eric Westhof. Assemble: An interactive graphical tool to analyze and build rna architectures at the 2d and 3d levels. *Bioinformatics*, 26(16):2057–2059, 2010.

[261] Suk Hoon Jung, Bora Hyun, Woo-Hyuk Jang, Hee-Young Hur, and Dong-Soo Han. Protein complex prediction based on simultaneous protein interaction network. *Bioinformatics*, 26(3):385–391, 2010.

[262] Thomas Junier and Evgeny M. Zdobnov. The newick utilities: High-throughput phylogenetic tree processing in the unix shell. *Bioinformatics*, 26(13):1669–1670, 2010.

[263] Ari B. Kahn, Barry R. Zeeberg, Michael C. Ryan, D. Curtis Jamison, David M. Rockoff, Yves Pommier, and John N. Weinstein. Ontogenomic study of the relationship between number of gene splice variants and go categorization. *Bioinformatics*, 26(16):1945–1949, 2010.

[264] Crystal L. Kahn, Borislav H. Hristov, and Benjamin J. Raphael. Parsimony and likelihood reconstruction of human segmental duplications. *Bioinformatics*, 26(18):446–452, 2010.

[265] Matúš Kalaš, Pål Puntervoll, Alexandre Joseph, Edita Bartaševičiūtė, Armin Töpfer, Prabakar Venkataraman, Steve Pettifer, Jan Christian Bryne, Jon Ison, Christophe Blanchet, Kristoffer Rapacki, and Inge Jonassen. Bioxsd: The common data-exchange format for everyday bioinformatics web services. *Bioinformatics*, 26(18):540–546, 2010.

[266] Matan Kalman and Nir Ben-Tal. Quality assessment of protein model-structures using evolutionary conservation. *Bioinformatics*, 26(10):1299–1307, 2010.

[267] Bo-Yeong Kang, Song Ko, and Dae-Won Kim. Sicago: Semi-supervised cluster analysis using semantic distance between gene pairs in gene ontology. *Bioinformatics*, 26(10):1384–1385, 2010.

[268] Yoshinobu Kano, Paul Dobson, Mio Nakanishi, Jun'ichi Tsujii, and Sophia Ananiadou. Text mining meets workflow: Linking u-compare with taverna. *Bioinformatics*, 26(19):2486–2487, 2010.

[269] Kota Kasahara, Kengo Kinoshita, and Toshihisa Takagi. Ligand-binding site prediction of proteins based on known fragment-fragment interactions. *Bioinformatics*, 26(12):1493–1499, 2010.

[270] Tsuyoshi Kato and Nozomi Nagano. Metric learning for enzyme active-site search. *Bioinformatics*, 26(21):2698–2704, 2010.

[271] Yuki Kato, Kengo Sato, Michiaki Hamada, Yoshihide Watanabe, Kiyoshi Asai, and Tatsuya Akutsu. Ractip: Fast and accurate prediction of rna-rna interaction using integer programming. *Bioinformatics*, 26(18):460–466, 2010.

[272] Kazutaka Katoh and Hiroyuki Toh. Parallelization of the mafft multiple sequence alignment program. *Bioinformatics*, 26(15):1899–1900, 2010.

[273] Edward Kawas and Mark D. Wilkinson. Owl:2perl: Creating perl modules from owl class definitions. *Bioinformatics*, 26(18):2357–2358, 2010.

[274] Sebastian Kelm, Jiye Shi, and Charlotte M. Deane. Medeller: Homology-based coordinate generation for membrane proteins. *Bioinformatics*, 26(22):2833–2840, 2010.

[275] Steven W. Kembel, Peter D. Cowan, Matthew R. Helmus, William K. Cornwell, Helene Morlon, David D. Ackerly, Simon P. Blomberg, and Campbell O. Webb. Picante: R tools for integrating phylogenies and ecology. *Bioinformatics*, 26(11):1463–1464, 2010.

[276] Brian Kemper, Takuya Matsuzaki, Yukiko Matsuoka, Yoshimasa Tsuruoka, Hiroaki Kitano, Sophia Ananiadou, and Jun'ichi Tsujii. Pathtext: A text mining integrator for biological pathway visualizations. *Bioinformatics*, 26(12):374–381, 2010.

[277] W.J. Kent, A.S. Zweig, G. Barber, A.S. Hinrichs, and D. Karolchik. Bigwig and bigbed: Enabling browsing of large distributed datasets. *Bioinformatics*, 26(17):2204–2207, 2010.

[278] George Khelashvili, Kevin Dorff, Jufang Shan, Marta Camacho-Artacho, Lucy Skrabanek, Bas Vroling, Michel Bouvier, Lakshmi A. Devi, Susan R. George, Jonathan A. Javitch, Martin J. Lohse, Graeme Milligan, Richard R. Neubig, Krzysztof Palczewski, Marc Parmentier,

Jean-Philippe Pin, Gerrit Vriend, Fabien Campagne, and Marta Filizola. Gpcr-okb: The g protein coupled receptor oligomer knowledge base. *Bioinformatics*, 26(14):1804–1805, 2010.

[279] Steven J. Kiddle, Oliver P.F. Windram, Stuart McHattie, Andrew Mead, Jim Beynon, Vicky Buchanan-Wollaston, Katherine J. Denby, and Sach Mukherjee. Temporal clustering by affinity propagation reveals transcriptional modules in arabidopsis thaliana. *Bioinformatics*, 26(3):355–362, 2010.

[280] Bong-Hyun Kim, Qian Cong, and Nick V. Grishin. Hangout: Generating clean psi-blast profiles for domains with long insertions. *Bioinformatics*, 26(12):1564–1565, 2010.

[281] Changsik Kim, Jiwon Choi, Hyunjin Park, Yunsun Park, Jungsun Park, Taesung Park, Kwanghui Cho, Young Yang, and Sukjoon Yoon. Global analysis of microarray data reveals intrinsic properties in gene expression and tissue selectivity. *Bioinformatics*, 26(14):1723–1730, 2010.

[282] Mingoo Kim, Sung Bum Cho, and Ju Han Kim. Mixture-model based estimation of gene expression variance from public database improves identification of differentially expressed genes in small sized microarray data. *Bioinformatics*, 26(4):486–492, 2010.

[283] Anmol Kiran and Pavel V. Baranov. Darned: A database of rna editing in humans. *Bioinformatics*, 26(14):1772–1776, 2010.

[284] Marc Kirchner, Bernhard Y. Renard, Ullrich Köthe, Darryl J. Pappin, Fred A. Hamprecht, Hanno Steen, and Judith A.J. Steen. Computational protein profile similarity screening for quantitative mass spectrometry experiments. *Bioinformatics*, 26(1):77–83, 2010.

[285] Marc Kirchner, Wiebke Timm, Peying Fong, Philine Wangemann, and Hanno Steen. Non-linear classification for on-the-fly fractional mass filtering and targeted precursor fragmentation in mass spectrometry experiments. *Bioinformatics*, 26(6):791–797, 2010.

[286] Andrey O. Kislyuk, Lee S. Katz, Sonia Agrawal, Matthew S. Hagen, Andrew B. Conley, Pushkala Jayaraman, Viswateja Nelakuditi, Jay C.

Humphrey, Scott A. Sammons, Dhwani Govil, Raydel D. Mair, Kathleen M. Tatti, Maria L. Tondella, Brian H. Harcourt, Leonard W. Mayer, and I. King Jordan. A computational genomics pipeline for prokaryotic sequencing projects. *Bioinformatics*, 26(15):1819–1826, 2010.

[287] Steffen Klamt, Robert J. Flassig, and Kai Sundmacher. Transwesd: Inferring cellular networks with transitive reduction. *Bioinformatics*, 26(17):2160–2168, 2010.

[288] Kjetil Klepper and Finn Drabløs. Priorseditor: A tool for the creation and use of positional priors in motif discovery. *Bioinformatics*, 26(17):2195–2197, 2010.

[289] D.P. Klose, B.A. Wallace, and Robert W. Janes. 2struc: The secondary structure server. *Bioinformatics*, 26(20):2624–2625, 2010.

[290] Sinan Kockara, Mutlu Mete, Vincent Yip, Brendan Lee, and Kemal Aydin. A soft kinetic data structure for lesion border detection. *Bioinformatics*, 26(12):21–28, 2010.

[291] Devin C. Koestler, Carmen J. Marsit, Brock C. Christensen, Margaret R. Karagas, Raphael Bueno, David J. Sugarbaker, Karl T. Kelsey, and E. Andres Houseman. Semi-supervised recursively partitioned mixture models for identifying cancer subtypes. *Bioinformatics*, 26(20):2578–2585, 2010.

[292] Chuan Hock Koh, Masao Nagasaki, Ayumu Saito, Limsoon Wong, and Satoru Miyano. Da 1.0: Parameter estimation of biological pathways using data assimilation approach. *Bioinformatics*, 26(14):1794–1796, 2010.

[293] Janez Konc and Dusanka Janežič. Probis algorithm for detection of structurally similar protein binding sites by local structural alignment. *Bioinformatics*, 26(9):1160–1168, 2010.

[294] Alexey S. Kondrashov and Raquel Assis. Bridges: A tool for identifying local similarities in long sequences. *Bioinformatics*, 26(16):2055–2056, 2010.

[295] Hashem Koohy, Nigel P. Dyer, John E. Reid, Georgy Koentges, and Sascha Ott. An alignment-free model for comparison of regulatory sequences. *Bioinformatics*, 26(19):2391–2397, 2010.

[296] Klaus O. Kopec, Vikram Alva, and Andrei N. Lupas. Homology of smp domains to the tulip superfamily of lipid-binding proteins provides a structural basis for lipid exchange between er and mitochondria. *Bioinformatics*, 26(16):1927–1931, 2010.

[297] Tamás Korcsmáros, Illés J. Farkas, Máté S. Szalay, Petra Rovó, Dávid Fazekas, Zoltán Spiró, Csaba Böde, Katalin Lenti, Tibor Vellai, and Péter Csermely. Uniformly curated signaling pathways reveal tissue-specific cross-talks and support drug target discovery. *Bioinformatics*, 26(16):2042–2050, 2010.

[298] Rao M. Kotamarti, Michael Hahsler, Douglas Raiford, Monnie McGee, and Margaret H. Dunham. Analyzing taxonomic classification using extensible markov models. *Bioinformatics*, 26(18):2235–2241, 2010.

[299] Falko Krause, Jannis Uhlendorf, Timo Lubitz, Marvin Schulz, Edda Klipp, and Wolfram Liebermeister. Annotation and merging of sbml models with semanticsbml. *Bioinformatics*, 26(3):421–422, 2010.

[300] Peter Krawitz, Christian Rödelsperger, Marten Jäger, Luke Jostins, Sebastian Bauer, and Peter N. Robinson. Microindel detection in short-read sequence data. *Bioinformatics*, 26(6):722–729, 2010.