References

[1] Francesco Abate, Andrea Acquaviva, Giulia Paciello, Carmelo Foti, Elisa Ficarra, Alberto Ferrarini, Massimo Delledonne, Ilaria Iacobucci, Simona Soverini, Giovanni Martinelli, and Enrico Macii. Bellerophontes: An rna-seq data analysis framework for chimeric transcripts discovery based on accurate fusion model. *Bioinformatics*, 28(16):2114–2121, 2012.

[2] Anton Aboukhalil and Martha L. Bulyk. Loess correction for length variation in gene set-based genomic sequence analysis. *Bioinformatics*, 28(11):1446–1454, 2012.

[3] Lipi R. Acharya, Thair Judeh, Guangdi Wang, and Dongxiao Zhu. Optimal structural inference of signaling pathways from unordered and overlapping gene sets. *Bioinformatics*, 28(4):546–556, 2012.

[4] Vicente Acuña, Paulo Vieira Milreu, Ludovic Cottret, Alberto Marchetti-Spaccamela, Leen Stougie, and Marie-France Sagot. Algorithms and complexity of enumerating minimal precursor sets in genome-wide metabolic networks. *Bioinformatics*, 28(19):2474–2483, 2012.

[5] Richard R. Adams. Sed-ed, a workflow editor for computational biology experiments written in sed-ml. *Bioinformatics*, 28(8):1180–1181, 2012.

[6] Nima Aghaeepour, Pratip K. Chattopadhyay, Anuradha Ganesan, Kieran O'Neill, Habil Zare, Adrin Jalali, Holger H. Hoos, Mario Roederer, and Ryan R. Brinkman. Early immunologic correlates of hiv protection can be identified from computational analysis of complex multivariate t-cell flow cytometry assays. *Bioinformatics*, 28(7):1009–1016, 2012.

[7] Derek Aguiar, Bjarni V. Halldórsson, Eric M. Morrow, and Sorin Istrail. Delishus: An efficient and exact algorithm for genome-wide detection of deletion polymorphism in autism. *Bioinformatics*, 28(12):154–162, 2012.

[8] Leslie Aïchaoui, Matthieu Jules, Ludovic Le Chat, Stéphane Aymerich, Vincent Fromion, and Anne Goelzer. Basylica: A tool for automatic

processing of a bacterial live cell array. *Bioinformatics*, 28(20):2705–2706, 2012.

[9] N. Alachiotis, A. Stamatakis, and P. Pavlidis. Omegaplus: A scalable tool for rapid detection of selective sweeps in whole-genome datasets. *Bioinformatics*, 28(17):2274–2275, 2012.

[10] Benjamin Albrecht, Celine Scornavacca, Alberto Cenci, and Daniel H. Huson. Fast computation of minimum hybridization networks. *Bioinformatics*, 28(2):191–197, 2012.

[11] Adam F. Allred, Hilary Renshaw, Scott Weaver, Robert B. Tesh, and David Wang. Vipr hmm: A hidden markov model for detecting recombination with microbial detection microarrays. *Bioinformatics*, 28(22):2922–2929, 2012.

[12] Ryan M. Ames, Daniel Money, Vikramsinh P. Ghatge, Simon Whelan, and Simon C. Lovell. Determining the evolutionary history of gene families. *Bioinformatics*, 28(1):48–55, 2012.

[13] Tavis K. Anderson, William W. Laegreid, Francesco Cerutti, Fernando A. Osorio, Eric A. Nelson, Jane Christopher-Hennings, and Tony L. Goldberg. Ranking viruses: Measures of positional importance within networks define core viruses for rational polyvalent vaccine development. *Bioinformatics*, 28(12):1624–1632, 2012.

[14] Claudia Andreini, Gabriele Cavallaro, and Serena Lorenzini. Findgeo: A tool for determining metal coordination geometry. *Bioinformatics*, 28(12):1658–1660, 2012.

[15] Christof Angermüller, Andreas Biegert, and Johannes Söding. Discriminative modelling of context-specific amino acid substitution probabilities. *Bioinformatics*, 28(24):3240–3247, 2012.

[16] Danny Arends, K. Joeri van der Velde, Pjotr Prins, Karl W. Broman, Steffen Möller, Ritsert C. Jansen, and Morris A. Swertz. xqtl workbench: A scalable web environment for multi-level qtl analysis. *Bioinformatics*, 28(7):1042–1044, 2012.

[17] Phil Arnold, Ionas Erb, Mikhail Pachkov, Nacho Molina, and Erik van Nimwegen. Motevo: Integrated bayesian probabilistic methods

for inferring regulatory sites and motifs on multiple alignments of dna sequences. *Bioinformatics*, 28(4):487–494, 2012.

[18] Shaul Ashkenazi, Rotem Snir, and Yanay Ofran. Assessing the relationship between conservation of function and conservation of sequence using photosynthetic proteins. *Bioinformatics*, 28(24):3203–3210, 2012.

[19] Yan W. Asmann, Sumit Middha, Asif Hossain, Saurabh Baheti, Ying Li, High-Seng Chai, Zhifu Sun, Patrick H. Duffy, Ahmed A. Hadad, Asha Nair, Xiaoyu Liu, Yuji Zhang, Eric W. Klee, Krishna R. Kalari, and Jean-Pierre A. Kocher. Treat: A bioinformatics tool for variant annotations and visualizations in targeted and exome sequencing data. *Bioinformatics*, 28(2):277–278, 2012.

[20] András Aszódi. Multovl: Fast multiple overlaps of genomic regions. *Bioinformatics*, 28(24):3318–3319, 2012.

[21] Emmanouil Athanasiadis, Zoe Cournia, and George Spyrou. Chembioserver: A web-based pipeline for filtering, clustering and visualization of chemical compounds used in drug discovery. *Bioinformatics*, 28(22):3002–3003, 2012.

[22] Jaume Bacardit, Paweł Widera, Alfonso Márquez-Chamorro, Federico Divina, Jesús S. Aguilar-Ruiz, and Natalio Krasnogor. Contact map prediction using a large-scale ensemble of rule sets and the fusion of multiple predicted structural features. *Bioinformatics*, 28(19):2441–2448, 2012.

[23] Benjamin J. Bachman, Eric Venner, Rhonald C. Lua, Serkan Erdin, and Olivier Lichtarge. Etascape: Analyzing protein networks to predict enzymatic function and substrates in cytoscape. *Bioinformatics*, 28(16):2186–2188, 2012.

[24] Sentil Balaji, Charles Mcclendon, Rajesh Chowdhary, Jun S. Liu, and Jinfeng Zhang. Imid: Integrated molecular interaction database. *Bioinformatics*, 28(5):747–749, 2012.

[25] Till Bald, Johannes Barth, Anna Niehues, Michael Specht, Michael Hippler, and Christian Fufezan. pymzml — python module for high-throughput bioinformatics on mass spectrometry data. *Bioinformatics*, 28(7):1052–1053, 2012.

[26] Kathrin Ballerstein, Axel von Kamp, Steffen Klamt, and Utz-Uwe Haus. Minimal cut sets in a metabolic network are elementary modes in a dual network. *Bioinformatics*, 28(3):381–387, 2012.

[27] Mukul S. Bansal, Eric J. Alm, and Manolis Kellis. Efficient algorithms for the reconciliation problem with gene duplication, horizontal transfer and loss. *Bioinformatics*, 28(12):283–291, 2012.

[28] Yael Baran, Bogdan Pasaniuc, Sriram Sankararaman, Dara G. Torgerson, Christopher Gignoux, Celeste Eng, William Rodriguez-Cintron, Rocio Chapela, Jean G. Ford, Pedro C. Avila, Jose Rodriguez-Santana, Esteban Gonzàlez Burchard, and Eran Halperin. Fast and accurate inference of local ancestry in latino populations. *Bioinformatics*, 28(10):1359–1367, 2012.

[29] Alessandro Barbato, Pascal Benkert, Torsten Schwede, Anna Tramontano, and Jan Kosinski. Improving your target-template alignment with modalign. *Bioinformatics*, 28(7):1038–1039, 2012.

[30] Alan E. Barber II and Patricia C. Babbitt. Pythoscape: A framework for generation of large protein similarity networks. *Bioinformatics*, 28(21):2845–2846, 2012.

[31] Richard T. Barfield, Varun Kilaru, Alicia K. Smith, and Karen N. Conneely. Cpgassoc: An r function for analysis of dna methylation microarray data. *Bioinformatics*, 28(9):1280–1281, 2012.

[32] J. Lamar Barnett, Jialiang Yang, Zhipeng Cai, Tong Zhang, and Xiu-Feng Wan. Antigenmap 3d: An online antigenic cartography resource. *Bioinformatics*, 28(9):1292–1293, 2012.

[33] Sebastian Bauer, Sebastian Köhler, Marcel H. Schulz, and Peter N. Robinson. Bayesian ontology querying for accurate and noise-tolerant semantic searches. *Bioinformatics*, 28(19):2502–2508, 2012.

[34] Dominik Beck, Miriam B. Brandl, Lies Boelen, Ashwin Unnikrishnan, John E. Pimanda, and Jason W.H. Wong. Signal analysis for genome-wide maps of histone modifications measured by chip-seq. *Bioinformatics*, 28(8):1062–1069, 2012.

[35] Emmanuelle Becker, Benoît Robisson, Charles E. Chapple, Alain Guénoche, and Christine Brun. Multifunctional proteins revealed by overlapping clustering in protein interaction network. *Bioinformatics*, 28(1):84–90, 2012.

[36] Daniela Beisser, Stefan Brunkhorst, Thomas Dandekar, Gunnar W. Klau, Marcus T. Dittrich, and Tobias Müller. Robustness and accuracy of functional modules in integrated network analysis. *Bioinformatics*, 28(14):1887–1894, 2012.

[37] Michael J. Bell, Colin S. Gillespie, Daniel Swan, and Phillip Lord. An approach to describing and analysing bulk biological annotation quality: A case study using uniprotkb. *Bioinformatics*, 28(18):562–568, 2012.

[38] Céline Bellenguez, Amy Strange, Colin Freeman, Wellcome Trust Case Control Consortium, Peter Donnelly, and Chris C.A. Spencer. A robust clustering algorithm for identifying problematic samples in genome-wide association studies. *Bioinformatics*, 28(1):134–135, 2012.

[39] Matteo Benelli, Chiara Pescucci, Giuseppina Marseglia, Marco Severgnini, Francesca Torricelli, and Alberto Magi. Discovering chimeric transcripts in paired-end rna-seq data by using ericscript. *Bioinformatics*, 28(24):3232–3239, 2012.

[40] A. Benton, J.H. Holmes, S. Hill, A. Chung, and L. Ungar. medpie: An information extraction package for medical message board posts. *Bioinformatics*, 28(5):743–744, 2012.

[41] S‘everine Bérard, Coralie Gallien, Bastien Boussau, Gergely J. Szöllősi, Vincent Daubin, and Eric Tannier. Evolution of gene neighborhoods within reconciled phylogenies. *Bioinformatics*, 28(18):382–388, 2012.

[42] Axel Bernal, Koby Crammer, and Fernando Pereira. Automated gene-model curation using global discriminative learning. *Bioinformatics*, 28(12):1571–1578, 2012.

[43] Charles C. Berry, Nicolas A. Gillet, Anat Melamed, Niall Gormley, Charles R.M. Bangham, and Frederic D. Bushman. Estimating abundances of retroviral insertion sites from dna fragment length data. *Bioinformatics*, 28(6):755–762, 2012.

[44] Terry Bertozzi, Kate L. Sanders, Mark J. Sistrom, and Michael G. Gardner. Anonymous nuclear loci in non-model organisms: Making the most of high-throughput genome surveys. *Bioinformatics*, 28(14):1807–1810, 2012.

[45] Aparna Bhaduri, Kun Qu, Carolyn S. Lee, Alexander Ungewickell, and Paul A. Khavari. Rapid identification of non-human sequences in high-throughput sequencing datasets. *Bioinformatics*, 28(8):1174–1175, 2012.

[46] Benjamin P. Blackburne and Simon Whelan. Measuring the distance between multiple sequence alignments. *Bioinformatics*, 28(4):495–502, 2012.

[47] Valentina Boeva, Alban Lermine, Camille Barette, Christel Guillouf, and Emmanuel Barillot. Nebula — a web-server for advanced chip-seq data analysis. *Bioinformatics*, 28(19):2517–2519, 2012.

[48] Valentina Boeva, Tatiana Popova, Kevin Bleakley, Pierre Chiche, Julie Cappo, Gudrun Schleiermacher, Isabelle Janoueix-Lerosey, Olivier Delattre, and Emmanuel Barillot. Control-freec: A tool for assessing copy number and allelic content using next-generation sequencing data. *Bioinformatics*, 28(3):423–425, 2012.

[49] Marc J. Bonder, Sanne Abeln, Egija Zaura, and Bernd W. Brandt. Comparing clustering and pre-processing in taxonomy analysis. *Bioinformatics*, 28(22):2891–2897, 2012.

[50] Raoul J.P. Bonnal, Jan Aerts, George Githinji, Naohisa Goto, Dan MacLean, Chase A. Miller, Hiroyuki Mishima, Massimiliano Pagani, Ricardo Ramirez-Gonzalez, Geert Smant, Francesco Strozzi, Rob Syme, Rutger Vos, Trevor J. Wennblom, Ben J. Woodcroft, Toshiaki Katayama, and Pjotr Prins. Biogem: An effective tool-based approach for scaling up open source software development in bioinformatics. *Bioinformatics*, 28(7):1035–1037, 2012.

[51] Daniela Börnigen, Léon-Charles Tranchevent, Francisco Bonachela-Capdevila, Koenraad Devriendt, Bart De Moor, Patrick De Causmaecker, and Yves Moreau. An unbiased evaluation of gene prioritization tools. *Bioinformatics*, 28(23):3081–3088, 2012.

[52] Hannes Braberg, Benjamin M. Webb, Elina Tjioe, Ursula Pieper, Andrej Sali, and M.S. Madhusudhan. Salign: A web server for alignment of multiple protein sequences and structures. *Bioinformatics*, 28(15):2072–2073, 2012.

[53] Marco Brandizi, Natalja Kurbatova, Ugis Sarkans, and Philippe Rocca-Serra. graph2tab, a library to convert experimental workflow graphs into tabular formats. *Bioinformatics*, 28(12):1665–1667, 2012.

[54] Ryan Brenke, David R. Hall, Gwo-Yu Chuang, Stephen R. Comeau, Tanggis Bohnuud, Dmitri Beglov, Ora Schueler-Furman, Sandor Vajda, and Dima Kozakov. Application of asymmetric statistical potentials to antibody-protein docking. *Bioinformatics*, 28(20):2608–2614, 2012.

[55] Ma'ayan Bresler, Sara Sheehan, Andrew H. Chan, and Yun S. Song. Telescoper: De novo assembly of highly repetitive regions. *Bioinformatics*, 28(18):311–317, 2012.

[56] R.W.W. Brouwer, M.C.G.N. van den Hout, F.G. Grosveld, and W.F.J. van IJcken. Narwhal, a primary analysis pipeline for ngs data. *Bioinformatics*, 28(2):284–285, 2012.

[57] Marie Brown, David C. Wedge, Royston Goodacre, Douglas B. Kell, Philip N. Baker, Louise C. Kenny, Mamas A. Mamas, Ludwig Neyses, and Warwick B. Dunn. Corrigendum to "automated workflows for accurate mass-based putative metabolite identification in lc/ms-derived metabolomic datasets". *Bioinformatics*, 28(1):149–149, 2012. Originally in Bioinformatics, Vol. 27, 2011, No. 8, 1108-1112.

[58] Finja Büchel, Clemens Wrzodek, Florian Mittag, Andreas Dräger, Johannes Eichner, Nicolas Rodriguez, Nicolas Le Nov'ere, and Andreas Zell. Qualitative translation of relations from biopax to sbml qual. *Bioinformatics*, 28(20):2648–2653, 2012.

[59] Maria T. Buenavista, Daniel B. Roche, and Liam J. McGuffin. Improvement of 3d protein models using multiple templates guided by single-template model quality assessment. *Bioinformatics*, 28(14):1851–1857, 2012.

[60] Christoph Bueschl, Bernhard Kluger, Franz Berthiller, Gerald Lirk, Stephan Winkler, Rudolf Krska, and Rainer Schuhmacher. Metetract:

A new software tool for the automated comprehensive extraction of metabolite-derived lc/ms signals in metabolomics research. *Bioinformatics*, 28(5):736–738, 2012.

[61] Florian Buettner and Fabian J. Theis. A novel approach for resolving differences in single-cell gene expression patterns from zygote to blastocyst. *Bioinformatics*, 28(18):626–632, 2012.

[62] Quoc-Chinh Bui and Peter M.A. Sloot. A robust approach to extract biomedical events from literature. *Bioinformatics*, 28(20):2654–2661, 2012.

[63] John Bunge, Linda Woodard, Dankmar Böhning, James A. Foster, Sean Connolly, and Heather K. Allen. Estimating population diversity with catchall. *Bioinformatics*, 28(7):1045–1047, 2012.

[64] Matthew S. Burriesci, Erik M. Lehnert, and John R. Pringle. Fulcrum: Condensing redundant reads from high-throughput sequencing studies. *Bioinformatics*, 28(10):1324–1327, 2012.

[65] Xiao Cai, Hua Wang, Heng Huang, and Chris Ding. Joint stage recognition and anatomical annotation of drosophila gene expression patterns. *Bioinformatics*, 28(12):16–24, 2012.

[66] José Caldas, Nils Gehlenborg, Eeva Kettunen, Ali Faisal, Mikko Rönty, Andrew G. Nicholson, Sakari Knuutila, Alvis Brazma, and Samuel Kaski. Data-driven information retrieval in heterogeneous collections of transcriptomics data links sim2s to malignant pleural mesothelioma. *Bioinformatics*, 28(2):246–253, 2012.

[67] David Campos, Sérgio Matos, Ian Lewin, José Luís Oliveira, and Dietrich Rebholz-Schuhmann. Harmonization of gene/protein annotations: Towards a gold standard medline. *Bioinformatics*, 28(9):1253–1261, 2012.

[68] Stephanie A. Canny, Yasel Cruz, Mark R. Southern, and Patrick R. Griffin. Pubchem promiscuity: A web resource for gathering compound promiscuity data from pubchem. *Bioinformatics*, 28(1):140–141, 2012.

[69] Rogan Carr and Elhanan Borenstein. Netseed: A network-based reverse-ecology tool for calculating the metabolic interface of an organism with its environment. *Bioinformatics*, 28(5):734–735, 2012.

[70] Jean-Philippe Carralot, Arnaud Ogier, Annette Boese, Auguste Genovesio, Priscille Brodin, Peter Sommer, and Thierry Dorval. A novel specific edge effect correction method for rna interference screenings. *Bioinformatics*, 28(2):261–268, 2012.

[71] Paulo C. Carvalho, John R. Yates III, and Valmir C. Barbosa. Improving the tfold test for differential shotgun proteomics. *Bioinformatics*, 28(12):1652–1654, 2012.

[72] Tim Carver, Simon R. Harris, Matthew Berriman, Julian Parkhill, and Jacqueline A. McQuillan. Artemis: An integrated platform for visualization and analysis of high-throughput sequence-based experimental data. *Bioinformatics*, 28(4):464–469, 2012.

[73] Jean-Baptiste Cazier, Chris C. Holmes, and John Broxholme. Greve: Genomic recurrent event viewer to assist the identification of patterns across individual cancer samples. *Bioinformatics*, 28(22):2981–2982, 2012.

[74] Adrià Cereto-Massagué, Laura Guasch, Cristina Valls, Miquel Mulero, Gerard Pujadas, and Santiago Garcia-Vallvé. Decoyfinder: An easy-to-use python gui application for building target-specific decoy sets. *Bioinformatics*, 28(12):1661–1662, 2012.

[75] Sutirtha Chakraborty, Somnath Datta, and Susmita Datta. Surrogate variable analysis using partial least squares (sva-pls) in gene expression studies. *Bioinformatics*, 28(6):799–806, 2012.

[76] Kumar Chandan, Martijn P. van Iersel, Mirit I. Aladjem, Kurt W. Kohn, and Augustin Luna. Pathvisio-validator: A rule-based validation plugin for graphical pathway notations. *Bioinformatics*, 28(6):889–890, 2012.

[77] Darby Tien-Hao Chang, Chao-Hsuan Ke, Jung-Hsin Lin, and Jung-Hsien Chiang. Autobind: Automatic extraction of protein-ligand-binding affinity data from biological literature. *Bioinformatics*, 28(16):2162–2168, 2012.

[78] Jeffrey T. Chang. Deriving transcriptional programs and functional processes from gene expression databases. *Bioinformatics*, 28(8):1122–1129, 2012.

[79] Matthieu Chartier, Francis Gaudreault, and Rafael Najmanovich. Large-scale analysis of conserved rare codon clusters suggests an involvement in co-translational molecular recognition events. *Bioinformatics*, 28(11):1438–1445, 2012.

[80] Bor-Sen Chen and Chia-Chou Wu. On the calculation of signal transduction ability of signaling transduction pathways in intracellular communication: Systematic approach. *Bioinformatics*, 28(12):1604–1611, 2012.

[81] Cho-Yi Chen, Shui-Tein Chen, Hsueh-Fen Juan, and Hsuan-Cheng Huang. Lengthening of $3'$ utr increases with morphological complexity in animal evolution. *Bioinformatics*, 28(24):3178–3181, 2012.

[82] Chong-Jian Chen, Nicolas Servant, Joern Toedling, Alexis Sarazin, Antonin Marchais, Evelyne Duvernois-Berthet, Valérie Cognat, Vincent Colot, Olivier Voinnet, Edith Heard, Constance Ciaudo, and Emmanuel Barillot. ncpro-seq: A tool for annotation and profiling of ncrnas in srna-seq data. *Bioinformatics*, 28(23):3147–3149, 2012.

[83] Edward Y. Chen, Huilei Xu, Simon Gordonov, Maribel P. Lim, Matthew H. Perkins, and Avi Ma'ayan. Expression2kinases: mrna profiling linked to multiple upstream regulatory layers. *Bioinformatics*, 28(1):105–111, 2012.

[84] Gary K. Chen. A scalable and portable framework for massively parallel variable selection in genetic association studies. *Bioinformatics*, 28(5):719–720, 2012.

[85] Gary K. Chen, Kai Wang, Alex H. Stram, Eric M. Sobel, and Kenneth Lange. Mendel-gpu: Haplotyping and genotype imputation on graphics processing units. *Bioinformatics*, 28(22):2979–2980, 2012.

[86] Jun Chen, Kyle Bittinger, Emily S. Charlson, Christian Hoffmann, James Lewis, Gary D. Wu, Ronald G. Collman, Frederic D. Bushman,

and Hongzhe Li. Associating microbiome composition with environmental covariates using generalized unifrac distances. *Bioinformatics*, 28(16):2106–2113, 2012.

[87] Ke Chen, Marcin J. Mizianty, and Lukasz Kurgan. Prediction and analysis of nucleotide-binding residues using sequence and sequence-derived structural descriptors. *Bioinformatics*, 28(3):331–341, 2012.

[88] Ken Chen, John W. Wallis, Cyriac Kandoth, Joelle M. Kalicki-Veizer, Karen L. Mungall, Andrew J. Mungall, Steven J. Jones, Marco A. Marra, Timothy J. Ley, Elaine R. Mardis, Richard K. Wilson, John N. Weinstein, and Li Ding. Breakfusion: Targeted assembly-based identification of gene fusions in whole transcriptome paired-end sequencing data. *Bioinformatics*, 28(14):1923–1924, 2012.

[89] Mei-Ju May Chen, Lih-Ching Chou, Tsung-Ting Hsieh, Ding-Dar Lee, Kai-Wei Liu, Chi-Yuan Yu, Yen-Jen Oyang, Huai-Kuang Tsai, and Chien-Yu Chen. De novo motif discovery facilitates identification of interactions between transcription factors in saccharomyces cerevisiae. *Bioinformatics*, 28(5):701–708, 2012.

[90] Yang Chen, Jin Gu, Dan Li, and Shao Li. Time-course network analysis reveals tnf-α can promote g_1/s transition of cell cycle in vascular endothelial cells. *Bioinformatics*, 28(1):1–4, 2012.

[91] Zhongxue Chen, Qingzhong Liu, and Saralees Nadarajah. A new statistical approach to detecting differentially methylated loci for case control illumina array methylation data. *Bioinformatics*, 28(8):1109–1113, 2012.

[92] Tiejun Cheng, Yanli Wang, and Stephen H. Bryant. Fselector: A ruby gem for feature selection. *Bioinformatics*, 28(21):2851–2852, 2012.

[93] Sang-Mun Chi and Dougu Nam. Wegoloc: Accurate prediction of protein subcellular localization using weighted gene ontology terms. *Bioinformatics*, 28(7):1028–1030, 2012.

[94] Pierre-Yves Chibon, Heiko Schoof, Richard G.F. Visser, and Richard Finkers. Marker2sequence, mine your qtl regions for candidate genes. *Bioinformatics*, 28(14):1921–1922, 2012.

[95] Maria D. Chikina and Olga G. Troyanskaya. An effective statistical evaluation of chipseq dataset similarity. *Bioinformatics*, 28(5):607–613, 2012.

[96] Leonid Chindelevitch, Daniel Ziemek, Ahmed Enayetallah, Ranjit Randhawa, Ben Sidders, Christoph Brockel, and Enoch S. Huang. Causal reasoning on biological networks: Interpreting transcriptional changes. *Bioinformatics*, 28(8):1114–1121, 2012.

[97] Thomas W. Chittenden, Eleanor A. Howe, Jennifer M. Taylor, Jessica C. Mar, Martin J. Aryee, Harold Gómez, Razvan Sultana, John Braisted, Sarita J. Nair, John Quackenbush, and Chris Holmes. nease: A method for gene ontology subclassification of high-throughput gene expression data. *Bioinformatics*, 28(5):726–728, 2012.

[98] Grzegorz Chojnowski, Janusz M. Bujnicki, and Matthias Bochtler. Riber/diber: A software suite for crystal content analysis in the studies of protein-nucleic acid complexes. *Bioinformatics*, 28(6):880–881, 2012.

[99] Zechen Chong, Jue Ruan, and Chung-I. Wu. Rainbow: An integrated tool for efficient clustering and assembling rad-seq reads. *Bioinformatics*, 28(21):2732–2737, 2012.

[100] Ryan G. Christensen, Metewo Selase Enuameh, Marcus B. Noyes, Michael H. Brodsky, Scot A. Wolfe, and Gary D. Stormo. Recognition models to predict dna-binding specificities of homeodomain proteins. *Bioinformatics*, 28(12):84–89, 2012.

[101] Dominique Chu, Nicolae Zabet, and Tobias von der Haar. A novel and versatile computational tool to model translation. *Bioinformatics*, 28(2):292–293, 2012.

[102] Gwo-Yu Chuang, Jeffrey C. Boyington, M. Gordon Joyce, Jiang Zhu, Gary J. Nabel, Peter D. Kwong, and Ivelin Georgiev. Computational prediction of n-linked glycosylation incorporating structural properties and patterns. *Bioinformatics*, 28(17):2249–2255, 2012.

[103] Alexander Churbanov, Rachael Ryan, Nabeeh Hasan, Donovan Bailey, Haofeng Chen, Brook Milligan, and Peter Houde. Highssr: High-

throughput ssr characterization and locus development from next-gen sequencing data. *Bioinformatics*, 28(21):2797–2803, 2012.

[104] Marleen Claeys, Valerie Storms, Hong Sun, Tom Michoel, and Kathleen Marchal. Motifsuite: Workflow for probabilistic motif detection and assessment. *Bioinformatics*, 28(14):1931–1932, 2012.

[105] Ofir Cohen, Haim Ashkenazy, David Burstein, and Tal Pupko. Uncovering the co-evolutionary network among prokaryotic genes. *Bioinformatics*, 28(18):389–394, 2012.

[106] Lachlan J.M. Coin, Dandan Cao, Jingjing Ren, Xianbo Zuo, Liangdan Sun, Sen Yang, Xuejun Zhang, Yong Cui, Yingrui Li, Xin Jin, and Jun Wang. An exome sequencing pipeline for identifying and genotyping common cnvs associated with disease with application to psoriasis. *Bioinformatics*, 28(18):370–374, 2012.

[107] Francesc Coll, Kim Mallard, Mark D. Preston, Stephen Bentley, Julian Parkhill, Ruth McNerney, Nigel Martin, and Taane G. Clark. Spolpred: Rapid and accurate prediction of mycobacterium tuberculosis spoligotypes from short genomic sequences. *Bioinformatics*, 28(22):2991–2993, 2012.

[108] Nigel Collier and Son Doan. Geni-db: A database of global events for epidemic intelligence. *Bioinformatics*, 28(8):1186–1188, 2012.

[109] Federico Comoglio and Maurizio Rinaldi. Rknots: Topological analysis of knotted biopolymers with r. *Bioinformatics*, 28(10):1400–1401, 2012.

[110] Thomas Conway, Jeremy Wazny, Andrew Bromage, Martin Tymms, Dhanya Sooraj, Elizabeth D. Williams, and Bryan Beresford-Smith. Xenome — a tool for classifying reads from xenograft samples. *Bioinformatics*, 28(12):172–178, 2012.

[111] Thomas Conway, Jeremy Wazny, Andrew Bromage, Justin Zobel, and Bryan Beresford-Smith. Gossamer — a resource-efficient de novo assembler. *Bioinformatics*, 28(14):1937–1938, 2012.

[112] Wade K. Copeland, Vandhana Krishnan, Daniel Beck, Matt Settles, James A. Foster, Kyu-Chul Cho, Mitch Day, Roxana Hickey,

Ursel M.E. Schütte, Xia Zhou, Christopher J. Williams, Larry J. Forney, and Zaid Abdo. mcagui: Microbial community analysis r-graphical user interface (gui). *Bioinformatics*, 28(16):2198–2199, 2012.

[113] Pablo Cordero, Julius B. Lucks, and Rhiju Das. An rna mapping database for curating rna structure mapping experiments. *Bioinformatics*, 28(22):3006–3008, 2012.

[114] Jole Costanza, Giovanni Carapezza, Claudio Angione, Pietro Lió, and Giuseppe Nicosia. Robust design of microbial strains. *Bioinformatics*, 28(23):3097–3104, 2012.

[115] Anthony J. Cox, Markus J. Bauer, Tobias Jakobi, and Giovanna Rosone. Large-scale compression of genomic sequence databases with the burrows-wheeler transform. *Bioinformatics*, 28(11):1415–1419, 2012.

[116] Darren J. Creek, Andris Jankevics, Karl E.V. Burgess, Rainer Breitling, and Michael P. Barrett. Ideom: An excel interface for analysis of lc-ms-based metabolomics data. *Bioinformatics*, 28(7):1048–1049, 2012.

[117] Gabriel Cuellar-Partida, Fabian A. Buske, Robert C. McLeay, Tom Whitington, William Stafford Noble, and Timothy L. Bailey. Epigenetic priors for identifying active transcription factor binding sites. *Bioinformatics*, 28(1):56–62, 2012.

[118] Anna Caroline E. Dahl, Matthieu Chavent, and Mark S.P. Sansom. Bendix: Intuitive helix geometry analysis and abstraction. *Bioinformatics*, 28(16):2193–2194, 2012.

[119] Zhiming Dai and Xianhua Dai. Antisense transcription is coupled to nucleosome occupancy in sense promoters. *Bioinformatics*, 28(21):2719–2723, 2012.

[120] Noah M. Daniels, Raghavendra Hosur, Bonnie Berger, and Lenore J. Cowen. Smurflite: Combining simplified markov random fields with simulated evolution improves remote homology detection for beta-structural proteins into the twilight zone. *Bioinformatics*, 28(9):1216–1222, 2012.

[121] Gregory Darnell, Dat Duong, Buhm Han, and Eleazar Eskin. Incorporating prior information into association studies. *Bioinformatics*, 28(12):147–153, 2012.

[122] Jishnu Das, Jaaved Mohammed, and Haiyuan Yu. Genome-scale analysis of interaction dynamics reveals organization of biological networks. *Bioinformatics*, 28(14):1873–1878, 2012.

[123] Shreepriya Das and Haris Vikalo. Onlinecall: Fast online parameter estimation and base calling for illumina's next-generation sequencing. *Bioinformatics*, 28(13):1677–1683, 2012.

[124] E. Dassi, A. Malossini, A. Re, T. Mazza, T. Tebaldi, L. Caputi, and A. Quattrone. Aura: Atlas of utr regulatory activity. *Bioinformatics*, 28(1):142–144, 2012.

[125] John A. Dawson, Shuyun Ye, and Christina Kendziorski. R/ebcoexpress: An empirical bayesian framework for discovering differential co-expression. *Bioinformatics*, 28(14):1939–1940, 2012.

[126] Vanderlei J. Debastiani and Valério D. Pillar. Syncsa — r tool for analysis of metacommunities based on functional traits and phylogeny of the community components. *Bioinformatics*, 28(15):2067–2068, 2012.

[127] Matthew DeJongh, Benjamin Bockstege, Paul Frybarger, Nicholas Hazekamp, Joshua Kammeraad, and Travis McGeehan. Cytoseed: A cytoscape plugin for viewing, manipulating and analyzing metabolic models created by the model seed. *Bioinformatics*, 28(6):891–892, 2012.

[128] Nicolas Delhomme, Ismaël Padioleau, Eileen E. Furlong, and Lars M. Steinmetz. easyrnaseq: A bioconductor package for processing rna-seq data. *Bioinformatics*, 28(19):2532–2533, 2012.

[129] David S. DeLuca, Joshua Z. Levin, Andrey Sivachenko, Timothy Fennell, Marc-Danie Nazaire, Chris Williams, Michael Reich, Wendy Winckler, and Gad Getz. Rna-seqc: Rna-seq metrics for quality control and process optimization. *Bioinformatics*, 28(11):1530–1532, 2012.

[130] Todd F. DeLuca, Jike Cui, Jae-Yoon Jung, Kristian Che St. Gabriel, and Dennis P. Wall. Roundup 2.0: Enabling comparative genomics for over 1800 genomes. *Bioinformatics*, 28(5):715–716, 2012.

[131] Christophe Dessimoz, Toni Gabaldón, David S. Roos, Erik L.L. Sonnhammer, Javier Herrero, and the Quest for Orthologs Consortium. Toward community standards in the quest for orthologs. *Bioinformatics*, 28(6):900–904, 2012.

[132] Pietro Di Lena, Ken Nagata, and Pierre Baldi. Deep architectures for protein contact map prediction. *Bioinformatics*, 28(19):2449–2457, 2012.

[133] Slavica Dimitrieva and Philipp Bucher. Genomic context analysis reveals dense interaction network between vertebrate ultraconserved noncoding elements. *Bioinformatics*, 28(18):395–401, 2012.

[134] Jiarui Ding, Ali Bashashati, Andrew Roth, Arusha Oloumi, Kane Tse, Thomas Zeng, Gholamreza Haffari, Martin Hirst, Marco A. Marra, Anne Condon, Samuel Aparicio, and Sohrab P. Shah. Feature-based classifiers for somatic mutation detection in tumour-normal paired sequencing data. *Bioinformatics*, 28(2):167–175, 2012.

[135] Fatemeh Miri Disfani, Wei-Lun Hsu, Marcin J. Mizianty, Christopher J. Oldfield, Bin Xue, A. Keith Dunker, Vladimir N. Uversky, and Lukasz Kurgan. Morfpred, a computational tool for sequence-based prediction and characterization of short disorder-to-order transitioning binding regions in proteins. *Bioinformatics*, 28(12):75–83, 2012.

[136] Tomás Di Domenico, Ian Walsh, Alberto J.M. Martin, and Silvio C.E. Tosatto. Mobidb: A comprehensive database of intrinsic protein disorder annotations. *Bioinformatics*, 28(15):2080–2081, 2012.

[137] Chao-Yi Dong, Dongkwan Shin, Sunghoon Joo, YoonKey Nam, and Kwang-Hyun Cho. Identification of feedback loops in neural networks based on multi-step granger causality. *Bioinformatics*, 28(16):2146–2153, 2012.

[138] Gero Doose and Dirk Metzler. Bayesian sampling of evolutionarily conserved rna secondary structures with pseudoknots. *Bioinformatics*, 28(17):2242–2248, 2012.

[139] Mikhail G. Dozmorov, Lukas R. Cara, Cory B. Giles, and Jonathan D. Wren. Genomerunner: Automating genome exploration. *Bioinformatics*, 28(3):419–420, 2012.

[140] Plamen Dragiev, Robert Nadon, and Vladimir Makarenkov. Two effective methods for correcting experimental high-throughput screening data. *Bioinformatics*, 28(13):1775–1782, 2012.

[141] Bas E. Dutilh, Robert Schmieder, Jim Nulton, Ben Felts, Peter Salamon, Robert A. Edwards, and John L. Mokili. Reference-independent comparative metagenomics using cross-assembly: crass. *Bioinformatics*, 28(24):3225–3231, 2012.

[142] John Eargle and Zaida Luthey-Schulten. Networkview: 3d display and analysis of protein rna interaction networks. *Bioinformatics*, 28(22):3000–3001, 2012.

[143] Federica Eduati, Javier De Las Rivas, Barbara Di Camillo, Gianna Toffolo, and Julio Saez-Rodriguez. Integrating literature-constrained and data-driven inference of signalling networks. *Bioinformatics*, 28(18):2311–2317, 2012.

[144] Robert A. Edwards, Robert Olson, Terry Disz, Gordon D. Pusch, Veronika Vonstein, Rick Stevens, and Ross Overbeek. Real time metagenomics: Using k-mers to annotate metagenomes. *Bioinformatics*, 28(24):3316–3317, 2012.

[145] Dennis Egen and Desmond S. Lun. Truncated branch and bound achieves efficient constraint-based genetic design. *Bioinformatics*, 28(12):1619–1623, 2012.

[146] Jesse Eickholt and Jianlin Cheng. Predicting protein residue-residue contacts using deep networks and boosting. *Bioinformatics*, 28(23):3066–3072, 2012.

[147] Anne-Katrin Emde, Marcel H. Schulz, David Weese, Ruping Sun, Martin Vingron, Vera M. Kalscheuer, Stefan A. Haas, and Knut Reinert. Detecting genomic indel variants with exact breakpoints in single- and paired-end sequencing data using splazers. *Bioinformatics*, 28(5):619–627, 2012.

[148] John Spencer Evans. Aragonite-associated biomineralization proteins are disordered and contain interactive motifs. *Bioinformatics*, 28(24):3182–3185, 2012.

[149] Götz Fabian, Thomas Wächter, and Michael Schroeder. Extending ontologies by finding siblings using set expansion techniques. *Bioinformatics*, 28(12):292–300, 2012.

[150] David Fange, Anel Mahmutovic, and Johan Elf. Mesord 1.0: Stochastic reaction-diffusion simulations in the microscopic limit. *Bioinformatics*, 28(23):3155–3157, 2012.

[151] Gregory G. Faust and Ira M. Hall. Yaha: Fast and flexible long-read alignment with optimal breakpoint detection. *Bioinformatics*, 28(19):2417–2424, 2012.

[152] Nizar Fawal, Bruno Savelli, Christophe Dunand, and Catherine Mathé. Geca: A fast tool for gene evolution and conservation analysis in eukaryotic protein families. *Bioinformatics*, 28(10):1398–1399, 2012.

[153] Ariel Feiglin, Adar Hacohen, Avital Sarusi, Jasmin Fisher, Ron Unger, and Yanay Ofran. Static network structure can be used to model the phenotypic effects of perturbations in regulatory networks. *Bioinformatics*, 28(21):2811–2818, 2012.

[154] Feng Feng, Ana Paula Sales, and Thomas B. Kepler. Corrigendum to "a bayesian approach for estimating calibration curves and unknown concentrations in immunoassays". *Bioinformatics*, 28(10):1413–1413, 2012. Originally in Bioinformatics, Vol. 27, 2011, No. 5, 707-712.

[155] Jianxing Feng, Clifford A. Meyer, Qian Wang, Jun S. Liu, X. Shirley Liu, and Yong Zhang. Gfold: A generalized fold change for ranking differentially expressed genes from rna-seq data. *Bioinformatics*, 28(21):2782–2788, 2012.

[156] Linqing Feng, Ting Zhao, and Jinhyun Kim. Improved synapse detection for mgrasp-assisted brain connectivity mapping. *Bioinformatics*, 28(12):25–31, 2012.

[157] Heide Fier, Sungho Won, Dmitry Prokopenko, Taofik AlChawa, Kerstin U. Ludwig, Rolf Fimmers, Edwin K. Silverman, Marcello Pagano, Elisabeth Mangold, and Christoph Lange. "location, location, location": A spatial approach for rare variant analysis and an application to a study on non-syndromic cleft lip with or without cleft palate. *Bioinformatics*, 28(23):3027–3033, 2012.

[158] R.J. Flassig and K. Sundmacher. Optimal design of stimulus experiments for robust discrimination of biochemical reaction networks. *Bioinformatics*, 28(23):3089–3096, 2012.

[159] Nuno A. Fonseca, Johan Rung, Alvis Brazma, and John C. Marioni. Tools for mapping high-throughput sequencing data. *Bioinformatics*, 28(24):3169–3177, 2012.

[160] Christian Frech, Caleb Choo, and Nansheng Chen. Featurestack: Perl module for comparative visualization of gene features. *Bioinformatics*, 28(23):3137–3138, 2012.

[161] Jr Freeman, Thomas C. and William C. Wimley. Tmbb-db: A transmembrane β-barrel proteome database. *Bioinformatics*, 28(19):2425–2430, 2012.

[162] Leon French, Suzanne Lane, Lydia Xu, Celia Siu, Cathy Kwok, Yiqi Chen, Claudia Krebs, and Paul Pavlidis. Application and evaluation of automated methods to extract neuroanatomical connectivity statements from free text. *Bioinformatics*, 28(22):2963–2970, 2012.

[163] Milana Frenkel-Morgenstern and Alfonso Valencia. Novel domain combinations in proteins encoded by chimeric transcripts. *Bioinformatics*, 28(12):67–74, 2012.

[164] Kai Fu, Qianzi Tang, Jianxing Feng, X. Shirley Liu, and Yong Zhang. Dinup: A systematic approach to identify regions of differential nucleosome positioning. *Bioinformatics*, 28(15):1965–1971, 2012.

[165] Limin Fu, Beifang Niu, Zhengwei Zhu, Sitao Wu, and Weizhong Li. Cd-hit: Accelerated for clustering the next-generation sequencing data. *Bioinformatics*, 28(23):3150–3152, 2012.

[166] Christian Fuchsberger, Daniel Taliun, Peter P. Pramstaller, Cristian Pattaro, and on behalf of the CKDGen consortium. Gwatoolbox: An r package for fast quality control and handling of genome-wide association studies meta-analysis data. *Bioinformatics*, 28(3):444–445, 2012.

[167] Edvin Fuglebakk, Julián Echave, and Nathalie Reuter. Measuring and comparing structural fluctuation patterns in large protein datasets. *Bioinformatics*, 28(19):2431–2440, 2012.

[168] Shigeo Fujimori, Naoya Hirai, Kazuyo Masuoka, Tomohiro Oshikubo, Tatsuhiro Yamashita, Takanori Washio, Ayumu Saito, Masao Nagasaki, Satoru Miyano, and Etsuko Miyamoto-Sato. Irview: A database and viewer for protein interacting regions. *Bioinformatics*, 28(14):1949–1950, 2012.

[169] V.L. Galinsky. Yoabs: Yet other aligner of biological sequences — an efficient linearly scaling nucleotide aligner. *Bioinformatics*, 28(8):1070–1077, 2012.

[170] Feng Gao, Hao Luo, and Chun-Ting Zhang. Deori: A database of eukaryotic dna replication origins. *Bioinformatics*, 28(11):1551–1552, 2012.

[171] Maxime Garcia, Raphaelle Millat-Carus, François Bertucci, Pascal Finetti, Daniel Birnbaum, and Ghislain Bidaut. Interactome-transcriptome integration for predicting distant metastasis in breast cancer. *Bioinformatics*, 28(5):672–678, 2012.

[172] Fernando García-Alcalde, Konstantin Okonechnikov, José Carbonell, Luis M. Cruz, Stefan Götz, Sonia Tarazona, Joaquín Dopazo, Thomas F. Meyer, and Ana Conesa. Qualimap: Evaluating next-generation sequencing alignment data. *Bioinformatics*, 28(20):2678–2679, 2012.

[173] Dennis K. Gascoigne, Seth W. Cheetham, Pierre B. Cattenoz, Michael B. Clark, Paulo P. Amaral, Ryan J. Taft, Dagmar Wilhelm, Marcel E. Dinger, and John S. Mattick. Pinstripe: A suite of programs for integrating transcriptomic and proteomic datasets identifies novel proteins and improves differentiation of protein-coding and non-coding genes. *Bioinformatics*, 28(23):3042–3050, 2012.

[174] Paulo Gaspar, José Luís Oliveira, Jörg Frommlet, Manuel A.S. Santos, and Gabriela Moura. Eugene: Maximizing synthetic gene design for heterologous expression. *Bioinformatics*, 28(20):2683–2684, 2012.

[175] Laurent Gatto and Kathryn S. Lilley. Msnbase-an r/bioconductor package for isobaric tagged mass spectrometry data visualization, processing and quantitation. *Bioinformatics*, 28(2):288–289, 2012.

[176] Francis Gaudreault, Matthieu Chartier, and Rafael Najmanovich. Side-chain rotamer changes upon ligand binding: Common, crucial, correlate with entropy and rearrange hydrogen bonding. *Bioinformatics*, 28(18):423–430, 2012.

[177] Mathieu Gautier and Renaud Vitalis. rehh: An r package to detect footprints of selection in genome-wide snp data from haplotype structure. *Bioinformatics*, 28(8):1176–1177, 2012.

[178] Yongchao Ge and Stuart C. Sealfon. flowpeaks: A fast unsupervised clustering for flow cytometry data via k-means and density peak finding. *Bioinformatics*, 28(15):2052–2058, 2012.

[179] Geert Geeven, Ronald E. van Kesteren, August B. Smit, and Mathisca C.M. de Gunst. Identification of context-specific gene regulatory networks with gemula — gene expression modeling using lasso. *Bioinformatics*, 28(2):214–221, 2012.

[180] Walter Georgescu, John P. Wikswo, and Vito Quaranta. cellanimation: An open source matlab framework for microscopy assays. *Bioinformatics*, 28(1):138–139, 2012.

[181] Elisabeth Georgii, Jarkko Salojärvi, Mikael Brosché, Jaakko Kangasjärvi, and Samuel Kaski. Targeted retrieval of gene expression measurements using regulatory models. *Bioinformatics*, 28(18):2349–2356, 2012.

[182] Martin Gerner, Farzaneh Sarafraz, Casey M. Bergman, and Goran Nenadic. Biocontext: An integrated text mining system for large-scale extraction and contextualization of biomolecular events. *Bioinformatics*, 28(16):2154–2161, 2012.

[183] Sebastian Gibb and Korbinian Strimmer. Maldiquant: A versatile r package for the analysis of mass spectrometry data. *Bioinformatics*, 28(17):2270–2271, 2012.

[184] Dorothee Girbig, Joachim Selbig, and Sergio Grimbs. A matlab toolbox for structural kinetic modeling. *Bioinformatics*, 28(19):2546–2547, 2012.

[185] Enrico Glaab, Anaïs Baudot, Natalio Krasnogor, Reinhard Schneider, and Alfonso Valencia. Enrichnet: Network-based gene set enrichment analysis. *Bioinformatics*, 28(18):451–457, 2012.

[186] Enrico Glaab and Reinhard Schneider. Pathvar: Analysis of gene and protein expression variance in cellular pathways using microarray data. *Bioinformatics*, 28(3):446–447, 2012.

[187] Peter Glaus, Antti Honkela, and Magnus Rattray. Identifying differentially expressed transcripts from rna-seq data with biological variation. *Bioinformatics*, 28(13):1721–1728, 2012.

[188] Florian Gnad, Javier Estrada, and Jeremy Gunawardena. Proteus: A web-based, context-specific modelling tool for molecular networks. *Bioinformatics*, 28(9):1284–1286, 2012.

[189] Stephanie M. Gogarten, Tushar Bhangale, Matthew P. Conomos, Cecelia A. Laurie, Caitlin P. McHugh, Ian Painter, Xiuwen Zheng, David R. Crosslin, David Levine, Thomas Lumley, Sarah C. Nelson, Kenneth Rice, Jess Shen, Rohit Swarnkar, Bruce S. Weir, and Cathy C. Laurie. Gwastools: An r/bioconductor package for quality control and analysis of genome-wide association studies. *Bioinformatics*, 28(24):3329–3331, 2012.

[190] Wilson Wen Bin Goh, Hirotaka Oikawa, Judy Chia Ghee Sng, Marek Sergot, and Limsoon Wong. The role of mirnas in complex formation and control. *Bioinformatics*, 28(4):453–456, 2012.

[191] Jonathan Göke, Marcel H. Schulz, Julia Lasserre, and Martin Vingron. Estimation of pairwise sequence similarity of mammalian enhancers with word neighbourhood counts. *Bioinformatics*, 28(5):656–663, 2012.

[192] David Golan, Yaniv Erlich, and Saharon Rosset. Weighted pooling — practical and cost-effective techniques for pooled high-throughput sequencing. *Bioinformatics*, 28(12):197–206, 2012.

[193] Tatyana Goldberg, Tobias Hamp, and Burkhard Rost. Loctree2 predicts localization for all domains of life. *Bioinformatics*, 28(18):458–465, 2012.

[194] Jacqueline I. Goldstein, Andrew Crenshaw, Jason Carey, George B. Grant, Jared Maguire, Menachem Fromer, Colm O'Dushlaine, Jennifer L. Moran, Kimberly Chambert, Christine Stevens, Swedish Schizophrenia Consortium, ARRA Autism Sequencing Consortium, Pamela Sklar, Christina M. Hultman, Shaun Purcell, Steven A. McCarroll, Patrick F. Sullivan, Mark J. Daly, and Benjamin M. Neale. zcall: A rare variant caller for array-based genotyping. *Bioinformatics*, 28(19):2543–2545, 2012.

[195] V.M. Gonçalves-Almeida, D.E.V. Pires, R.C. de Melo-Minardi, C.H. da Silveira, W. Meira, and M.M. Santoro. Hydropace: Understanding and predicting cross-inhibition in serine proteases through hydrophobic patch centroids. *Bioinformatics*, 28(3):342–349, 2012.

[196] M. Gönen. Predicting drug-target interactions from chemical and genomic kernels using bayesian matrix factorization. *Bioinformatics*, 28(18):2304–2310, 2012.

[197] Antonio Gonzalez, Jesse Stombaugh, Christian L. Lauber, Noah Fierer, and Rob Knight. Sitepainter: A tool for exploring biogeographical patterns. *Bioinformatics*, 28(3):436–438, 2012.

[198] Santi González, Bàrbara Montserrat-Sentís, Friman Sánchez, Montserrat Puiggròs, Enrique Blanco, Alex Ramirez, and David Torrents. Rela, a local alignment search tool for the identification of distal and proximal gene regulatory regions and their conserved transcription factor binding sites. *Bioinformatics*, 28(6):763–770, 2012.

[199] Dmitry Grapov and John W. Newman. imdev: A graphical user interface to r multivariate analysis tools in microsoft excel. *Bioinformatics*, 28(17):2288–2290, 2012.

[200] Johannes Gräßler, Dirk Koschützki, and Falk Schreiber. Centilib: Comprehensive analysis and exploration of network centralities. *Bioinformatics*, 28(8):1178–1179, 2012.

[201] A. Gray, I. Stewart, and A. Tenesa. Advanced complex trait analysis. *Bioinformatics*, 28(23):3134–3136, 2012.

[202] Vanessa E. Gray, Kimberly R. Kukurba, and Sudhir Kumar. Performance of computational tools in evaluating the functional impact of laboratory-induced amino acid mutations. *Bioinformatics*, 28(16):2093–2096, 2012.

[203] Alexey A. Gritsenko, Jurgen F. Nijkamp, Marcel J.T. Reinders, and Dick de Ridder. Grass: A generic algorithm for scaffolding next-generation sequencing assemblies. *Bioinformatics*, 28(11):1429–1437, 2012.

[204] Anika Groß, Michael Hartung, Kay Prüfer, Janet Kelso, and Erhard Rahm. Impact of ontology evolution on functional analyses. *Bioinformatics*, 28(20):2671–2677, 2012.

[205] Bettina Grün, Theresa Scharl, and Friedrich Leisch. Modelling time course gene expression data with finite mixtures of linear additive models. *Bioinformatics*, 28(2):222–228, 2012.

[206] Jinghua Gu, Jianhua Xuan, Rebecca B. Riggins, Li Chen, Yue Wang, and Robert Clarke. Robust identification of transcriptional regulatory networks using a gibbs sampler on outlier sum statistic. *Bioinformatics*, 28(15):1990–1997, 2012.

[207] Valentin Guignon, Gaëtan Droc, Michael Alaux, Franc-Christophe Baurens, Olivier Garsmeur, Claire Poiron, Tim Carver, Mathieu Rouard, and Stéphanie Bocs. Chado controller: Advanced annotation management with a community annotation system. *Bioinformatics*, 28(7):1054–1056, 2012.

[208] Ergun Gumus, Olcay Kursun, Ahmet Sertbas, and Duran Ustek. Application of canonical correlation analysis for identifying viral integration preferences. *Bioinformatics*, 28(5):651–655, 2012.

[209] Vikas Gupta, Katharina Markmann, Christian N.S. Pedersen, Jens Stougaard, and Stig U. Andersen. shortran : A pipeline for small rna-seq data analysis. *Bioinformatics*, 28(20):2698–2700, 2012.

[210] Daniel Gusenleitner, Eleanor A. Howe, Stefan Bentink, John Quackenbush, and Aedín C. Culhane. ibbig: Iterative binary bi-clustering of gene sets. *Bioinformatics*, 28(19):2484–2492, 2012.

[211] Arief Gusnanto, Henry M. Wood, Yudi Pawitan, Pamela Rabbitts, and Stefano Berri. Correcting for cancer genome size and tumour cell content enables better estimation of copy number alterations from next-generation sequence data. *Bioinformatics*, 28(1):40–47, 2012.

[212] Attila Gyenesei, Jonathan Moody, Colin A.M. Semple, Chris S. Haley, and Wen-Hua Wei. High-throughput analysis of epistasis in genome-wide association studies with biforce. *Bioinformatics*, 28(15):1957–1964, 2012.

[213] Lukas Habegger, Suganthi Balasubramanian, David Z. Chen, Ekta Khurana, Andrea Sboner, Arif Harmanci, Joel Rozowsky, Declan Clarke, Michael Snyder, and Mark Gerstein. Vat: A computational framework to functionally annotate variants in personal genomes within a cloud-computing environment. *Bioinformatics*, 28(17):2267–2269, 2012.

[214] Faraz Hach, Ibrahim Numanagić, Can Alkan, and S. Cenk Sahinalp. Scalce: Boosting sequence compression algorithms using locally consistent encoding. *Bioinformatics*, 28(23):3051–3057, 2012.

[215] Iman Hajirasouliha, Alexander Schönhuth, David de Juan, Alfonso Valencia, and S. Cenk Sahinalp. Mirroring co-evolving trees in the light of their topologies. *Bioinformatics*, 28(9):1202–1208, 2012.

[216] T. Handorf and E. Klipp. Modeling mechanistic biological networks: An advanced boolean approach. *Bioinformatics*, 28(4):557–563, 2012.

[217] Jie Hao, William Astle, Maria De Iorio, and Timothy Ebbels. Batman — an r package for the automated quantification of metabolites from nuclear magnetic resonance spectra using a bayesian model. *Bioinformatics*, 28(15):2088–2090, 2012.

[218] Thomas J. Hardcastle, Krystyna A. Kelly, and David C. Baulcombe. Identifying small interfering rna loci from high-throughput sequencing data. *Bioinformatics*, 28(4):457–463, 2012.

[219] Tim Harder, Mikael Borg, Wouter Boomsma, Peter Røgen, and Thomas Hamelryck. Fast large-scale clustering of protein structures using gauss integrals. *Bioinformatics*, 28(4):510–515, 2012.

[220] Nathan Harmston, Wendy Filsell, and Michael P.H. Stumpf. Which species is it? species-driven gene name disambiguation using random walks over a mixture of adjacency matrices. *Bioinformatics*, 28(2):254–260, 2012.

[221] Elena Y. Harris, Nadia Ponts, Karine G. Le Roch, and Stefano Lonardi. Brat-bw: Efficient and accurate mapping of bisulfite-treated reads. *Bioinformatics*, 28(13):1795–1796, 2012.

[222] Michael Hartung, Anika Gross, and Erhard Rahm. Codex: Exploration of semantic changes between ontology versions. *Bioinformatics*, 28(6):895–896, 2012.

[223] Tatsunori Hashimoto, Tommi Jaakkola, Richard Sherwood, Esteban O. Mazzoni, Hynek Wichterle, and David Gifford. Lineage-based identification of cellular states and expression programs. *Bioinformatics*, 28(12):250–257, 2012.

[224] Hiroshi Hatsuda. Finding differentially expressed regions of arbitrary length in quantitative genomic data based on marked point process model. *Bioinformatics*, 28(18):633–639, 2012.

[225] Sikander Hayat and Arne Elofsson. Boctopus: Improved topology prediction of transmembrane β barrel proteins. *Bioinformatics*, 28(4):516–522, 2012.

[226] Sikander Hayat and Arne Elofsson. Ranking models of transmembrane β-barrel proteins using z-coordinate predictions. *Bioinformatics*, 28(12):90–96, 2012.

[227] Catherine A. Hayes, Szilard Nemes, and Niclas G. Karlsson. Statistical analysis of glycosylation profiles to compare tissue type and inflammatory disease state. *Bioinformatics*, 28(13):1669–1676, 2012.

[228] Feng He, Jie Ren, Wei Wang, and Jun Ma. Evaluating the drosophila bicoid morphogen gradient system through dissecting the noise in transcriptional bursts. *Bioinformatics*, 28(7):970–975, 2012.

[229] Zengyou He and Haipeng Gong. Comments on “mmfph: A maximal motif finder for phosphoproteomics datasets”. *Bioinformatics*, 28(16):2211–2212, 2012.

[230] J.W. Heal, J.E. Jimenez-Roldan, S.A. Wells, R.B. Freedman, and R.A. Römer. Inhibition of hiv-1 protease: The rigidity perspective. *Bioinformatics*, 28(3):350–357, 2012.

[231] Markus Heinonen, Huibin Shen, Nicola Zamboni, and Juho Rousu. Metabolite identification and molecular fingerprint prediction through machine learning. *Bioinformatics*, 28(18):2333–2341, 2012.

[232] Thomas Hentrich, Julia M. Schulze, Eldon Emberly, and Michael S. Kobor. Chromatra: A galaxy tool for visualizing genome-wide chromatin signatures. *Bioinformatics*, 28(5):717–718, 2012.

[233] A. Herbig, G. Jäger, F. Battke, and K. Nieselt. Genomering: Alignment visualization based on supergenome coordinates. *Bioinformatics*, 28(12):7–15, 2012.

[234] Steffen Heyne, Fabrizio Costa, Dominic Rose, and Rolf Backofen. Graphclust: Alignment-free structural clustering of local rna secondary structures. *Bioinformatics*, 28(12):224–232, 2012.

[235] Rolf Hilker, Corinna Sickinger, Christian N.S. Pedersen, and Jens Stoye. Unimog — a unifying framework for genomic distance calculation and sorting based on dcj. *Bioinformatics*, 28(19):2509–2511, 2012.

[236] Steven M. Hill, Yiling Lu, Jennifer Molina, Laura M. Heiser, Paul T. Spellman, Terence P. Speed, Joe W. Gray, Gordon B. Mills, and Sach Mukherjee. Bayesian inference of signaling network topology in a cancer cell line. *Bioinformatics*, 28(21):2804–2810, 2012.

[237] Dorit S. Hochbaum, Chun-Nan Hsu, and Yan T. Yang. Ranking of multidimensional drug profiling data by fractional-adjusted bi-partitional scores. *Bioinformatics*, 28(12):106–114, 2012.

[238] Robert Hoehndorf, Michel Dumontier, and Georgios V. Gkoutos. Identifying aberrant pathways through integrated analysis of knowledge in pharmacogenomics. *Bioinformatics*, 28(16):2169–2175, 2012.

[239] Robert Hoehndorf, Midori A. Harris, Heinrich Herre, Gabriella Rustici, and Georgios V. Gkoutos. Semantic integration of physiology phenotypes with an application to the cellular phenotype ontology. *Bioinformatics*, 28(13):1783–1789, 2012.

[240] Jan Hoinka, Elena Zotenko, Adam Friedman, Zuben E. Sauna, and Teresa M. Przytycka. Identification of sequence-structure rna binding motifs for selex-derived aptamers. *Bioinformatics*, 28(12):215–223, 2012.

[241] David Hoksza and Daniel Svozil. Efficient rna pairwise structure comparison by setter method. *Bioinformatics*, 28(14):1858–1864, 2012.

[242] Dongwan Hong, Arang Rhie, Sung-Soo Park, Jongkeun Lee, Young Seok Ju, Sujung Kim, Saet-Byeol Yu, Thomas Bleazard, Hyun-Seok Park, Hwanseok Rhee, Hyonyong Chong, Kap-Seok Yang, Yeon-Su Lee, In-Hoo Kim, Jin Soo Lee, Jong-Il Kim, and Jeong-Sun Seo. Fx: An rna-seq analysis tool on the cloud. *Bioinformatics*, 28(5):721–723, 2012.

[243] Farhad Hormozdiari, Faraz Hach, S. Cenk Sahinalp, Evan E. Eichler, and Can Alkan. Corrigendum to “sensitive and fast mapping of di-base encoded reads”. *Bioinformatics*, 28(1):150–150, 2012. Originally in Bioinformatics, Vol. 27, 2011, No. 4, 1915-1921.

[244] Adam Hospital, Pau Andrio, Carles Fenollosa, Damjan Cicin-Sain, Modesto Orozco, and Josep Lluís Gelpí. Mdweb and mdmoby: An integrated web-based platform for molecular dynamics simulations. *Bioinformatics*, 28(9):1278–1279, 2012.

[245] Valerie Hower, Richard Starfield, Adam Roberts, and Lior Pachter. Quantifying uniformity of mapped reads. *Bioinformatics*, 28(20):2680–2682, 2012.

[246] Jinyu Hu and David Zhiwei Gao. Distinction immune genes of hepatitis-induced heptatocellular carcinoma. *Bioinformatics*, 28(24):3191–3194, 2012.

[247] Jun Hu, Huanying Ge, Matt Newman, and Kejun Liu. Osa: A fast and accurate alignment tool for rna-seq. *Bioinformatics*, 28(14):1933–1934, 2012.

[248] Ming Hu, Ke Deng, Siddarth Selvaraj, Zhaohui Qin, Bing Ren, and Jun S. Liu. Hicnorm: Removing biases in hi-c data via poisson regression. *Bioinformatics*, 28(23):3131–3133, 2012.

[249] Ming Hu, Yu Zhu, Jeremy M.G. Taylor, Jun S. Liu, and Zhaohui S. Qin. Using poisson mixed-effects model to quantify transcript-level gene expression in rna-seq. *Bioinformatics*, 28(1):63–68, 2012.

[250] Xuesong Hu, Jianying Yuan, Yujian Shi, Jianliang Lu, Binghang Liu, Zhenyu Li, Yanxiang Chen, Desheng Mu, Hao Zhang, Nan Li, Zhen Yue, Fan Bai, Heng Li, and Wei Fan. pirs: Profile-based illumina pair-end reads simulator. *Bioinformatics*, 28(11):1533–1535, 2012.

[251] Hanwen Huang, Xiaosun Lu, Yufeng Liu, Perry Haaland, and J.S. Marron. R/dwd: Distance-weighted discrimination for classification, visualization and batch adjustment. *Bioinformatics*, 28(8):1182–1183, 2012.

[252] J. Huang, V. Renault, J. Sengen‘es, N. Touleimat, S. Michel, M. Lathrop, and J. Tost. Meqa: A pipeline for medip-seq data quality assessment and analysis. *Bioinformatics*, 28(4):587–588, 2012.

[253] Ting Huang and Zengyou He. A linear programming model for protein inference problem in shotgun proteomics. *Bioinformatics*, 28(22):2956–2962, 2012.

[254] Weichun Huang, Leping Li, Jason R. Myers, and Gabor T. Marth. Art: A next-generation sequencing read simulator. *Bioinformatics*, 28(4):593–594, 2012.

[255] Yi-Fei Huang and G. Brian Golding. Inferring sequence regions under functional divergence in duplicate genes. *Bioinformatics*, 28(2):176–183, 2012.

[256] Franziska Hufsky, Kai Dührkop, Florian Rasche, Markus Chimani, and Sebastian Böcker. Fast alignment of fragmentation trees. *Bioinformatics*, 28(12):265–273, 2012.

[257] Ling-Hong Hung and Ram Samudrala. Accelerated protein structure comparison using tm-score-gpu. *Bioinformatics*, 28(16):2191–2192, 2012.

[258] Vân Anh Huynh-Thu, Yvan Saeys, Louis Wehenkel, and Pierre Geurts. Statistical interpretation of machine learning-based feature importance scores for biomarker discovery. *Bioinformatics*, 28(13):1766–1774, 2012.

[259] Doug Hyatt, Philip F. LoCascio, Loren J. Hauser, and Edward C. Uberbacher. Gene and translation initiation site prediction in metagenomic sequences. *Bioinformatics*, 28(17):2223–2230, 2012.

[260] Doug Hyatt and Chongle Pan. Exhaustive database searching for amino acid mutations in proteomes. *Bioinformatics*, 28(14):1895–1901, 2012.

[261] Ernesto Iacucci, Léon-Charles Tranchevent, Dusan Popovic, Georgios A. Pavlopoulos, Bart De Moor, Reinhard Schneider, and Yves Moreau. Reliance: A machine learning and literature-based prioritization of receptor — ligand pairings. *Bioinformatics*, 28(18):569–574, 2012.

[262] Ovidiu D. Iancu, Sunita Kawane, Daniel Bottomly, Robert Searles, Robert Hitzemann, and Shannon McWeeney. Utilizing rna-seq data for de novo coexpression network inference bioinformatics. *Bioinformatics*, 28(12):1592–1597, 2012.

[263] Natsuhiro Ichinose, Tetsushi Yada, and Osamu Gotoh. Large-scale motif discovery using dna gray code and equiprobable oligomers. *Bioinformatics*, 28(1):25–31, 2012.

[264] Christopher J.R. Illingworth and Ville Mustonen. A method to infer positive selection from marker dynamics in an asexual population. *Bioinformatics*, 28(6):831–837, 2012.

[265] Günter Jäger, Florian Battke, and Kay Nieselt. Reveal — visual eqtl analytics. *Bioinformatics*, 28(18):542–548, 2012.

[266] Regis A. James, Mitchell M. Rao, Edward S. Chen, Margaret A. Goodell, and Chad A. Shaw. The hematopoietic expression viewer: Expanding mobile apps as a scientific tool. *Bioinformatics*, 28(14):1941–1942, 2012.

[267] Ashwini Jeggari, Debora S. Marks, and Erik Larsson. mircode: A map of putative microrna target sites in the long non-coding transcriptome. *Bioinformatics*, 28(15):2062–2063, 2012.

[268] Peiyong Jiang, K.C. Allen Chan, Gary J.W. Liao, Yama W.L. Zheng, Tak Y. Leung, Rossa W.K. Chiu, Yuk Ming Dennis Lo, and Hao Sun.

Fetalquant: Deducing fractional fetal dna concentration from massively parallel sequencing of dna in maternal plasma. *Bioinformatics*, 28(22):2883–2890, 2012.

[269] Yue Jiang, Yadong Wang, and Michael Brudno. Prism: Pair-read informed split-read mapping for base-pair level detection of insertion, deletion and structural variants. *Bioinformatics*, 28(20):2576–2583, 2012.

[270] Xiaoli Jiao, Brad T. Sherman, Da Wei Huang, Robert Stephens, Michael W. Baseler, H. Clifford Lane, and Richard A. Lempicki. David-ws: A stateful web service to facilitate gene/protein list analysis. *Bioinformatics*, 28(13):1805–1806, 2012.

[271] Natalia Jiménez-Lozano, Joan Segura, José Ramón Macías, Juanjo Vega, and José María Carazo. Integrating human and murine anatomical gene expression data for improved comparisons. *Bioinformatics*, 28(3):397–402, 2012.

[272] Kjell Johnson, Cen Guo, Mark Gosink, Vicky Wang, and Manfred Hauben. Multinomial modeling and an evaluation of common data-mining algorithms for identifying signals of disproportionate reporting in pharmacovigilance databases. *Bioinformatics*, 28(23):3123–3130, 2012.

[273] Bradley R. Jones, Ashok Rajaraman, Eric Tannier, and Cedric Chauve. Anges: Reconstructing ancestral genomes maps. *Bioinformatics*, 28(18):2388–2390, 2012.

[274] Daniel C. Jones, Walter L. Ruzzo, Xinxia Peng, and Michael G. Katze. A new approach to bias correction in rna-seq. *Bioinformatics*, 28(7):921–928, 2012.

[275] David T. Jones, Daniel W.A. Buchan, Domenico Cozzetto, and Massimiliano Pontil. Psicov: Precise structural contact prediction using sparse inverse covariance estimation on large multiple sequence alignments. *Bioinformatics*, 28(2):184–190, 2012.

[276] Hiren J. Joshi, Katy M. Christiansen, Joffrey Fitz, Jun Cao, Anna Lipzen, Joel Martin, A. Michelle Smith-Moritz, Len A. Pennacchio,

Wendy S. Schackwitz, Detlef Weigel, and Joshua L. Heazlewood. 1001 proteomes: A functional proteomics portal for the analysis of arabidopsis thaliana accessions. *Bioinformatics*, 28(10):1303–1306, 2012.

[277] Laurent Jourdren, Maria Bernard, Marie-Agn‘es Dillies, and Stéphane Le Crom. Eoulsan: A cloud computing-based framework facilitating high throughput sequencing analyses. *Bioinformatics*, 28(11):1542–1543, 2012.

[278] Ivan Kalev, Martin Mechelke, Klaus O. Kopec, Thomas Holder, Simeon Carstens, and Michael Habeck. Csb: A python framework for structural bioinformatics. *Bioinformatics*, 28(22):2996–2997, 2012.

[279] Manal Kalkatawi, Farania Rangkuti, Michael Schramm, Boris R. Jankovic, Allan Kamau, Rajesh Chowdhary, John A.C. Archer, and Vladimir B. Bajic. Dragon polya spotter: Predictor of poly(a) motifs within human genomic dna sequences. *Bioinformatics*, 28(1):127–129, 2012.

[280] Morten Källberg, Nitin Bhardwaj, Robert Langlois, and Hui Lu. A structure-based protocol for learning the family-specific mechanisms of membrane-binding domains. *Bioinformatics*, 28(18):431–437, 2012.

[281] Tomasz Kalwarczyk, Marcin Tabaka, and Robert Holyst. Biologistics — diffusion coefficients for complete proteome of escherichia coli. *Bioinformatics*, 28(22):2971–2978, 2012.

[282] Tom Kamphans and Peter M. Krawitz. Genetalk: An expert exchange platform for assessing rare sequence variants in personal genomes. *Bioinformatics*, 28(19):2515–2516, 2012.

[283] Chul Joo Kang and Paul Marjoram. Exact coalescent simulation of new haplotype data from existing reference haplotypes. *Bioinformatics*, 28(6):838–844, 2012.

[284] Lars J. Kangas, Thomas O. Metz, Giorgis Isaac, Brian T. Schrom, Bojana Ginovska-Pangovska, Luning Wang, Li Tan, Robert R. Lewis, and John H. Miller. In silico identification software (isis): A machine learning approach to tandem mass spectral identification of lipids. *Bioinformatics*, 28(13):1705–1713, 2012.

[285] Theofanis Karaletsos, Oliver Stegle, Christine Dreyer, John Winn, and Karsten M. Borgwardt. Shapepheno: Unsupervised extraction of shape phenotypes from biological image collections. *Bioinformatics*, 28(7):1001–1008, 2012.

[286] Alla Karnovsky, Terry Weymouth, Tim Hull, V. Glenn Tarcea, Giovanni Scardoni, Carlo Laudanna, Maureen A. Sartor, Kathleen A. Stringer, H.V. Jagadish, Charles Burant, Brian Athey, and Gilbert S. Omenn. Metscape 2 bioinformatics tool for the analysis and visualization of metabolomics and gene expression data. *Bioinformatics*, 28(3):373–380, 2012.

[287] Kazutaka Katoh and Martin C. Frith. Adding unaligned sequences into an existing alignment using mafft and last. *Bioinformatics*, 28(23):3144–3146, 2012.

[288] Shuji Kawaguchi, Kei Iida, Erimi Harada, Kousuke Hanada, Akihiro Matsui, Masanori Okamoto, Kazuo Shinozaki, Motoaki Seki, and Tetsuro Toyoda. Positional correlation analysis improves reconstruction of full-length transcripts and alternative isoforms from noisy array signals or short reads. *Bioinformatics*, 28(7):929–937, 2012.

[289] Darius Kazlauskas and Česlovas Venclovas. Two distinct ssb protein families in nucleo-cytoplasmic large dna viruses. *Bioinformatics*, 28(24):3186–3190, 2012.

[290] Matthew Kearse, Richard Moir, Amy Wilson, Steven Stones-Havas, Matthew Cheung, Shane Sturrock, Simon Buxton, Alex Cooper, Sidney Markowitz, Chris Duran, Tobias Thierer, Bruce Ashton, Peter Meintjes, and Alexei Drummond. Geneious basic: An integrated and extendable desktop software platform for the organization and analysis of sequence data. *Bioinformatics*, 28(12):1647–1649, 2012.

[291] Noppadon Khiripet, Wongarnet Khantuwan, and John R. Jungck. Kame: A voronoi image analyzer. *Bioinformatics*, 28(13):1802–1804, 2012.

[292] Halil Kilicoglu, Dongwook Shin, Marcelo Fiszman, Graciela Rosemblat, and Thomas C. Rindflesch. Semmeddb: A pubmed-scale repository of

biomedical semantic predications. *Bioinformatics*, 28(23):3158–3160, 2012.

[293] Ji-Hong Kim, Hae-Jin Hu, Seon-Hee Yim, Joon Seol Bae, Seon-Young Kim, and Yeun-Jun Chung. Cnvruler: A copy number variation-based case-control association analysis tool. *Bioinformatics*, 28(13):1790–1792, 2012.

[294] Kyungpil Kim, Keni Jiang, Siew Leng Teng, Lewis J. Feldman, and Haiyan Huang. Using biologically interrelated experiments to identify pathway genes in arabidopsis. *Bioinformatics*, 28(6):815–822, 2012.

[295] Seongho Kim, Imhoi Koo, Xiaoli Wei, and Xiang Zhang. A method of finding optimal weight factors for compound identification in gas chromatography-mass spectrometry. *Bioinformatics*, 28(8):1158–1163, 2012.

[296] Sun Kim, Dongseop Kwon, Soo-Yong Shin, and W. John Wilbur. Pie the search: Searching pubmed literature for protein interaction information. *Bioinformatics*, 28(4):597–598, 2012.

[297] Paul Kirk, Jim E. Griffin, Richard S. Savage, Zoubin Ghahramani, and David L. Wild. Bayesian correlated clustering to integrate multiple datasets. *Bioinformatics*, 28(24):3290–3297, 2012.

[298] Hisanori Kiryu and Kiyoshi Asai. Rchange: Algorithms for computing energy changes of rna secondary structures in response to base mutations. *Bioinformatics*, 28(8):1093–1101, 2012.

[299] Michael Klann, Arnab Ganguly, and Heinz Koeppl. Hybrid spatial gillespie and particle tracking simulation. *Bioinformatics*, 28(18):549–555, 2012.

[300] Johannes Klein, Stefan Leupold, Ilona Biegler, Rebekka Biedendieck, Richard Münch, and Dieter Jahn. Tlm-tracker: Software for cell segmentation, tracking and lineage analysis in time-lapse microscopy movies. *Bioinformatics*, 28(17):2276–2277, 2012.