References

[1] M.D. Atkinson and J.S. Heslop-Harrison. A simple method of hidden-line removal in three-dimensional modelling: Hiding the problem behind filled polygons. *Bioinformatics*, 6(1):55–56, 1990.

[2] I.E. Auger and C.E. Lawrence. Identification of the most significant amphipathic helix with application to hiv and mhv envelope proteins. *Bioinformatics*, 6(3):165–171, 1990.

[3] W. Bains. A program to optimize dna sequences for protein expression. *Bioinformatics*, 6(4):399–400, 1990.

[4] P.L. Bellon and S. Lanzavecchia. Polca, a library running in a modern environment, implements a protocol for averaging randomly oriented images. *Bioinformatics*, 6(3):271–277, 1990.

[5] Y. Bengio and Y. Pouliot. Efficient recognition of immunoglobulin domains from amino acid sequences using a neural network. *Bioinformatics*, 6(4):319–324, 1990.

[6] F. Blanca, C. Ferraz, J. Sri Widada, and J.P. Liautard. Quantitative analysis of the selective pressure exerted on homologous proteins. *Bioinformatics*, 6(3):223–228, 1990.

[7] C.G. Bridges. Olga-oligonucleotide primer design program for the atari st. *Bioinformatics*, 6(2):124–125, 1990.

[8] D.L. Brutlag, J.P. Dautricourt, S. Maulik, and J. Relph. Improved sensitivity of biological sequence database searches. *Bioinformatics*, 6(3):237–245, 1990.

[9] J.H Chen, S.Y. Le, B. Shapiro, K.M. Currey, and J.V. Maizel. A computational procedure for assessing the significance of rna secondary structure. *Bioinformatics*, 6(1):7–18, 1990.

[10] K.J. Cios, R.E. Freasier, L.S. Goodenday, and L.T. Andrews. An expert system for diagnosis of coronary artery stenosis based on 201ti scintigrams using the dempster-shafer theory of evidence. *Bioinformatics*, 6(4):333–342, 1990.

[11] J.H. Correia. Management of personal bibliographic reference using a simple database program. *Bioinformatics*, 6(2):126–127, 1990.

[12] P. Dessen, C. Fondrat, C. Valencien, and C. Mugnier. Bisance: A french service for access to biomolecular sequence databases. *Bioinformatics*, 6(4):355–356, 1990.

[13] A. Diaspro, P. Scelza, and C. Nicolini. Mucids: An operative c environment for acquisition and processing of polarized-light scattered from biological specimens. *Bioinformatics*, 6(3):229–236, 1990.

[14] J. Dopazo. Multiple sequence editing by spreadsheet. *Bioinformatics*, 6(4):401–402, 1990.

[15] M. Dubnick and D.W. Mount. Splice, a computer program for automated extraction of information from genbank sequence entries. *Bioinformatics*, 6(4):343–346, 1990.

[16] M. Eberhard. A set of programs for analysis of kinetic and equilibrium data. *Bioinformatics*, 6(3):213–221, 1990.

[17] C.A. Fields and C.A. Soderlund. gm: A practical tool for automating dna sequence analysis. *Bioinformatics*, 6(3):263–270, 1990.

[18] T.H. Fischer and G.C. White II. The development of a high-order taylor expansion solution to the chemical rate equation for the simulation of complex biochemical systems. *Bioinformatics*, 6(3):173–177, 1990.

[19] R. Fuchs. Free molecular biological software available from the embl file server. *Bioinformatics*, 6(2):120–121, 1990.

[20] K.P Fung and J. Lee. Basic program to assess the extent and pattern of agreement between two procedures. *Bioinformatics*, 6(1):54–54, 1990.

[21] A.E. Gabrielian, V.S. Ivanov, and A.T. Kozhich. On searching for the active sites in proteins and peptide hormones. *Bioinformatics*, 6(1):1–2, 1990.

[22] D. Gautheret, F. Major, and R. Cedergren. Pattern searching/alignment with rna primary and secondary structures: An effective descriptor for trna. *Bioinformatics*, 6(4):325–331, 1990.

[23] N. Gautier and A. Pave. Object-centered representation for species systematics and identification in living systems in nature. *Bioinformatics*, 6(4):383–386, 1990.

[24] D.G. Gilbert. Dot plot sequence comparisons on macintosh computers. *Bioinformatics*, 6(2):117–117, 1990.

[25] D.G. Gilbert. Two hypercard calculators for molecular biology. *Bioinformatics*, 6(2):113–116, 1990.

[26] J. Gomel. A fast algorithm for evaluating an approximation to the information enclosed within coronas and their sectors in square matrices. *Bioinformatics*, 6(1):19–21, 1990.

[27] A.V Grigorjev and A.A. Mironov. Mapping dna by stochastic relaxation: A new approach to fragment sizes. *Bioinformatics*, 6(2):107–111, 1990.

[28] B. Henrissat, E. Raimbaud, V. Tran, and J.P. Mornon. Hcaband: A computer program for the 2d-helical representation of protein sequences. *Bioinformatics*, 6(1):3–5, 1990.

[29] G.Z Hertz, G.W. Hartzell III, and G.D. Stormo. Identification of consensus patterns in unaligned dna sequences known to be functionally related. *Bioinformatics*, 6(2):81–92, 1990.

[30] S.T. Ho, L. Allison, and C.N. Yee. Restriction site mapping for three or more enzymes. *Bioinformatics*, 6(3):195–204, 1990.

[31] H.G. Holzhutter and A. Colosimo. Simfit: A microcomputer software-toolkit for modelistic studies in biochemistry. *Bioinformatics*, 6(1):23–28, 1990.

[32] X.Q. Huang, R.C. Hardison, and W. Miller. A space-efficient algorithm for local similarities. *Bioinformatics*, 6(4):373–381, 1990.

[33] P.R Hunter. A character separation index suitable for binary data containing equivocal responses. *Bioinformatics*, 6(2):67–69, 1990.

[34] K. Jiang, J. Zheng, S.B. Higgins, D.M. Watterson, T.A. Craig, T.J. Lukas, and L.J. Van Eldik. A knowledge-based experimental design system for nucleic acid engineering. *Bioinformatics*, 6(3):205–212, 1990.

[35] G.J. Kemp and P.M. Gray. Finding hydrophobic microdomains using an object-oriented database. *Bioinformatics*, 6(4):357–363, 1990.

[36] J. Kleffe and U. Langbecker. Exact computation of pattern probabilities in random sequences generated by markov chains. *Bioinformatics*, 6(4):347–353, 1990.

[37] J. Mandler and S. Ludwig. Subsis: Dnasis/prosis subdirectory management. *Bioinformatics*, 6(3):291–292, 1990.

[38] P.L. Mauri, M. Bitonti, M. Pace, P.G. Pietta, and D. Agnellini. Automatic computation of enzyme kinetics by hplc. *Bioinformatics*, 6(4):395–398, 1990.

[39] J.I. Mechanick and C.S. Peskin. A c version of fourier-derived affinity spectrum analysis (fasa) to resolve binding heterogeneity. *Bioinformatics*, 6(3):189–194, 1990.

[40] L. Menendez-Arias and R. Rodriguez. A basic microcomputer program for prediction of b and t cell epitopes in proteins. *Bioinformatics*, 6(2):101–105, 1990.

[41] W. Miller, J. Ostell, and K.E. Rudd. An algorithm for searching restriction maps. *Bioinformatics*, 6(3):247–252, 1990.

[42] R.F. Mott and T.B. Kirkwood. Statsearch: A gcg-compatible program for assessing statistical significance during dna and protein databank searches. *Bioinformatics*, 6(3):293–295, 1990.

[43] R. Myers, S. Olsen, and S. Maloy. Computer programs for the rapid determination of enzyme kinetics on ms-dos compatible microcomputers. *Bioinformatics*, 6(2):63–65, 1990.

[44] R. Myers, S. Olson, and S. Maloy. Computer programs for the rapid determination of enzyme kinetics on ms-dos compatible microcomputers. *Bioinformatics*, 6(1):51–53, 1990.

[45] P. Petrilli, C. Caporale, and C. Sepe. Prolang: An expandable software in protein chemistry. *Bioinformatics*, 6(2):128–130, 1990.

[46] P. Petrilli, C. Sepe, D. Picone, C. Caporale, and C. Caruso. Prolang: The scan command. *Bioinformatics*, 6(4):403–403, 1990.

[47] M.F. Petrini, T.M. Dwyer, M.A. Wall, J.K. Mansel, and J.R. Norman. Communication between the pc and laboratory instruments. *Bioinformatics*, 6(3):161–164, 1990.

[48] N.D. Rawlings and A.J. Barrett. Flusys: A software package for the collection and analysis of kinetic and scanning data from perkin-elmer fluorimeters. *Bioinformatics*, 6(2):118–119, 1990.

[49] A.H. Reisner, C.A. Bucholtz, G.A. Bell, K. Tsui, D. Rosenfeld, and G.T. Herman. Two- and three-dimensional image reconstructions from stained and autoradiographed histological sections. *Bioinformatics*, 6(3):253–261, 1990.

[50] B. Rossaro. Some programs useful for managing data in ecology, taxonomy and zoogeography. *Bioinformatics*, 6(3):289–290, 1990.

[51] B.A. Shapiro and K.Z. Zhang. Comparing multiple rna secondary structures using tree comparisons. *Bioinformatics*, 6(4):309–318, 1990.

[52] P.R. Sibbald and P. Argos. Scrutineer: A computer program that flexibly seeks and describes motifs and profiles in protein sequence databases. *Bioinformatics*, 6(3):279–288, 1990. see Erratum in Comput. Appl. Biosci., Vol. 6, 1990, No. 4, 431-431.

[53] J.M Smith and D.J. Thomas. Quantitative analysis of one-dimensional gel electrophoresis profiles. *Bioinformatics*, 6(2):93–99, 1990.

[54] M.L. Sparling. Analysis of mixed lipid extracts using 1h nmr spectra. *Bioinformatics*, 6(1):29–42, 1990.

[55] R. Staden. An improved sequence handling package that runs on the apple macintosh. *Bioinformatics*, 6(4):387–393, 1990.

[56] R.O. Stephen, P.M. Shelton, and M.S. Bradshaw. Generating precise mechanical stimuli and recording chordotonal organ discharge patterns using a microcomputer. *Bioinformatics*, 6(3):179–188, 1990.

[57] G.M. Suboch and Yu.A. Sprizhitsky. Statistical significance of some complex nucleotide combinations: A comparison of dna models. *Bioinformatics*, 6(1):43–48, 1990.

[58] A. Viari, H. Soldano, and E. Ollivier. A scale-independent signal processing method for sequence analysis. *Bioinformatics*, 6(2):71–80, 1990.

[59] G.W. Williams and G.P. Gibbs. Automatic updating of the embl database via ebmnet. *Bioinformatics*, 6(2):122–123, 1990.

[60] S. Winker, R. Overbeek, C.R. Woese, G.J. Olsen, and N. Pfluger. Structure detection through automated covariance search. *Bioinformatics*, 6(4):365–371, 1990.

[61] P. Wozniak and W. Makalowski. Searching for trna genes in dna sequences — an ibm microcomputer program. *Bioinformatics*, 6(1):49–50, 1990.