References

[1] P.H. Abbrecht, I.M. Thio, and R.R. Kyle. A simple algorithm for averaging multiple cycles of waveforms having varying cycle periods. *Bioinformatics*, 7(4):489–493, 1991.

[2] P. Arrigo, F. Giuliano, F. Scalia, A. Rapallo, and G. Damiani. Identification of a new motif on nucleic acid sequence data using kohonen's self-organizing map. *Bioinformatics*, 7(3):353–357, 1991.

[3] A. Bairoch. Seqanalref: A sequence analysis bibliographic reference databank. *Bioinformatics*, 7(2):268–268, 1991.

[4] S.S. Ball, V.H. Mah, and P.L. Miller. Senex: A computer-based representation of cellular signal transduction processes in the central nervous system. *Bioinformatics*, 7(2):175–187, 1991.

[5] J. Baranyi and T. Illeni. A back-step algorithm for simulation of monod-type models. *Bioinformatics*, 7(3):399–401, 1991.

[6] S. Barron, M. Witten, R. Harkness, and J. Driver. A bibliography on computational algorithms in molecular biology and genetics. *Bioinformatics*, 7(2):269–269, 1991.

[7] G.J. Barton. Scanning protein sequence databanks using a distributed processing workstation network. *Bioinformatics*, 7(1):85–88, 1991.

[8] A. Bekker, S. Von Hagen, and J. Yarmush. A macintosh hypercard stack to simulate the pharmacokinetics of infusion of intravenous anesthetic drugs (narsim). *Bioinformatics*, 7(4):531–532, 1991.

[9] M.P. Berger and P.J. Munson. A novel randomized iterative strategy for aligning multiple protein sequences. *Bioinformatics*, 7(4):479–484, 1991.

[10] P. Blaise and C. Gessler. Geobase: A simple geographical information system on a personal computer. *Bioinformatics*, 7(2):155–160, 1991.

[11] J.A. Bradshaw, K.J. Carden, and D. Riordan. Ecological applications using a novel expert system shell. *Bioinformatics*, 7(1):79–83, 1991.

[12] R.J. Brammer, T.N. Bryant, and J.H. May. Investigation of an expert systems approach to bacterial identification. *Bioinformatics*, 7(4):461–469, 1991.

[13] J.W. Brown. Materials methods: A macintosh hypercard stack for laboratory protocols. *Bioinformatics*, 7(3):397–397, 1991.

[14] J.W. Brown. Phylogenetic comparative analysis of rna structure on macintosh computers. *Bioinformatics*, 7(3):391–393, 1991.

[15] D.L. Brutlag, A.R. Galper, and D.H. Millis. Knowledge-based simulation of dna metabolism: Prediction of enzyme action. *Bioinformatics*, 7(1):9–19, 1991.

[16] T.N. Bryant. Software for the development and evaluation of probabilistic identification matrices. *Bioinformatics*, 7(2):189–193, 1991.

[17] R.S. Carmenes. Lstsq: A module for reliable constrained and unconstrained nonlinear regression. *Bioinformatics*, 7(3):373–378, 1991.

[18] C. Chappey, A. Danckaert, P. Dessen, and S. Hazout. Mash: An interactive program for multiple alignment and consensus sequence construction for biological sequences. *Bioinformatics*, 7(2):195–202, 1991.

[19] E.A. Cheever, G.C. Overton, and D.B. Searls. Fast fourier transform-based correlation of dna sequences using complex plane encoding. *Bioinformatics*, 7(2):143–154, 1991.

[20] M. Cheminant and R. Labia. The michaelis-menten equation: Computing substrate concentration as a function of time without restrictions on the initial conditions. *Bioinformatics*, 7(1):99–101, 1991.

[21] D.K. Chiu and T. Kolodziejczak. Inferring consensus structure from nucleic acid sequences. *Bioinformatics*, 7(3):347–352, 1991.

[22] J.M. Claverie and C. Daulmerie. Smoothing profiles with sliding windows: Better to wear a hat! *Bioinformatics*, 7(1):113–115, 1991.

[23] J. Collado-Vides. The search for a grammatical theory of gene regulation is formally justified by showing the inadequacy of context-free grammars. *Bioinformatics*, 7(3):321–326, 1991.

[24] A. Colosimo, E. Rota, and P. Omodeo. A hypercard program for the identification of biological specimens. *Bioinformatics*, 7(1):63–69, 1991. see Erratum in Comput. Appl. Biosci., Vol. 7, 1991, No. 2, 285-285.

[25] A. Cornish-Bowden and J.H. Hofmeyr. Metamodel: A program for modelling and control analysis of metabolic pathways on the ibm pc and compatibles. *Bioinformatics*, 7(1):89–93, 1991.

[26] A. Danckaert, C. Chappey, and S. Hazout. "size leap" algorithm: An efficient extraction of the longest common motifs from a molecular sequence set. application to the dna sequence reconstruction. *Bioinformatics*, 7(4):509–513, 1991.

[27] H.E. Dayringer and S.A. Sammons. Pollux: A program for simulated cloning, mutagenesis and database searching of dna constructs. *Bioinformatics*, 7(2):161–167, 1991.

[28] J.G. de Boer. Mars: A program to find potential restriction sites. *Bioinformatics*, 7(2):267–267, 1991. see Erratum in Comput. Appl. Biosci., Vol. 7, 1991, No. 3, 415-415.

[29] N.R. Deering and D. Shalloway. Gelmetric: Semi-automated electrophoretic mobility analysis. *Bioinformatics*, 7(1):109–110, 1991.

[30] A.S. Deshpande, D.S. Richards, and W.R. Pearson. A platform for biological sequence comparison on parallel computers. *Bioinformatics*, 7(2):237–247, 1991.

[31] G.H. Dibdin. Precise charge-coupling calculations for finite difference diffusion problems using a modification of the add-on algorithm q-couple. *Bioinformatics*, 7(2):261–263, 1991.

[32] A. Facchiano, F. Facchiano, R. Ragone, A. Facchiano, and G. Colonna. Converter: A program to convert crystallographic coordinates among different molecular graphics standards on pc-ibm platforms. *Bioinformatics*, 7(3):395–396, 1991.

[33] M. Farza and A. Cheruy. Cambio: Software for modelling and simulation of bioprocesses. *Bioinformatics*, 7(3):327–336, 1991.

[34] D.H. Fitch and M. Goodman. Phylogenetic scanning: A computer-assisted algorithm for mapping gene conversions and other recombinational events. *Bioinformatics*, 7(2):207–215, 1991.

[35] R. Fuchs. Macpattern: Protein pattern searching on the apple macintosh. *Bioinformatics*, 7(1):105–106, 1991.

[36] K.P. Fung and J. Lee. Basic: Program for polynomial regression and smoothing. *Bioinformatics*, 7(1):103–104, 1991.

[37] J. Garnier and J.M. Levin. The protein structure code: What is its present status? *Bioinformatics*, 7(2):133–142, 1991.

[38] C.J. Gartmann and U. Grob. A menu-shell for the gcg programs. *Bioinformatics*, 7(4):457–460, 1991.

[39] T.J. Gleeson and R. Staden. An x windows and unix implementation of our sequence analysis package. *Bioinformatics*, 7(3):398–398, 1991.

[40] M. Grabner and R. Hofbauer. A computer program for molecular weight determination of dna fragments (howbig). *Bioinformatics*, 7(3):317–319, 1991.

[41] U. Grob and C.J. Gartmann. Cool — a vax program for finding common oligomers in nucleic acid sequences. thyroid hormone receptor sequences used as an example. *Bioinformatics*, 7(3):379–381, 1991.

[42] R. Guigo, A. Johansson, and T.F. Smith. Automatic evaluation of protein sequence functional patterns. *Bioinformatics*, 7(3):309–315, 1991.

[43] M. Hauer-Jensen. Statistical analysis in dbase-compatible databases. *Bioinformatics*, 7(1):61–62, 1991.

[44] R. Hernandez, J.A. Esteban, M. Garcia, and F. Moran. Pashemos: A versatile program written in pascal to simulate patterns on the shells of molluscs, according to the meinhardt model. *Bioinformatics*, 7(2):169–174, 1991.

[45] A. Jacot-Descombes, K. Todorov, D.F. Hochstrasser, C. Pellegrini, and T. Pun. Laboimage: A workstation environment for research in image processing and analysis. *Bioinformatics*, 7(2):225–232, 1991.

[46] K.Y. Jiang, J. Zheng, and S.B. Higgins. A generic algorithm for finding restriction sites within dna sequences. *Bioinformatics*, 7(2):249–256, 1991.

[47] P.D. Karp. Artificial intelligence methods for theory representation and hypothesis formation. *Bioinformatics*, 7(3):301–308, 1991.

[48] C.G. Kozhukhin and P.A. Pevzner. Genome inhomogeneity is determined mainly by ww and ss dinucleotides. *Bioinformatics*, 7(1):39–49, 1991.

[49] I. Ladunga, F. Czako, I. Csabai, and T. Geszti. Improving signal peptide prediction accuracy by simulated neural network. *Bioinformatics*, 7(4):485–487, 1991.

[50] S.Y. Le, J.H. Chen, and J.V. Maizel. Detection of unusual rna folding regions in hiv and siv sequences. *Bioinformatics*, 7(1):51–55, 1991.

[51] T. Letellier, C. Reder, and J.P. Mazat. Control: Software for the analysis of the control of metabolic networks. *Bioinformatics*, 7(3):383–390, 1991.

[52] K. Lucas, M. Busch, S. Mossinger, and J.A. Thompson. An improved microcomputer program for finding gene- or gene family-specific oligonucleotides suitable as primers for polymerase chain reactions or as probes. *Bioinformatics*, 7(4):525–529, 1991.

[53] G. Mancini and A. Valbonesi. Mcs/sel/bas program — an overlapping clustering method with examples from mating type interactions of ciliated protozoa. *Bioinformatics*, 7(3):365–371, 1991.

[54] P.L. Miller, P.M. Nadkarni, and N.M. Carriero. Parallel computation and fasta: Confronting the problem of parallel database search for a fast sequence comparison algorithm. *Bioinformatics*, 7(1):71–78, 1991.

[55] W. Miller, J. Barr, and K.E. Rudd. Improved algorithms for searching restriction maps. *Bioinformatics*, 7(4):447–456, 1991.

[56] C.G. Moore. A didactic computer simulation of the environmental impact of a pollution discharge. *Bioinformatics*, 7(1):95–98, 1991.

[57] S. Morante and V. Parisi. Building structural models of peptides: A semi-automatic software. *Bioinformatics*, 7(1):21–26, 1991.

[58] M.P. Mujumdar. Monte carlo simulations of ionic channel selectivity. *Bioinformatics*, 7(3):359–364, 1991.

[59] R. Nussinov. Compositional variations in dna sequences. *Bioinformatics*, 7(3):287–293, 1991.

[60] R. Nussinov. Signals in dna sequences and their potential properties. *Bioinformatics*, 7(3):295–299, 1991.

[61] S.I. O'Donoghue. Structural interpretation of fluorescence resonance-energy transfer measurements. *Bioinformatics*, 7(4):471–477, 1991.

[62] P.J. O'Hara and D. Venezia. Primegen, a tool for designing primers from multiple alignments. *Bioinformatics*, 7(4):533–534, 1991.

[63] E. Ollivier, H. Soldano, and A. Viari. "multifrequency" location and clustering of sequence patterns from proteins. *Bioinformatics*, 7(1):31–38, 1991.

[64] D.J. Parry-Smith and T.K. Attwood. Somap: A novel interactive approach to multiple protein sequences alignment. *Bioinformatics*, 7(2):233–235, 1991.

[65] D.S. Prestridge. Signal scan: A computer program that scans dna sequences for eukaryotic transcriptional elements. *Bioinformatics*, 7(2):203–206, 1991.

[66] P. Reiner and M. Brenowitz. Quantitative densitometry of autoradiograms: Digital images representative of optical density. *Bioinformatics*, 7(3):337–340, 1991.

[67] P.J. Russell, J.M. Doenias, and S.J. Russell. Gelymac: A macintosh application for calculating dna fragment size from gel electrophoresis migration data. *Bioinformatics*, 7(2):265–266, 1991.

[68] J. Saldanha and J. Eccles. The application of ssadm to modelling the logical structure of proteins. *Bioinformatics*, 7(4):515–524, 1991.

[69] T.B. Schillen. Designing a neural network simulator — the mens modelling environment for network systems: I. *Bioinformatics*, 7(4):417–430, 1991.

[70] T.B. Schillen. Designing a neural network simulator — the mens modelling environment for network systems: Ii. *Bioinformatics*, 7(4):431–446, 1991.

[71] R. Schnobel. Integrated displays of aligned amino acid sequences and protein structures. *Bioinformatics*, 7(3):341–346, 1991.

[72] D. Shalloway and C. Royer. Smgws 2: Improved microcomputer-based three-dimensional stereoscopic macromolecular graphics display. *Bioinformatics*, 7(1):107–108, 1991.

[73] P.R. Sibbald, H. Sommerfeldt, and P. Argos. Automated protein sequence pattern handling and prosite searching. *Bioinformatics*, 7(4):535–536, 1991.

[74] P.R. Smith, A.J. Ropelewski, D.A. Balog, S. Gottesman, Deerfield II, and D.W. A simple approach for the distribution of computationally intense tasks in an heterogeneous environment: Distribution of the mdpp image-processing package. *Bioinformatics*, 7(4):501–507, 1991.

[75] R.H. Smith, S. Gottesman, B. Hobbs, E. Lear, D. Kristofferson, D. Benton, and P.R. Smith. A mechanism for maintaining an up-to-date genbank database via usenet. *Bioinformatics*, 7(1):111–112, 1991.

[76] J.L. Spouge. Fast optimal alignment. *Bioinformatics*, 7(1):1–7, 1991.

[77] F. Stefanini and A. Camussi. An apl procedure to estimate genotype by environment interaction when two environments are considered. *Bioinformatics*, 7(1):27–29, 1991.

[78] M.J. Sternberg. Promot: A fortran program to scan protein sequences against a library of known motifs. *Bioinformatics*, 7(2):257–260, 1991.

[79] G.M. Studnicka. Elisa assay optimization using hyperbolic regression. *Bioinformatics*, 7(2):217–224, 1991.

[80] P. Taylor, P. Rosenberg, and M.G. Samsonova. A new method for finding long consensus patterns in nucleic acid sequences. *Bioinformatics*, 7(4):495–500, 1991.

[81] A. Zaritsky and E. Forester. A simulation program to display specific digestion products of predicted rna foldings. *Bioinformatics*, 7(1):57–60, 1991.