References

[1] G.R. Abecasis and W.O.C. Cookson. Gold — graphical overview of linkage disequilibrium. *Bioinformatics*, 16(2):182–183, 2000.

[2] Josep F. Abril and Roderic Guigó. gff2ps: Visualizing genomic annotations. *Bioinformatics*, 16(8):743–744, 2000.

[3] Viatcheslav R. Akmaev, Scott T. Kelley, and Gary D. Stormo. Phylogenetically enhanced statistical tools for rna structure prediction. *Bioinformatics*, 16(6):501–512, 2000.

[4] Tatsuya Akutsu, Satoru Miyano, and Satoru Kuhara. Inferring qualitative relations in genetic networks and metabolic pathways. *Bioinformatics*, 16(8):727–734, 2000.

[5] Rui Alves and Michael A. Savageau. Comparing systemic properties of ensembles of biological networks by graphical and statistical methods. *Bioinformatics*, 16(6):527–533, 2000.

[6] Rui Alves and Michael A. Savageau. Extending the method of mathematically controlled comparison to include numerical comparisons. *Bioinformatics*, 16(9):786–798, 2000.

[7] Rui Alves and Michael A. Savageau. Systemic properties of ensembles of metabolic networks: Application of graphical and statistical methods to simple unbranched pathways. *Bioinformatics*, 16(6):534–547, 2000.

[8] Dimitris Anastassiou. Frequency-domain analysis of biomolecular sequences. *Bioinformatics*, 16(12):1073–1081, 2000.

[9] R. Apweiler, T.K. Attwood, A. Bairoch, A. Bateman, E. Birney, M. Biswas, P. Bucher, L. Cerutti, F. Corpet, M.D.R. Croning, R. Durbin, L. Falquet, W. Fleischmann, J. Gouzy, H. Hermjakob, N. Hulo, I. Jonassen, D. Kahn, A. Kanapin, Y. Karavidopoulou, R. Lopez, B. Marx, N.J. Mulder, T.M. Oinn, M. Pagni, F. Servant, C.J.A. Sigrist, and E.M. Zdobnov. Interpro — an integrated documentation resource for protein families, domains and functional sites. *Bioinformatics*, 16(12):1145–1150, 2000.

[10] A.G. Bachinsky, A.S. Frolov, A.N. Naumochkin, L.Ph. Nizolenko, and A.A. Yarigin. Prof_pat 1.3: Updated database of patterns used to detect local similarities. *Bioinformatics*, 16(4):358–366, 2000.

[11] Gary D. Bader and Christopher W.V. Hogue. Bind — a data specification for storing and describing biomolecular interactions, molecular complexes and pathways. *Bioinformatics*, 16(5):465–477, 2000.

[12] Timothy L. Bailey and Michael Gribskov. Concerning the accuracy of mast e-values. *Bioinformatics*, 16(5):488–489, 2000.

[13] Amos Bairoch. Serendipity in bioinformatics, the tribulations of a swiss bioinformatician through exciting times! *Bioinformatics*, 16(1):48–64, 2000.

[14] Pierre Baldi. On the convergence of a clustering algorithm for protein-coding regions in microbial genomes. *Bioinformatics*, 16(4):367–371, 2000.

[15] Pierre Baldi and Pierre-François Baisnée. Sequence analysis by additive scales: Dna structure for sequences and repeats of all lengths. *Bioinformatics*, 16(10):865–889, 2000.

[16] Pierre Baldi, Søren Brunak, Yves Chauvin, Claus A.F. Andersen, and Henrik Nielsen. Assessing the accuracy of prediction algorithms for classification: An overview. *Bioinformatics*, 16(5):412–424, 2000.

[17] Kevin G. Becker, Shawnte L. White, Jerri Muller, and James Engel. Bbid: The biological biochemical image database. *Bioinformatics*, 16(8):745–746, 2000.

[18] Joseph A. Bedell, Ian Korf, and Warren Gish. Maskeraid: A performance enhancement to repeatmasker. *Bioinformatics*, 16(11):1040–1041, 2000.

[19] T. Beißbarth, K. Fellenberg, B. Brors, R. Arribas-Prat, J.M. Boer, N.C. Hauser, M. Scheideler, J.D. Hoheisel, G. Schütz, A. Poustka, and M. Vingron. Processing and quality control of dna array hybridization data. *Bioinformatics*, 16(11):1014–1022, 2000.

[20] Eric Beitz. Texshade: Shading and labeling of multiple sequence alignments using latex2e. *Bioinformatics*, 16(2):135–139, 2000.

[21] Eric Beitz. T_extopo: Shaded membrane protein topology plots in latex2_e. *Bioinformatics*, 16(11):1050–1051, 2000.

[22] Jonathan Bingham and Sucha Sudarsanam. Visualizing large hierarchical clusters in hyperbolic space. *Bioinformatics*, 16(7):660–661, 2000.

[23] Christophe Blanchet, Christophe Combet, Christophe Geourjon, and Gilbert Deléage. Mpsa: Integrated system for multiple protein sequence analysis with client/server capabilities. *Bioinformatics*, 16(3):286–287, 2000.

[24] Simon Blomberg. Fels-rand: An xlisp-stat program for the comparative analysis of data under phylogenetic uncertainty. *Bioinformatics*, 16(11):1010–1013, 2000.

[25] Matthew Boone and Chris Upton. Blast search updater: A notification system for new database matches. *Bioinformatics*, 16(11):1054–1055, 2000.

[26] John Bouck, Michael P. McLeod, Kim Worley, and Richard A. Gibbs. The human transcript database: A catalogue of full length cdna inserts. *Bioinformatics*, 16(2):176–177, 2000.

[27] Philip E. Bourne and Michael Gribskov. Ismb-2000: Bioinformatics enters a new millennium. *Bioinformatics*, 16(9):749–749, 2000.

[28] Christopher M.L.S. Bouton and Jonathan Pevsner. Dragon: Database referencing of array genes online. *Bioinformatics*, 16(11):1038–1039, 2000.

[29] Andy Brass. Bioinformatics education — a uk perspective. *Bioinformatics*, 16(2):77–78, 2000.

[30] David F. Burke, Charlotte M. Deane, and Tom L. Blundell. Browsing the sloop database of structurally classified loops connecting elements of protein secondary structure. *Bioinformatics*, 16(6):513–519, 2000.

[31] Deyou Cai, Arthur Delcher, Ben Kao, and Simon Kasif. Modeling splice sites with bayes networks. *Bioinformatics*, 16(2):152–158, 2000.

[32] Andrea Califano. Splash: Structural pattern localization analysis by sequential histograms. *Bioinformatics*, 16(4):341–357, 2000.

[33] Stephen A. Cammer. Schism: Creating interactive web page annotations of molecular structure models using chime. *Bioinformatics*, 16(7):658–659, 2000.

[34] F. Campagne. Clustalnet: The joining of clustal and corba. *Bioinformatics*, 16(7):606–612, 2000.

[35] G. Cannarozzi, M.T. Hallett, J. Norberg, and X. Zhou. A cross-comparison of a large dataset of genes. *Bioinformatics*, 16(7):654–655, 2000.

[36] Ting Chen and Steven S. Skiena. A case study in genome-level fragment assembly. *Bioinformatics*, 16(6):494–500, 2000.

[37] Wooyoung Choe, Okan K. Ersoy, and Minou Bina. Neural network schemes for detecting rare events in human genomic dna. *Bioinformatics*, 16(12):1062–1072, 2000.

[38] Jeong-Hyeon Choi, Ho-Youl Jung, Hye-Sun Kim, and Hwan-Gue Cho. Phylodraw: A phylogenetic tree drawing system. *Bioinformatics*, 16(11):1056–1058, 2000.

[39] Raphaël Clifford and Aaron J. Mackey. Disperse: A simple and efficient approach to parallel database searching. *Bioinformatics*, 16(6):564–565, 2000.

[40] James A. Cuff, Ewan Birney, Michele E. Clamp, and Geoffrey J. Barton. Protest: Protein multiple sequence alignments from expressed sequence tags. *Bioinformatics*, 16(2):111–116, 2000.

[41] Antoine Danchin. A brief history of genome research and bioinformatics in france. *Bioinformatics*, 16(1):65–75, 2000.

[42] W.P.H. de Boer, J.J. Oudejans, C.J.L.M. Meijer, and J. Lankelma. Analysing gene expressions with grank. *Bioinformatics*, 19(15):2000–2001, 2003.

[43] Miquel de Càceres, Jordi Villà, Juan J. Lozano, and Ferran Sanz. Mipsim: Similarity analysis of molecular interaction potentials. *Bioinformatics*, 16(6):568–569, 2000.

[44] Kirill Degtyarenko. Bioinorganic motifs: Towards functional classification of metalloproteins. *Bioinformatics*, 16(10):851–864, 2000.

[45] Patrik D'haeseleer, Shoudan Liang, and Roland Somogyi. Genetic network inference: From co-expression clustering to reverse engineering. *Bioinformatics*, 16(8):707–726, 2000.

[46] Russell F. Doolittle. On the trail of protein sequences. *Bioinformatics*, 16(1):24–33, 2000.

[47] Anton J. Enright and Christos A. Ouzounis. Generage: A robust algorithm for sequence clustering and domain detection. *Bioinformatics*, 16(5):451–457, 2000.

[48] Angelo M. Facchiano. Helm: Searching for helix motifs within protein sequences. *Bioinformatics*, 16(3):292–293, 2000.

[49] András Fiser and István Simon. Predicting the oxidation state of cysteines by multiple sequence alignment. *Bioinformatics*, 16(3):251–256, 2000.

[50] A.C. Frank and J.R. Lobry. Oriloc: Prediction of replication boundaries in unannotated bacterial chromosomes. *Bioinformatics*, 16(6):560–561, 2000.

[51] Rainer Fuchs. Analyse this...or: Intelligent help for the rest of us. *Bioinformatics*, 16(6):491–493, 2000.

[52] Terrence S. Furey, Nello Cristianini, Nigel Duffy, David W. Bednarski, Michèl Schummer, and David Haussler. Support vector machine classification and validation of cancer tissue samples using microarray expression data. *Bioinformatics*, 16(10):906–914, 2000.

[53] Mark J. Gibbs, John S. Armstrong, and Adrian J. Gibbs. Sister-scanning: A monte carlo procedure for assessing signals in recombinant sequences. *Bioinformatics*, 16(7):573–582, 2000.

[54] Michael C. Giddings, Olga V. Matveeva, John F. Atkins, and Raymond F. Gesteland. Odnbase — a web database for antisense oligonucleotide effectiveness studies. *Bioinformatics*, 16(9):843–844, 2000.

[55] Robert Giegerich. A systematic approach to dynamic programming in bioinformatics. *Bioinformatics*, 16(8):665–677, 2000.

[56] R. Gilmour. Taxonomic markup language: Applying xml to systematic data. *Bioinformatics*, 16(4):406–407, 2000.

[57] Gustavo Glusman and Doron Lancet. Gestalt: A workbench for automatic integration and visualization of large-scale genomic sequence analyses. *Bioinformatics*, 16(5):482–483, 2000.

[58] T.V. Gnanasekaran, Suraj Peri, A. Arockiasamy, and S. Krishnaswamy. Profiles from structure based sequence alignment of porins can identify β stranded integral membrane proteins. *Bioinformatics*, 16(9):839–842, 2000.

[59] G.H. Gonnet, M.T. Hallett, C. Korostensky, and L. Bernardin. Darwin v. 2.0: An interpreted computer language for the biosciences. *Bioinformatics*, 16(2):101–103, 2000.

[60] Osamu Gotoh. Homology-based gene structure prediction: Simplified matching algorithm using a translated codon (tron) and improved accuracy by allowing for long gaps. *Bioinformatics*, 16(3):190–202, 2000.

[61] Kunchur Guruprasad, Maheshuni S. Prasad, and Gundu R. Kumar. Database of structural motifs in proteins. *Bioinformatics*, 16(4):372–375, 2000.

[62] Bernhard Haubold and Richard R. Hudson. Lian 3.0: Detecting linkage disequilibrium in multilocus data. *Bioinformatics*, 16(9):847–849, 2000.

[63] Ralf Herwig, Armin O. Schmitt, Matthias Steinfath, John O'Brien, Henrik Seidel, Sebastian Meier-Ewert, Hans Lehrach, and Uwe Radelof. Information theoretical probe selection for hybridisation experiments. *Bioinformatics*, 16(10):890–898, 2000.

[64] David Hiscock and Chris Upton. Viral genome database: Storing and analyzing genes and proteins from complete viral genomes. *Bioinformatics*, 16(5):484–485, 2000.

[65] T.C. Hodgman. A historical perspective on gene/protein functional assignment. *Bioinformatics*, 16(1):10–15, 2000.

[66] Liisa Holm and Jong Park. Dalilite workbench for protein structure comparison. *Bioinformatics*, 16(6):566–567, 2000.

[67] Peter M. Hooper, Haiyan Zhang, and David S. Wishart. Prediction of genetic structure in eukaryotic dna using reference point logistic regression and sequence alignment. *Bioinformatics*, 16(5):425–438, 2000.

[68] Yuh-Jyh Hu, Suzanne Sandmeyer, Calvin McLaughlin, and Dennis Kibler. Combinatorial motif analysis and hypothesis generation on a genomic scale. *Bioinformatics*, 16(3):222–232, 2000.

[69] B. Jagla and J. Schuchhardt. Adaptive encoding neural networks for the recognition of human signal peptide cleavage sites. *Bioinformatics*, 16(3):245–250, 2000.

[70] D. Curtis Jamison, James W. Thomas, and Eric D. Green. Comboscreen facilitates the multiplex hybridization-based screening of high-density clone arrays. *Bioinformatics*, 16(8):678–684, 2000.

[71] Lars Juhl Jensen and Steen Knudsen. Automatic discovery of regulatory patterns in promoter regions based on whole cell expression data and functional annotation. *Bioinformatics*, 16(4):326–333, 2000.

[72] George Johnson and Tai T. Wu. Matching amino acid and nucleotide sequences of mouse rheumatoid factor cdrh3-frh4 segments to other mouse antibodies with known specificities. *Bioinformatics*, 16(10):941–943, 2000.

[73] C. Victor Jongeneel. The need for a human gene index. *Bioinformatics*, 16(12):1059–1061, 2000.

[74] Thomas Junier and Marco Pagni. Dotlet: Diagonal plots in a web browser. *Bioinformatics*, 16(2):178–179, 2000.

[75] Peter D. Karp. An ontology for biological function based on molecular interactions. *Bioinformatics*, 16(3):269–285, 2000.

[76] Mukund V. Katti, Meena K. Sakharkar, Prabhakar K. Ranjekar, and Vidya S. Gupta. Tres: Comparative promoter sequence analysis. *Bioinformatics*, 16(8):739–740, 2000.

[77] Toni Kazic. Semiotes: A semantics for sharing. *Bioinformatics*, 16(12):1129–1144, 2000.

[78] Paul Kersey, Henning Hermjakob, and Rolf Apweiler. Varsplic: Alternatively-spliced protein sequences derived from swiss-prot and trembl. *Bioinformatics*, 16(11):1048–1049, 2000.

[79] Junhyong Kim, Etsuko N. Moriyama, Coral G. Warr, Peter J. Clyne, and John R. Carlson. Identification of novel multi-transmembrane proteins from genomic databases using quasi-periodic structural properties. *Bioinformatics*, 16(9):767–775, 2000.

[80] Oliver Kohlbacher and Hans-Peter Lenhof. Ball — rapid software prototyping in computational molecular biology. *Bioinformatics*, 16(9):815–824, 2000.

[81] Ian Korf and Warren Gish. Mpblast: Improved blast performance with multiplexed queries. *Bioinformatics*, 16(11):1052–1053, 2000.

[82] Chantal Korostensky and Gaston H. Gonnet. Using traveling salesman problem algorithms for evolutionary tree construction. *Bioinformatics*, 16(7):619–627, 2000.

[83] Robert Küffner, Ralf Zimmer, and Thomas Lengauer. Pathway analysis in metabolic databases via differential metabolic display (dmd). *Bioinformatics*, 16(9):825–836, 2000.

[84] Alexey Lagunin, Alla Stepanchikova, Dmitrii Filimonov, and Vladimir Poroikov. Pass: Prediction of activity spectra for biologically active substances. *Bioinformatics*, 16(8):747–748, 2000.

[85] Dorothy M. Lang. Net nearest neighbor analysis (nnna) summarizes non-compensated dinucleotides within gene sequences. *Bioinformatics*, 16(3):212–221, 2000.

[86] Weizhong Li, Frederic Pio, Krzysztof Pawlowski, and Adam Godzik. Saturated blast: An automated multiple intermediate sequence search

used to detect distant homology. *Bioinformatics*, 16(12):1105–1110, 2000.

[87] Birong Liao, Walker Hale, Charles B. Epstein, Ronald A. Butow, and Harold R. Garner. Mad: A suite of tools for microarray data management and processing. *Bioinformatics*, 16(10):946–947, 2000.

[88] Pietro Liò and Marina Vannucci. Finding pathogenicity islands and gene transfer events in genome data. *Bioinformatics*, 16(10):932–940, 2000.

[89] Pietro Lio and Marina Vannucci. Wavelet change-point prediction of transmembrane proteins. *Bioinformatics*, 16(4):376–382, 2000.

[90] Robert M. MacCallum, Lawrence A. Kelley, and Michael J.E. Sternberg. Sawted: Structure assignment with text description — enhanced detection of remote homologues with automated swiss-prot annotation comparisons. *Bioinformatics*, 16(2):125–129, 2000.

[91] Michael Z. Man, Xuning Wang, and Yixin Wang. Power_sage: Comparing statistical tests for sage experiments. *Bioinformatics*, 16(11):953–959, 2000.

[92] Elisabetta Manduchi, Gregory R. Grant, Steven E. McKenzie, G. Christian Overton, Saul Surrey, Stoeckert, and Jr. Christian J. Generation of patterns from gene expression data by assigning confidence to differentially expressed genes. *Bioinformatics*, 16(8):685–698, 2000.

[93] Kenneth F. Manly. Mathematica packages for simulation of experimental genetics. *Bioinformatics*, 16(4):408–410, 2000.

[94] Elliott H. Margulies and Jeffrey W. Innis. esage: Managing and analysing data generated with serial analysis of gene expression (sage). *Bioinformatics*, 16(7):650–651, 2000.

[95] Darren Martin and Ed Rybicki. Rdp: Detection of recombination amongst aligned sequences. *Bioinformatics*, 16(6):562–563, 2000.

[96] T. Massingham and N. Goldman. Edible: Experimental design and information calculations in phylogenetics. *Bioinformatics*, 16(3):294–295, 2000.

[97] Chris Mayor, Michael Brudno, Jody R. Schwartz, Alexander Poliakov, Edward M. Rubin, Kelly A. Frazer, Lior S. Pachter, and Inna Dubchak. Vista : Visualizing global dna sequence alignments of arbitrary length. *Bioinformatics*, 16(11):1046–1047, 2000.

[98] Marcella A. McClure. The complexities of genome analysis, the retroid agent perspective. *Bioinformatics*, 16(2):79–95, 2000.

[99] Peter B. McGarvey, Hongzhan Huang, Winona C. Barker, Bruce C. Orcutt, John S. Garavelli, Geetha Y. Srinivasarao, Lai-Su L. Yeh, Chunlin Xiao, and Cathy H. Wu. Pir: A new resource for bioinformatics. *Bioinformatics*, 16(3):290–291, 2000.

[100] Liam J. McGuffin, Kevin Bryson, and David T. Jones. The psipred protein structure prediction server. *Bioinformatics*, 16(4):404–405, 2000.

[101] Gráinne McGuire and Frank Wright. Topal 2.0: Improved detection of mosaic sequences within multiple alignments. *Bioinformatics*, 16(2):130–134, 2000.

[102] Kerstin M.L. Menne, Henning Hermjakob, and Rolf Apweiler. A comparison of signal sequence prediction methods using a test set of signal peptides. *Bioinformatics*, 16(8):741–742, 2000.

[103] Denis Milan, Rachel Hawken, Cédric Cabau, Sophie Leroux, Carine Genet, Yvette Lahbib, Gwenola Tosser, Annie Robic, Francois Hatey, Lee Alexander, Craig Beattie, Larry Schook, Martine Yerle, and Jöel Gellin. Imprh server: An rh mapping server available on the web. *Bioinformatics*, 16(6):558–559, 2000.

[104] Aleksandar Milosavljevic. The economic value of bioinformation. *Bioinformatics*, 16(7):571–572, 2000.

[105] Kenji Mizuguchi and Tom L. Blundell. Analysis of conservation and substitutions of secondary structure elements within protein superfamilies. *Bioinformatics*, 16(12):1111–1119, 2000.

[106] Steffen Möller, Evgenia V. Kriventseva, and Rolf Apweiler. A collection of well characterised integral membrane proteins. *Bioinformatics*, 16(12):1159–1160, 2000.

[107] Burkhard Morgenstern. A space-efficient algorithm for aligning large genomic sequences. *Bioinformatics*, 16(10):948–949, 2000.

[108] János Murvai, Kristian Vlahovicek, and Sándor Pongor. A simple probabilistic scoring method for protein domain identification. *Bioinformatics*, 16(12):1155–1156, 2000.

[109] Pauline C. Ng, Jorja G. Henikoff, and Steven Henikoff. Phat: A transmembrane-specific substitution matrix. *Bioinformatics*, 16(9):760–766, 2000. see Erratum in Bioinformatics, Vol. 17, 2001, No. 3, 290-290.

[110] Tetsuo Nishikawa, Toshio Ota, and Takao Isogai. Prediction whether a human cdna sequence contains initiation codon by combining statistical information and similarity with protein sequences. *Bioinformatics*, 16(11):960–967, 2000. see Erratum in: Bioinformatics, Vol. 17, 2001, No. 3, 290-290.

[111] Tamotsu Noguchi, Kentaro Onizuka, Makoto Ando, Hideo Matsuda, and Yutaka Akiyama. Quick selection of representative protein chain sets based on customizable requirements. *Bioinformatics*, 16(6):520–526, 2000.

[112] Sorinel Adrian Oprisan, Aurel Ardelean, and Petre T. Frangopol. Self-organization and competition in the immune response to cancer invasion: A phase-orientated computational model of oncogenesis. *Bioinformatics*, 16(2):96–100, 2000.

[113] Christos Ouzounis. Two or three myths about bioinformatics. *Bioinformatics*, 16(3):187–189, 2000.

[114] Roderic D.M. Page. Circles: Automating the comparative analysis of rna secondary structure. *Bioinformatics*, 16(11):1042–1043, 2000.

[115] Jong Park, Sabine Dietmann, Andreas Heger, and Liisa Holm. Estimating the significance of sequence order in protein secondary structure and prediction. *Bioinformatics*, 16(11):978–987, 2000.

[116] Jong Park, Liisa Holm, and Cyrus Chothia. Sequence search algorithm assessment and testing toolkit (sat). *Bioinformatics*, 16(2):104–110, 2000.

[117] Jong Park, Liisa Holm, Andreas Heger, and Cyrus Chothia. Rsdb: Representative protein sequence databases have high information content. *Bioinformatics*, 16(5):458–464, 2000.

[118] J.D. Parsons and P. Rodriguez-Tomé. Jesam: Corba software components to create and publish est alignments and clusters. *Bioinformatics*, 16(4):313–325, 2000.

[119] Norman W. Paton, Shakeel A. Khan, Andrew Hayes, Fouzia Moussouni, Andy Brass, Karen Eilbeck, Carole A. Goble, Simon J. Hubbard, and Stephen G. Oliver. Conceptual modelling of genomic information. *Bioinformatics*, 16(6):548–557, 2000.

[120] Hugh-G. Patterton and Steven Graves. Dnassist: The integrated editing and analysis of molecular biology sequences in windows. *Bioinformatics*, 16(7):652–653, 2000.

[121] Graziano Pesole, Sabino Liuni, and Mark D'Souza. Patsearch: A pattern matcher software that finds functional elements in nucleotide and protein sequences and assesses their statistical significance. *Bioinformatics*, 16(5):439–450, 2000.

[122] F. Plewniak, J.D. Thompson, and O. Poch. Ballast: Blast post-processing based on locally conserved segments. *Bioinformatics*, 16(9):750–759, 2000.

[123] M.R. Pocock and T.J.P. Hubbard. A browser for expression data. *Bioinformatics*, 16(4):402–403, 2000.

[124] Martin Prokop, Jirí Damborský, and Jaroslav Koca. Triton: In silico construction of protein mutants and prediction of their activities. *Bioinformatics*, 16(9):845–846, 2000.

[125] Vasilis J. Promponas, Anton J. Enright, Sophia Tsoka, David P. Kreil, Christophe Leroy, Stavros Hamodrakas, Chris Sander, and Christos A. Ouzounis. Cast: An iterative algorithm for the complexity analysis of sequence tracts. *Bioinformatics*, 16(10):915–922, 2000.

[126] Jr. Purdom, P.W., P.G. Bradford, K. Tamura, and S. Kumar. Single column discrepancy and dynamic max-mini optimizations for quickly

finding the most parsimonious evolutionary trees. *Bioinformatics*, 16(2):140–151, 2000.

[127] Abdelkrim Rachedi, Michael Rebhan, and Hong Xue. Gabaagent: A system for integrating data on gaba receptors. *Bioinformatics*, 16(4):301–312, 2000.

[128] Andrew Rambaut. Estimating the rate of molecular evolution: Incorporating non-contemporaneous sequences into maximum likelihood phylogenies. *Bioinformatics*, 16(4):395–399, 2000.

[129] Chenna Ramu, Christine Gemünd, and Toby J. Gibson. Object-oriented parsing of biological databases with python. *Bioinformatics*, 16(7):628–638, 2000.

[130] Francois Rechenmann. From data to knowledge. *Bioinformatics*, 16(5):411–411, 2000.

[131] Knut Reinert, Jens Stoye, and Torsten Will. An iterative method for faster sum-of-pairs multiple sequence alignment. *Bioinformatics*, 16(9):808–814, 2000.

[132] Elena Rivas and Sean R. Eddy. The language of rna: A formal grammar that includes pseudoknots. *Bioinformatics*, 16(4):334–340, 2000.

[133] Elena Rivas and Sean R. Eddy. Secondary structure alone is generally not statistically significant for the detection of noncoding rnas. *Bioinformatics*, 16(7):583–605, 2000.

[134] Richard J. Roberts. The early days of bioinformatics publishing. *Bioinformatics*, 16(1):2–4, 2000.

[135] Marc Robinson-Rechavi and Dorothée Huchon. Rrtree: Relative-rate tests between groups of sequences on a phylogenetic tree. *Bioinformatics*, 16(3):296–297, 2000.

[136] Torbjørn Rognes and Erling Seeberg. Six-fold speed-up of smith-waterman sequence database searches using parallel processing on common microprocessors. *Bioinformatics*, 16(8):699–706, 2000.

[137] Patrick P. Rose and Bette T. Korber. Detecting hypermutations in viral sequences with an emphasis on g $\rightarrow$ a hypermutation. *Bioinformatics*, 16(4):400–401, 2000.

[138] Kim Rutherford, Julian Parkhill, James Crook, Terry Horsnell, Peter Rice, Marie-Adèle Rajandream, and Bart Barrell. Artemis: Sequence visualization and annotation. *Bioinformatics*, 16(10):944–945, 2000.

[139] Derek A. Ruths, Edward S. Chen, and Leland Ellis. Arbor 3d: An interactive environment for examining phylogenetic and taxonomic trees in multiple dimensions. *Bioinformatics*, 16(11):1003–1009, 2000.

[140] Andrey Rzhetsky, Tomohiro Koike, Sergey Kalachikov, Shawn M. Gomez, Michael Krauthammer, Sabina H. Kaplan, Pauline Kra, James J. Russo, and Carol Friedman. A knowledge model for analysis and simulation of regulatory networks. *Bioinformatics*, 16(12):1120–1128, 2000.

[141] Meena K. Sakharkar, Pandjassarame Kangueane, Tong W. Woon, Tin W. Tan, Prasanna R. Kolatkar, Manyuan Long, and Sandro J. de Souza. Ie-kb: Intron exon knowledge base. *Bioinformatics*, 16(12):1151–1152, 2000.

[142] Luis Sánchez-Pulido, Yan P. Yuan, Miguel A. Andrade, and Peer Bork. Nail — network analysis interface for linking hmmer results. *Bioinformatics*, 16(7):656–657, 2000.

[143] David Sankoff. The early introduction of dynamic programming into computational biology. *Bioinformatics*, 16(1):41–47, 2000.

[144] Naoki Sato. Siseq: Manipulation of multiple sequence and large database files for common platforms. *Bioinformatics*, 16(2):180–181, 2000.

[145] C.A.M. Semple, S.W. Morris, D.J. Porteous, and K.L. Evans. In silico identification of transcripts and snps from a region of 4p linked with bipolar affective disorder. *Bioinformatics*, 16(8):735–738, 2000.

[146] Xavier Serra-Hartmann, Xavier Rebordosa, Jaume Piñol, Enrique Querol, and Marc A. Martí-Renom. Asap: Analysis of peptide composition. *Bioinformatics*, 16(12):1153–1154, 2000.

[147] Naomi Siew, Arne Elofsson, Leszek Rychlewski, and Daniel Fischer. Maxssub: An automated measure for the assessment of protein structure prediction quality. *Bioinformatics*, 16(9):776–785, 2000.

[148] Kevin A.T. Silverstein, Alan Kilian, John L. Freeman, James E. Johnson, Ihab A. Awad, and Ernest F. Retzel. Panal: An integrated resource for protein sequence analysis. *Bioinformatics*, 16(12):1157–1158, 2000.

[149] M.M. Soloviev. Detection of a surface-exposed pest like sequence in the metabotropic glutamate receptor mglur1 alpha. *Bioinformatics*, 16(9):837–838, 2000.

[150] F.M. Stefanini and A. Camussi. The reduction of large molecular profiles to informative components using a genetic algorithm. *Bioinformatics*, 16(10):923–931, 2000.

[151] D.L. Steffen, A.E. Levine, S. Yarus, R.A. Baasiri, and D.A. Wheeler. Digital reviews in molecular biology: Approaches to structured digital publication. *Bioinformatics*, 16(7):639–649, 2000.

[152] Robert Stevens, Patricia Baker, Sean Bechhofer, Gary Ng, Alex Jacoby, Norman W. Paton, Carole A. Goble, and Andy Brass. Tambis: Transparent access to multiple bioinformatics information sources. *Bioinformatics*, 16(2):184–186, 2000.

[153] Gary D. Stormo. Dna binding sites: Representation and discovery. *Bioinformatics*, 16(1):16–23, 2000.

[154] Sarah A. Teichmann, Cyrus Chothia, George M. Church, and Jong Park. Fast assignment of protein structures to sequences using the intermediate sequence library pdb-isl. *Bioinformatics*, 16(2):117–124, 2000.

[155] Joseph L. Thorley and Roderic D.M. Page. Radcon: Phylogenetic tree comparison and consensus. *Bioinformatics*, 16(5):486–487, 2000.

[156] Keith Tipton and Sinéad Boyce. History of the enzyme nomenclature system. *Bioinformatics*, 16(1):34–40, 2000.

[157] Edward N. Trifonov. Earliest pages of bioinformatics. *Bioinformatics*, 16(1):5–9, 2000.

[158] Jonathan Usuka, Wei Zhu, and Volker Brendel. Optimal spliced alignment of homologous cdna to a genomic dna template. *Bioinformatics*, 16(3):203–211, 2000.

[159] A.H.C. van Kampen, B.D.C. van Schaik, E. Pauws, E.M.C. Michiels, J.M. Ruijter, H.N. Caron, R. Versteeg, S.H. Heisterkamp, J.A.M. Leunissen, F. Baas, and M. van der Mee. Usage: A web-based approach towards the analysis of sage data. *Bioinformatics*, 16(10):899–905, 2000.

[160] Ana T. Vasconcelos, Marco A. Grivet Mattoso Maia, and Darcy F. de Almeida. Short interrupted palindromes on the extragenic dna of escherichia coli k-12, haemophilus influenzae and neisseria meningitidis. *Bioinformatics*, 16(11):968–977, 2000.

[161] Kristian Vlahovicek and Sándor Pongor. model.it: Building three dimensional dna models from sequence data. *Bioinformatics*, 16(11):1044–1045, 2000.

[162] Eberhard O. Voit and Tomas Radivoyevitch. Biochemical systems analysis of genome-wide expression data. *Bioinformatics*, 16(11):1023–1037, 2000.

[163] Akiyoshi Wada. Bioinformatics – the necessity of the quest for "first principles" in life. *Bioinformatics*, 16(8):663–664, 2000.

[164] Anders Wallqvist, Yoshifumi Fukunishi, Lynne Reed Murphy, Addi Fadel, and Ronald M. Levy. Iterative sequence/secondary structure search for protein homologs: Comparison with amino acid sequence alignments and application to fold recognition in genome databases. *Bioinformatics*, 16(11):988–1002, 2000.

[165] John D. Westbrook and Philip E. Bourne. Star/mmcif: An ontology for macromolecular structure. *Bioinformatics*, 16(2):159–168, 2000.

[166] S.J. Wheelan, A. Marchler-Bauer, and S.H. Bryant. Domain size distributions can predict domain boundaries. *Bioinformatics*, 16(7):613–618, 2000.

[167] Raymond Wheeler and Richard Hughey. Optimizing reduced-space sequence analysis. *Bioinformatics*, 16(12):1082–1090, 2000.

[168] Marty J. Wolf, Simon Easteal, Margaret Kahn, Brendan D. McKay, and Lars S. Jermiin. Trexml: A maximum-likelihood approach for extensive tree-space exploration. *Bioinformatics*, 16(4):383–394, 2000.

[169] Stephen Wooding. Promt: Inferring demographic history from dna sequences. *Bioinformatics*, 16(3):298–299, 2000.

[170] Thomas D. Wu, Craig G. Nevill-Manning, and Douglas L. Brutlag. Fast probabilistic analysis of sequence function using scoring matrices. *Bioinformatics*, 16(3):233–244, 2000.

[171] Guochun Xie, Reynold DeMarco, Richard Blevins, and Yuhong Wang. Storing biological sequence databases in relational form. *Bioinformatics*, 16(3):288–289, 2000.

[172] Dong Xu, Michael A. Unseren, Ying Xu, and Edward C. Uberbacher. Sequence-structure specificity of a knowledge based energy function at the secondary structure level. *Bioinformatics*, 16(3):257–268, 2000.

[173] Ying Xu, Dong Xu, and Harold N. Gabow. Protein domain decomposition using a graph-theoretic approach. *Bioinformatics*, 16(12):1091–1104, 2000. see Erratum in: Bioinformatics, Vol. 17, 2001, No. 3, 290-290.

[174] Mikio Yoshida, Ken-ichiro Fukuda, and Toshihisa Takagi. Pnad-css: A workbench for constructing a protein name abbreviation dictionary. *Bioinformatics*, 16(2):169–175, 2000.

[175] Chang Zhu, Kevin Karplus, Leslie Grate, and Philip Coffino. A homolog of mammalian antizyme is present in fission yeast schizosaccharomyces pombe but not detected in budding yeast saccharomyces cerevisiae. *Bioinformatics*, 16(5):478–481, 2000.

[176] H. Zhu, C.H. Schein, and W. Braun. Masia: Recognition of common patterns and properties in multiple aligned protein sequences. *Bioinformatics*, 16(10):950–951, 2000.

[177] A. Zien, G. Rätsch, S. Mika, B. Schölkopf, T. Lengauer, and K.-R. Müller. Engineering support vector machine kernels that recognize translation initiation sites. *Bioinformatics*, 16(9):799–807, 2000.