References

[1] Alessandro Armando, Silvio Ranise, and Michaël Rusinowitch. A rewriting approach to satisfiability procedures. *Inf. Comput.*, 183(2):140–164, 2003.

[2] Ulrich Berger, Matthias Eberl, and Helmut Schwichtenberg. Term rewriting for normalization by evaluation. *Inf. Comput.*, 183(1):19–42, 2003.

[3] Vincent Danos and Jean-Baptiste Joinet. Linear logic and elementary time. *Inf. Comput.*, 183(1):123–137, 2003.

[4] Georg Gottlob and Christos Papadimitriou. On the complexity of single-rule datalog queries. *Inf. Comput.*, 183(1):104–122, 2003.

[5] Dieter Hofbauer. An upper bound on the derivational complexity of knuth-bendix orderings. *Inf. Comput.*, 183(1):43–56, 2003.

[6] Martin Hofmann. Linear types and non-size-increasing polynomial time computation. *Inf. Comput.*, 183(1):57–85, 2003.

[7] Konstantin Korovin and Andrei Voronkov. Orienting rewrite rules with the knuth-bendix order. *Inf. Comput.*, 183(2):165–186, 2003.

[8] J.Y. Marion. Analysing the implicit complexity of programs. *Inf. Comput.*, 183(1):2–18, 2003.

[9] Frank Neven and Thomas Schwentick. On the power of tree-walking automata. *Inf. Comput.*, 183(1):86–103, 2003.

[10] Michio Oyamaguchi and Yoshikatsu Ohta. The unification problem for confluent right-ground term rewriting systems. *Inf. Comput.*, 183(2):187–211, 2003.

[11] René Vestergaard and James Brotherston. A formalised first-order confluence proof for the λ-calculus using one-sorted variable names. *Inf. Comput.*, 183(2):212–244, 2003.

[12] Jens R. Woinowski. The context-splittable normal form for church-rosser language systems. *Inf. Comput.*, 183(2):245–274, 2003.