References

[1] Javed A. Aslam and Scott E. Decatur. Specification and simulation of statistical query algorithms for efficiency and noise tolerance. *J. Comput. Syst. Sci.*, 56(2):191–208, 1998.

[2] Peter L. Bartlett and Philip M. Long. Prediction, learning, uniform convergence, and scale-sensitive dimensions. *J. Comput. Syst. Sci.*, 56(2):174–190, 1998.

[3] Shai Ben-David and Eli Dichterman. Learning with restricted focus of attention. *J. Comput. Syst. Sci.*, 56(3):277–298, 1998.

[4] Christer Berg and Staffan Ulfberg. A lower bound for perceptrons and an oracle separation of the pp^{PH} hierarchy. *J. Comput. Syst. Sci.*, 56(3):263–271, 1998.

[5] Avrim Blum, Prasad Chalasani, Sally A. Goldman, and Donna K. Slonim. Learning with unreliable boundary queries. *J. Comput. Syst. Sci.*, 56(2):209–222, 1998.

[6] Daoud Bshouty and Nader H. Bshouty. On interpolating arithmetic read-once formulas with exponentiation. *J. Comput. Syst. Sci.*, 56(1):112–124, 1998.

[7] Nader Bshouty and Lisa Hellerstein. Attribute-efficient learning in query and mistake-bound models. *J. Comput. Syst. Sci.*, 56(3):310–319, 1998.

[8] Lin Chen. Optimal circular arc representations: Properties, recognition, and construction. *J. Comput. Syst. Sci.*, 56(3):320–331, 1998.

[9] Pavol Ďuriš and José D.P. Rolim. Lower bounds on the multiparty communication complexity. *J. Comput. Syst. Sci.*, 56(1):90–95, 1998.

[10] Joost Engelfriet and Heiko Vogler. The equivalence of bottom-up and top-down tree-to-graph transducers. *J. Comput. Syst. Sci.*, 56(3):332–356, 1998.

[11] Seymour Ginsburg and X. Sean Wang. Regular sequence operations and their use in database queries. *J. Comput. Syst. Sci.*, 56(1):1–26, 1998.

[12] Lucian Ilie and Arto Salomaa. 2-testability and relabelings produce everything. *J. Comput. Syst. Sci.*, 56(3):253–262, 1998.

[13] Jeong Han Kim and James R. Roche. Covering cubes by random half cubes, with applications to binary neural networks. *J. Comput. Syst. Sci.*, 56(2):223–252, 1998.

[14] Juha Kortelainen. Remarks about commutative context-free languages. *J. Comput. Syst. Sci.*, 56(1):125–129, 1998.

[15] Richard E. Ladner, Anthony LaMarca, and Ewan Tempero. Counting protocols for reliable end-to-end transmission. *J. Comput. Syst. Sci.*, 56(1):96–111, 1998.

[16] Francesco Mario Malvestuto and Marina Moscarini. A fast algorithm for query optimization in universal-relation databases. *J. Comput. Syst. Sci.*, 56(3):299–309, 1998.

[17] Giovanni Manzini and Luciano Margara. Invertible linear cellular automata over z_m: Algorithmic and dynamical aspects. *J. Comput. Syst. Sci.*, 56(1):60–67, 1998.

[18] Sanguthevar Rajasekaran and Shibu Yooseph. Tal recognition in $o(m(n^2))$ time. *J. Comput. Syst. Sci.*, 56(1):83–89, 1998.

[19] Rajeev Rastogi, Sharad Mehrotra, Yuri Breitbart, Henry F. Korth, and Avi Silberschatz. On correctness of nonserializable executions. *J. Comput. Syst. Sci.*, 56(1):68–82, 1998.

[20] Dana Ron, Yoram Singer, and Naftali Tishby. On the learnability and usage of acyclic probabilistic finite automata. *J. Comput. Syst. Sci.*, 56(2):133–152, 1998.

[21] Giorgio Satta. Trading independent for synchronized parallelism in finite copying parallel rewriting systems. *J. Comput. Syst. Sci.*, 56(1):27–45, 1998.

[22] Arun Sharma. A note on batch and incremental learnability. *J. Comput. Syst. Sci.*, 56(3):272–276, 1998.

[23] V. Vovk. A game of prediction with expert advice. *J. Comput. Syst. Sci.*, 56(2):153–173, 1998.

[24] Andreas Weber. Transforming a single-valued transducer into a mealey machine. *J. Comput. Syst. Sci.*, 56(1):46–59, 1998.