References

[1] Noga Alon and Michael Krivelevich. Testing k-colorability. *SIAM J. Disc. Math.*, 15(2):211–227, 2002.

[2] Noga Alon, Benny Sudakov, and Uri Zwick. Constructing worst case instances for semidefinite programming based approximation algorithms. *SIAM J. Disc. Math.*, 15(1):58–72, 2001-2002.

[3] Yaagoub A. Ashir and Iain A. Stewart. Fault-tolerant embeddings of hamiltonian circuits in k-ary n-cubes. *SIAM J. Disc. Math.*, 15(3):317–328, 2002.

[4] Hans-Jürgen Bandelt and Victor Chepoi. Graphs with connected medians. *SIAM J. Disc. Math.*, 15(2):268–282, 2002.

[5] Alexander Barg. On some polynomials related to weight enumerators of linear codes. *SIAM J. Disc. Math.*, 15(2):155–164, 2002.

[6] Piotr Berman, Bhaskar DasGupta, and S. Muthukrishnan. Exact size of binary space partitionings and improved rectangle tiling algorithms. *SIAM J. Disc. Math.*, 15(2):252–267, 2002.

[7] T. Blackmore and G.H. Norton. Determining when the absolute state complexity of a hermitian code achieves its dlp bound. *SIAM J. Disc. Math.*, 15(1):14–40, 2001-2002.

[8] Oleg V. Borodin and Douglas R. Woodall. Cyclic colorings of 3-polytopes with large maximum face size. *SIAM J. Disc. Math.*, 15(2):143–154, 2002.

[9] Eddie Cheng and Sven de Vries. On the facet-inducing antiweb-wheel inequalities for stable set polytopes. *SIAM J. Disc. Math.*, 15(4):470–487, 2002.

[10] Gérard Cornuéjols and Bertrand Guenin. Ideal binary clutters, connectivity, and a conjecture of seymour. *SIAM J. Disc. Math.*, 15(3):329–352, 2002.

[11] Jitender S. Deogun and Dieter Kratsch. Dominating pair graphs. *SIAM J. Disc. Math.*, 15(3):353–366, 2002.

[12] Jean-Paul Doignon and Samuel Fiorini. Facets of the weak order polytope derived from the induced partition projection. *SIAM J. Disc. Math.*, 15(1):112–121, 2001-2002.

[13] Danny Dolev, Yuval Harari, Nathan Linial, Noam Nisan, and Michal Parnas. Neighborhood preserving hashing and approximate queries. *SIAM J. Disc. Math.*, 15(1):73–85, 2001-2002.

[14] Ding-Zhu Du, Frank K. Hwang, Xiaohua Jia, and Hung Q. Ngo. Optimal consecutive-k-out-of-n: g cycle for $n \leq 2k+1$. *SIAM J. Disc. Math.*, 15(3):305–316, 2002.

[15] M.A. Fiol and E. Garriga. An algebraic characterization of completely regular codes in distance-regular graphs. *SIAM J. Disc. Math.*, 15(1):1–13, 2001-2002.

[16] Peter C. Fishburn and Paul E. Wright. Interference patterns in regular graphs with bijective colorings. *SIAM J. Disc. Math.*, 15(3):382–402, 2002.

[17] Josselin Garnier and Leila Kallel. Efficiency of local search with multiple local optima. *SIAM J. Disc. Math.*, 15(1):122–141, 2001-2002.

[18] Michel X. Goemans, Maurice Queyranne, Andreas S. Schulz, Martin Skutella, and Yaoguang Wang. Single machine scheduling with release dates. *SIAM J. Disc. Math.*, 15(2):165–192, 2002.

[19] Michał Hańćkowiak, Michał Karoński, and Alessandro Panconesi. On the distributed complexity of computing maximal matchings. *SIAM J. Disc. Math.*, 15(1):41–57, 2001-2002.

[20] Refael Hassin and Shlomi Rubinstein. Robust matchings. *SIAM J. Disc. Math.*, 15(4):530–537, 2002.

[21] Teresa W. Haynes, Sandra M. Hedetniemi, Stephen T. Hedetniemi, and Michael A. Henning. Domination in graphs applied to electric power networks. *SIAM J. Disc. Math.*, 15(4):519–529, 2002.

[22] Iiro Honkala and Andrew Klapper. Multicovering bounds from relative covering radii. *SIAM J. Disc. Math.*, 15(2):228–234, 2002.

[23] Sun-Yuan Hsieh, Chin-Wen Ho, Tsan-Sheng Hsu, Ming-Tat Ko, and Gen-Huey Chen. Characterization of efficiently parallel solvable problems on distance-hereditary graphs. *SIAM J. Disc. Math.*, 15(4):488–518, 2002.

[24] Bruce Kitchens. Multidimensional convolutional codes. *SIAM J. Disc. Math.*, 15(3):367–381, 2002.

[25] Sandi Klavžar and Henry Martyn Mulder. Partial cubes and crossing graphs. *SIAM J. Disc. Math.*, 15(2):235–251, 2002.

[26] D. Kratsch and L. Stewart. Approximating bandwidth by mixing layouts of interval graphs. *SIAM J. Disc. Math.*, 15(4):435–449, 2002.

[27] David Peleg and Avishai Wool. How to be an efficient snoop, or the probe complexity of quorum systems. *SIAM J. Disc. Math.*, 15(3):416–433, 2002.

[28] Kalle Ranto. Infinite families of 3-designs from z_4-goethals codes with block size 8. *SIAM J. Disc. Math.*, 15(3):289–304, 2002.

[29] Romeo Rizzi. Finding 1-factors in bipartite regular graphs and edge-coloring bipartite graphs. *SIAM J. Disc. Math.*, 15(3):283–288, 2002.

[30] Joe Sawada. A fast algorithm for generating nonisomorphic chord diagrams. *SIAM J. Disc. Math.*, 15(4):546–561, 2002.

[31] Alexander Schrijver. Strong t-perfection of bad-k_4-free graphs. *SIAM J. Disc. Math.*, 15(3):403–415, 2002.

[32] Andreas S. Schulz and Martin Skutella. Scheduling unrelated machines by randomized rounding. *SIAM J. Disc. Math.*, 15(4):450–469, 2002.

[33] Michael A. Steel and László A. Székely. Inverting random functions ii: Explicit bounds for discrete maximum likelihood estimation, with applications. *SIAM J. Disc. Math.*, 15(4):562–575, 2002.

[34] Biing-Feng Wang. Finding a 2-core of a tree in linear time. *SIAM J. Disc. Math.*, 15(2):193–210, 2002.

[35] Hong Wang. On covering a bipartite graph with cycles. *SIAM J. Disc. Math.*, 15(1):86–96, 2001-2002.

[36] Wei-Fan Wang and Ko-Wei Lih. Choosability and edge choosability of planar graphs without intersecting triangles. *SIAM J. Disc. Math.*, 15(4):538–545, 2002.

[37] Alexander Z. Zelikovsky and Ion I. Mandoiu. Practical approximation algorithms for zero- and bounded-skew trees. *SIAM J. Disc. Math.*, 15(1):97–111, 2001-2002.