References

[1] Gary Benson. A space efficient algorithm for finding the best nonoverlapping alignment score. *Theor. Comput. Sci.*, 145(1-2):357–369, 1995.

[2] Ofer Biran, Shlomo Moran, and Shmuel Zaks. Tight bounds on the round complexity of distributed 1-solvable tasks. *Theor. Comput. Sci.*, 145(1-2):271–290, 1995.

[3] G. Braga, G. Cattaneo, P. Flocchini, and C. Quaranta Vogliotti. Fundamental study: Pattern growth in elementary cellular automata. *Theor. Comput. Sci.*, 145(1-2):1–26, 1995.

[4] G. Braga, G. Cattaneo, P. Flocchini, and C. Quaranta Vogliotti. Pattern growth in elementary cellular automata. *Theor. Comput. Sci.*, 145(1-2):1–26, 1995.

[5] Y. Breitbart, H. Hunt III, and D. Rosenkrantz. On the size of binary decision diagrams representing boolean functions. *Theor. Comput. Sci.*, 145(1-2):45–69, 1995.

[6] Jiazhen Cai and Robert Paige. Using multiset discrimination to solve language processing problems without hashing. *Theor. Comput. Sci.*, 145(1-2):189–228, 1995.

[7] Nadia Creignou. The class of problems that are linearly equivalent to satisfiability or a uniform method for proving np-completeness. *Theor. Comput. Sci.*, 145(1-2):111–145, 1995.

[8] Krzysztof Diks, Evangelos Kranakis, Adam Malinowski, and Andrzej Pelc. Anonymous wireless rings. *Theor. Comput. Sci.*, 145(1-2):95–109, 1995.

[9] F. Drewes, A. Habel, H.-J. Kreowski, and S. Taubenberger. Generating self-affine fractals by collage grammars. *Theor. Comput. Sci.*, 145(1-2):159–187, 1995.

[10] Seymour Ginsburg and Katsumi Tanaka. Interval queries on object histories. *Theor. Comput. Sci.*, 145(1-2):291–316, 1995.

[11] Lane A. Hemaspaandra and Zhigen Jiang. p-selectivity: Intersections and indices. *Theor. Comput. Sci.*, 145(1-2):371–380, 1995.

[12] B. Jamison and S. Olariu. A linear-time recognition algorithm for p_4-reducible graphs. *Theor. Comput. Sci.*, 145(1-2):329–344, 1995.

[13] Ker-I Ko. A polynomial-time computable curve whose interior has a nonrecursive measure. *Theor. Comput. Sci.*, 145(1-2):241–270, 1995.

[14] Ernst L. Leiss. Implicit language equations: Existence and uniqueness of solutions. *Theor. Comput. Sci.*, 145(1-2):71–93, 1995.

[15] Oded Maler. A decomposition theorem for probabilistic transition systems. *Theor. Comput. Sci.*, 145(1-2):391–396, 1995.

[16] Martin Middendorf. On finding minimal, maximal, and consistent sequences over a binary alphabet. *Theor. Comput. Sci.*, 145(1-2):317–327, 1995.

[17] Christophe Reutenauer and Marcel Paul Schützenberger. Variétés et fonctions rationnelles. *Theor. Comput. Sci.*, 145(1-2):229–240, 1995.

[18] G. Srikrishna and C. Pandu Rangan. Optimal parallel algorithms for path problems on planar graphs. *Theor. Comput. Sci.*, 145(1-2):27–43, 1995.

[19] Iain A. Stewart. Complete problems for monotone np. *Theor. Comput. Sci.*, 145(1-2):147–157, 1995.

[20] Shang-Hua Teng. Independent sets versus perfect matchings. *Theor. Comput. Sci.*, 145(1-2):381–390, 1995.

[21] Liang Zhang and Zhonghui Shen. Completion of recognizable bifix codes. *Theor. Comput. Sci.*, 145(1-2):345–355, 1995.