References

[1] Matthias Baaz, Alexander Leitsch, and Richard Zach. Completeness of a first-order temporal logic with time-gaps. *Theor. Comput. Sci.*, 160(1-2):241–270, 1996.

[2] Piero A. Bonatti and Thomas Eiter. Querying disjunctive databases through nonmonotonic logics. *Theor. Comput. Sci.*, 160(1-2):321–363, 1996.

[3] Bruno Courcelle. The monadic second-order logic of graphs x: Linear orderings. *Theor. Comput. Sci.*, 160(1-2):87–143, 1996.

[4] Arnaud Durand and Solomampionona Ranaivoson. First-order spectra with one binary predicate. *Theor. Comput. Sci.*, 160(1-2):305–320, 1996.

[5] Michael Kaminski and Chung Kei Wong. The power of the "always" operator in first-order temporal logic. *Theor. Comput. Sci.*, 160(1-2):271–281, 1996.

[6] Roger D. Maddux. Relation-algebraic semantics. *Theor. Comput. Sci.*, 160(1-2):1–85, 1996.

[7] Kim Marriott and Martin Odersky. Negative boolean constraints. *Theor. Comput. Sci.*, 160(1-2):365–380, 1996.

[8] Enrico Tronci. Equational programming in λ-calculus via sl-systems: Part 1. *Theor. Comput. Sci.*, 160(1-2):145–184, 1996.

[9] Enrico Tronci. Equational programming in λ-calculus via sl-systems: Part 2. *Theor. Comput. Sci.*, 160(1-2):185–216, 1996.

[10] Chris Tuijn and Marc Gyssens. Cgood, a categorical graph-oriented object data model. *Theor. Comput. Sci.*, 160(1-2):217–239, 1996.

[11] Susumu Yamasaki. Sldnf resolution with non-safe rule and fixpoint semantics for general logic programs. *Theor. Comput. Sci.*, 160(1-2):283–303, 1996.