References

[1] Toshiyasu Arai and Grigori Mints. Extended normal form theorems for logical proofs from axioms. *Theor. Comput. Sci.*, 232(1-2):121–132, 2000.

[2] M.W. Bunder. Proof finding algorithms for implicational logics. *Theor. Comput. Sci.*, 232(1-2):165–186, 2000.

[3] James L. Caldwell, Ian P. Gent, and Judith Underwood. Search algorithms in type theory. *Theor. Comput. Sci.*, 232(1-2):55–90, 2000.

[4] Iliano Cervesato, Joshua S. Hodas, and Frank Pfenning. Efficient resource management for linear logic proof search. *Theor. Comput. Sci.*, 232(1-2):133–163, 2000.

[5] Amy Felty. The calculus of constructions as a framework for proof search with set variable instantiation. *Theor. Comput. Sci.*, 232(1-2):187–229, 2000.

[6] D. Galmiche. Connection methods in linear logic and proof nets construction. *Theor. Comput. Sci.*, 232(1-2):231–272, 2000.

[7] Didier Galmiche and David J. Pym. Proof-search in type-theoretic languages: An introduction. *Theor. Comput. Sci.*, 232(1-2):5–53, 2000.

[8] Raymond McDowell and Dale Miller. Cut-elimination for a logic with definitions and induction. *Theor. Comput. Sci.*, 232(1-2):91–119, 2000.

[9] Gopalan Nadathur. Correspondences between classical, intuitionistic and uniform provability. *Theor. Comput. Sci.*, 232(1-2):273–298, 2000.

[10] Eike Ritter, David Pym, and Lincoln Wallen. On the intuitionistic force of classical search. *Theor. Comput. Sci.*, 232(1-2):299–333, 2000.