References

[1] Andris Ambainis, Kalvis Apsītis, Rūsiņš Freivalds, and Carl H. Smith. Hierarchies of probabilistic and team fin-learning. *Theor. Comput. Sci.*, 261(1):91–117, 2001.

[2] John Case, Sanjay Jain, and Arun Sharma. Synthesizing noise-tolerant language learners. *Theor. Comput. Sci.*, 261(1):31–56, 2001.

[3] Fan Chung and Ronald Graham. Dynamic location problems with limited look-ahead. *Theor. Comput. Sci.*, 261(2):213–226, 2001.

[4] Thomas Erlebach, Peter Rossmanith, Hans Stadtherr, Angelika Steger, and Thomas Zeugmann. Learning one-variable pattern languages very efficiently on average, in parallel, and by asking queries. *Theor. Comput. Sci.*, 261(1):119–156, 2001.

[5] Leonid Gurvits. A note on a scale-sensitive dimension of linear bounded functionals in banach spaces. *Theor. Comput. Sci.*, 261(1):81–90, 2001.

[6] Kazuo Iwama, Eiji Miyano, Satoshi Tajima, and Hisao Tamaki. Efficient randomized routing algorithms on the two-dimensional mesh of buses. *Theor. Comput. Sci.*, 261(2):227–239, 2001.

[7] Sanjay Jain, Steffen Lange, and Jochen Nessel. On the learnability of recursively enumerable languages from good examples. *Theor. Comput. Sci.*, 261(1):3–29, 2001.

[8] Dongsoo S. Kim and Ding-Zhu Du. Multirate multicast switching networks. *Theor. Comput. Sci.*, 261(2):241–251, 2001.

[9] Marcos Kiwi, Daniel A. Spielman, and Shang-Hua Teng. Min-max-boundary domain decomposition. *Theor. Comput. Sci.*, 261(2):253–266, 2001.

[10] Alejandro López-Ortiz and Sven Schuierer. The ultimate strategy to search on m rays? *Theor. Comput. Sci.*, 261(2):267–295, 2001.

[11] Chi-Jen Lu. An exact characterization of symmetric functions in $qac^0[2]$. *Theor. Comput. Sci.*, 261(2):297–303, 2001.

[12] Wolfgang Maass. On the relevance of time in neural computation and learning. *Theor. Comput. Sci.*, 261(1):157–178, 2001.

[13] Steffen Reith and Klaus W. Wagner. On boolean lowness and boolean highness. *Theor. Comput. Sci.*, 261(2):305–321, 2001.

[14] Eiji Takimoto, Akira Maruoka, and Volodya Vovk. Predicting nearly as well as the best pruning of a decision tree through dynamic programming scheme. *Theor. Comput. Sci.*, 261(1):179–209, 2001.

[15] Kuo-Hui Tsai, Da-Wei Wang, and Frank Hwang. Lower bounds for wide-sense nonblocking clos network. *Theor. Comput. Sci.*, 261(2):323–328, 2001.

[16] V. Vovk. Probability theory for the brier game. *Theor. Comput. Sci.*, 261(1):57–79, 2001.