References

[1] Martín Abadi and Véronique Cortier. Deciding knowledge in security protocols under equational theories. *Theor. Comput. Sci.*, 367(1-2):2–32, 2006.

[2] Michael Backes, Anupam Datta, Ante Derek, John C. Mitchell, and Mathieu Turuani. Compositional analysis of contract-signing protocols. *Theor. Comput. Sci.*, 367(1-2):33–56, 2006.

[3] Frederick Butler, Iliano Cervesato, Aaron D. Jaggard, Andre Scedrov, and Christopher Walstad. Formal analysis of kerberos 5. *Theor. Comput. Sci.*, 367(1-2):57–87, 2006.

[4] Carlos Caleiro, Luca Viganò, and David Basin. On the semantics of alice&bob specifications of security protocols. *Theor. Comput. Sci.*, 367(1-2):88–122, 2006.

[5] Marco Carpentieri. A genetic system based on simulated crossover of sequences of two-bit genes. *Theor. Comput. Sci.*, 367(3):324–335, 2006.

[6] Konstantinos Chatzikokolakis and Catuscia Palamidessi. Probable innocence revisited. *Theor. Comput. Sci.*, 367(1-2):123–138, 2006.

[7] Jian Cheng Lv, Zhang Yi, and K.K. Tan. Global convergence of oja's pca learning algorithm with a non-zero-approaching adaptive learning rate. *Theor. Comput. Sci.*, 367(3):286–307, 2006.

[8] C.J.F. Cremers, S. Mauw, and E.P. de Vink. Injective synchronisation: An extension of the authentication hierarchy. *Theor. Comput. Sci.*, 367(1-2):139–161, 2006.

[9] Santiago Escobar, Catherine Meadows, and José Meseguer. A rewriting-based inference system for the nrl protocol analyzer and its meta-logical properties. *Theor. Comput. Sci.*, 367(1-2):162–202, 2006.

[10] Oleg Izmerly and Tal Mor. Chosen ciphertext attacks on lattice-based public key encryption and modern (non-quantum) cryptography in a quantum environment. *Theor. Comput. Sci.*, 367(3):308–323, 2006.

[11] Faisal Shah Khan and Marek Perkowski. Synthesis of multi-qudit hybrid and d-valued quantum logic circuits by decomposition. *Theor. Comput. Sci.*, 367(3):336–346, 2006. see Erratum in Theor. Comput. Sci., Vol. 403, 2008, No. 1, 130-131.

[12] Yiguang Liu, Zhisheng You, and Liping Cao. A concise functional neural network computing the largest modulus eigenvalues and their corresponding eigenvectors of a real skew matrix. *Theor. Comput. Sci.*, 367(3):273–285, 2006.

[13] Sebastian Nanz and Chris Hankin. A framework for security analysis of mobile wireless networks. *Theor. Comput. Sci.*, 367(1-2):203–227, 2006.

[14] R. Ramanujam and S.P. Suresh. A (restricted) quantifier elimination for security protocols. *Theor. Comput. Sci.*, 367(1-2):228–256, 2006.

[15] Graham Steel. Formal analysis of pin block attacks. *Theor. Comput. Sci.*, 367(1-2):257–270, 2006.