References

[1] Haitao Jiang, Daming Zhu, and Binhai Zhu. A $(1+\epsilon)$-approximation algorithm for sorting by short block-moves. *Theor. Comput. Sci.*, 439:1–8, 2012.

[2] Marcin Kamiński, Paul Medvedev, and Martin Milanič. Complexity of independent set reconfigurability problems. *Theor. Comput. Sci.*, 439:9–15, 2012.

[3] H.L.M. Kerivin, M. Lacroix, and A.R. Mahjoub. On the complexity of the eulerian closed walk with precedence path constraints problem. *Theor. Comput. Sci.*, 439:16–29, 2012.

[4] István Miklós and Eric Tannier. Approximating the number of double cut-and-join scenarios. *Theor. Comput. Sci.*, 439:30–40, 2012.

[5] Stavros D. Nikolopoulos, Leonidas Palios, and Charis Papadopoulos. A fully dynamic algorithm for the recognition of p_4-sparse graphs. *Theor. Comput. Sci.*, 439:41–57, 2012.

[6] Helmut Prodinger. Approximate counting with m counters: A detailed analysis. *Theor. Comput. Sci.*, 439:58–68, 2012.

[7] Qin Xin, Fredrik Manne, Yan Zhang, and Xin Wang. Almost optimal distributed m2m multicasting in wireless mesh networks. *Theor. Comput. Sci.*, 439:69–82, 2012.