References

[1] Parosh Aziz Abdulla, Yu-Fang Chen, Lukáš Holík, and Tomáš Vojnar. Mediating for reduction (on minimizing alternating büchi automata). *Theor. Comput. Sci.*, 552:26–43, 2014.

[2] Fei Chen, Kwok-wo Wong, Xiaofeng Liao, and Tao Xiang. Period distribution of generalized discrete arnold cat map. *Theor. Comput. Sci.*, 552:13–25, 2014.

[3] Graham Cormode and Hossein Jowhari. A second look at counting triangles in graph streams. *Theor. Comput. Sci.*, 552:44–51, 2014.

[4] Ying-Jun Guo and Zhi-Xiong Wen. Automaticity of the hankel determinants of difference sequences of the thue-morse sequence. *Theor. Comput. Sci.*, 552:1–12, 2014.

[5] Tomoko Izumi, Keigo Kinpara, Taisuke Izumi, and Koichi Wada. Space-efficient self-stabilizing counting population protocols on mobile sensor networks. *Theor. Comput. Sci.*, 552:99–108, 2014.

[6] István Miklós, Sándor Z. Kiss, and Eric Tannier. Counting and sampling scj small parsimony solutions. *Theor. Comput. Sci.*, 552:83–98, 2014.

[7] Zevi Miller, Dan Pritikin, and I.H. Sudborough. Embedding multidimensional grids into optimal hypercubes. *Theor. Comput. Sci.*, 552:52–82, 2014.

[8] Chen Yuan and Haibin Kan. A note on sparse solutions of sparse linear systems. *Theor. Comput. Sci.*, 552:109–111, 2014.