References

[1] Serge Abiteboul and Richard Hull. Restructuring hierarchical database objects. *Theor. Comput. Sci.*, 62:3–38, 1988.

[2] Paolo Atzeni and D. Stott Parker. Set containment inference and syllogisms. *Theor. Comput. Sci.*, 62:39–65, 1988.

[3] Samuel R. Buss and György Turán. Resolution proofs of generalized pigeonhole principles. *Theor. Comput. Sci.*, 62:311–317, 1988.

[4] Edward P.F. Chan and Héctor J. Hernández. On the desirability of γ-acyclic bcnf database schemes. *Theor. Comput. Sci.*, 62:67–104, 1988.

[5] Villiam Geffert. A representation of recursively enumerable languages by two homomorphisms and a quotient. *Theor. Comput. Sci.*, 62:235–249, 1988.

[6] V.S. Lakshmanan. Split-freedom and mvd-intersection: A new characterization of multivalued dependencies having conflict-free covers. *Theor. Comput. Sci.*, 62:105–122, 1988.

[7] Nancy Lynch and Michael Merritt. Introduction to the theory of nested transactions. *Theor. Comput. Sci.*, 62:123–185, 1988.

[8] Christoph Meinel. The power of nondeterminism in polynomial-size bounded-width branching programs. *Theor. Comput. Sci.*, 62:319–325, 1988.

[9] Nageswara S.V. Rao, S.S. Iyengar, and R.L. Kashyap. An average-case analysis of mat and inverted file. *Theor. Comput. Sci.*, 62:251–266, 1988.

[10] Domenico Saccà and Carlo Zaniolo. The generalized counting method for recursive logic queries. *Theor. Comput. Sci.*, 62:187–220, 1988.

[11] Kai Salomaa. A pumping result for 2-context-free languages. *Theor. Comput. Sci.*, 62:267–287, 1988.

[12] Dirk Van Gucht. Interaction-free multivalued dependency sets. *Theor. Comput. Sci.*, 62:221–233, 1988.

[13] Thomas Zeugmann. On the power of recursive optimizers. *Theor. Comput. Sci.*, 62:289–310, 1988.